



- ▶ All-aluminum coils
- ▶ Fully insulated galvanized steel cabinets
- ▶ Factory installed & shipped with flow controls
- ▶ Multi-speed fan motors
- ▶ Approved for manufactured/mobile housing
- ▶ Cooling & Heat Pump Compatible

Model Number	Capacity (Tons)	Dimensions (Inches) H x W x D	Motor Type	Flow Control	Electric Heat
--------------	-----------------	-------------------------------	------------	--------------	---------------

A4AH4 - MULTI-POSITION AIR HANDLERS

A4AH4E24A1B60A	1.5 - 3.0	45 x 18.5 x 21.1	CTM	FCCV	Field Installed
A4AH4E30A1B30A	1.5 - 3.0	46.8 x 18.5 x 21.1	CTM	TXV	Field Installed
A4AH4E36A1C30A	2.5 - 4.0	51.3 x 23.5 x 21.1	CTM	TXV	Field Installed
A4AH4E42B1C30A	3.0 - 4.0	51.3 x 23.5 x 21.1	CTM	TXV	Field Installed
A4AH4E48B1C30A	3.5 - 5.0	57.4 x 23.5 x 21.1	CTM	TXV	Field Installed
A4AH4E60B1C30A	3.5 - 5.0	57.4 x 23.5 x 21.1	CTM	TXV	Field Installed

A4AH5 - AIR HANDLERS

A4AH5E19A1B30A	1.0 - 2.0	45.2 x 18.5 x 21.1	CTM	TXV	Field Installed
A4AH5E31A1B30A	1.5 - 3.0	46.8 x 18.5 x 21.1	CTM	TXV	Field Installed
A4AH5E43A1C30A	3.0 - 4.0	51.3 x 23.5 x 21.1	CTM	TXV	Field Installed
A4AH5E49A1C30A	3.5 - 5.0	57.4 x 23.5 x 21.1	CTM	TXV	Field Installed
A4AH5E61A1C30A	3.5 - 5.0	57.4 x 23.5 x 21.1	CTM	TXV	Field Installed
A4AH5V24A1B30A	1.5 - 2.5	46.8 x 18.5 x 21.1	Variable Speed	TXV	Field Installed
A4AH5V30A1B30A	2.0 - 3.0	46.8 x 18.5 x 21.1	Variable Speed	TXV	Field Installed
A4AH5V36A1C30A	2.0 - 3.5	51.3 x 23.5 x 21.1	Variable Speed	TXV	Field Installed
A4AH5V42A1C30A	3.0 - 5.0	51.3 x 23.5 x 21.1	Variable Speed	TXV	Field Installed
A4AH5V48A1C30A	3.0 - 5.0	57.4 x 23.5 x 21.1	Variable Speed	TXV	Field Installed
A4AH5V60A1C30A	3.5 - 5.0	57.4 x 23.5 x 21.1	Variable Speed	TXV	Field Installed

TMM4 AIR HANDLERS

TMM4B0A18S21SA	1.5	36.5 x 20.5 x 15	PSC	Orifice	Field Installed
TMM4B0A24S21SA	2.0	36.5 x 20.5 x 15	PSC	Orifice	Field Installed
TMM4B0B30S21SA	2.5	39.5 x 22 x 19	PSC	Orifice	Field Installed
TMM4B0B36S31SA	3.0	39.5 x 22 x 19	PSC	Orifice	Field Installed

TMM5 AIR HANDLERS

TMM5B0A24M21SA	2.0	36.5 x 20.5 x 15	CTM	TXV	Field Installed
TMM5B0B30M21SA	2.5	39.5 x 22 x 19	CTM	TXV	Field Installed
TMM5B0B36M31SA	3.0	39.5 x 22 x 19	CTM	TXV	Field Installed



- ▶ All-aluminum coils
- ▶ Fully insulated galvanized steel cabinets
- ▶ Factory installed & shipped with flow controls
- ▶ Multi-speed fan motors
- ▶ Approved for manufactured/mobile housing
- ▶ Cooling & Heat Pump Compatible

Model Number	Capacity (Tons)	Dimensions (Inches) H x W x D	Motor Type	Flow Control	Electric Heat
A5AHV AIR HANDLERS ✱					
A5AHV003A1B30A	1.5 - 2.5	46.8 x 18.5 x 21.1	Variable Speed	TXV	Field Installed
A5AHV004A1D30A	2.0 - 3.5	51.4 x 23.5 x 21.1	Variable Speed	TXV	Field Installed
A5AHV006A1D30A	3.0 - 5.0	57.4 x 23.5 x 21.1	Variable Speed	TXV	Field Installed
A5AHV007A1D30A	3.5 - 5.0	57.4 x 23.5 x 21.1	Variable Speed	TXV	Field Installed

These select models are compatible with R-454B refrigerant

5 YEAR WARRANTY

Limited functional parts warranty¹

10 YEAR WARRANTY

Functional parts warranty with product registration¹

¹ Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 855-260-2975, otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on americanstandardair.com. Ask your dealer for full warranty information at time of purchase. Warranties are for residential and multi-family use only, some exclusions may apply. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.