FFAP-015Z-TFC-072

HCFC, R-22, 50Hz, 3- Phase, 200/220 V

Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	16.6
Unit Length (in):	24.1
Unit Width (in):	18.3
Ship Weight (lbs):	110.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.375 SWEAT
Suction Connection Size (in)/Type:	0.875 SWEAT
Discharge Line Size(in):	0.375
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	25

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	11.4
Compressor:	ZS09KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	57.0
Compressor LRA - Half winding:	
Compressor RLA:	8.0
UL:	None
UL File #:	None
UL Guide Card:	None
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	25-Aug-2017	Return Gas Temp. (°F):	40
Compressor:	ZS09KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	13642	Air Flow Rate (CFM)	890

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
0	5,560	103.3	13.3	5.7
5	6,300	104.6	14.6	6.4
10	7,050	106.0	16.0	7.0
15	7,830	107.5	17.5	7.6
20	8,650	109.1	19.1	8.1
25	9,500	110.8	20.8	8.6

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.