FFAP-017Z-CFV-072

HCFC, R-22, 60Hz, 1- Phase, 208/230 V

Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	16.6
Unit Length (in):	24.1
Unit Width (in):	18.3
Ship Weight (lbs):	114.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.375
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	25

Electrical

Max Fuse Size:	25
Min Circuit Ampacity:	17.2
Compressor:	ZS11KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	55.0
Compressor LRA - Half winding:	
Compressor RLA:	12.6
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	06-Dec-2017	Return Gas Temp. (°F):	40
Compressor:	ZS11KAE-PFV-118 x 1	Subcooling (°F):	5
Performance No:	13422	Air Flow Rate (CFM)	1070

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
10	9,910	110.2	20.2	6.8
15	11,000	112.0	22.0	7.3
20	12,100	113.9	23.9	7.7
25	13,300	116.0	26.0	8.1
30	14,500	118.1	28.1	8.5
35	15,800	120.3	30.3	8.9
40	17,200	122.7	32.7	9.3
45	18,600	125.1	35.1	9.6

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.