FFAP-020Z-TFC-072

HCFC, R-22, 50Hz, 3- Phase, 200/220 V

Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	18.9
Unit Length (in):	25.0
Unit Width (in):	34.1
Ship Weight (lbs):	180.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.375 SWEAT
Suction Connection Size (in)/Type:	0.875 SWEAT
Discharge Line Size(in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	25

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	13.9
Compressor:	ZS13KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	59.0
Compressor LRA - Half winding:	
Compressor RLA:	9.7
UL:	None
UL File #:	None
UL Guide Card:	None
Amps Per Motor:	0.6
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	25-Aug-2017	Return Gas Temp. (°F):	40
Compressor:	ZS13KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	13704	Air Flow Rate (CFM)	1485

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
0	7,560	104.8	14.8	5.2
5	8,560	106.3	16.3	5.8
10	9,590	107.9	17.9	6.4
15	10,600	109.5	19.5	6.9
20	11,700	111.3	21.3	7.4
25	12,900	113.1	23.1	7.8

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.