FFAP-022Z-CFV-072

HCFC, R-22, 60Hz, 1- Phase, 208/230 V

Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	19.0
Unit Length (in):	25.0
Unit Width (in):	34.0
Ship Weight (lbs):	183.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	25

Electrical

Max Fuse Size:	35
Min Circuit Ampacity:	22.4
Compressor:	ZS15KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	68.0
Compressor LRA - Half winding:	
Compressor RLA:	15.7
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	25-Aug-2017			Return Gas Temp. (°F):	40
Compressor:	ZS15KAE-PFV-118	x	1	Subcooling (°F):	5
Performance No:	13737			Air Flow Rate (CFM)	2170

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
0	10,500	107.0	17.0	5.2
5	11,900	108.6	18.6	5.8
10	13,400	110.4	20.4	6.4
15	14,800	112.2	22.2	6.9
20	16,300	114.2	24.2	7.3
25	17,900	116.3	26.3	7.7

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.