FFAP-022Z-TFC-072

HCFC, R-22, 50Hz, 3- Phase, 200/220 V

Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	18.9
Unit Length (in):	25.1
Unit Width (in):	34.0
Ship Weight (lbs):	186.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.375 SWEAT
Suction Connection Size (in)/Type:	0.875 SWEAT
Discharge Line Size(in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	25

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	16.1
Compressor:	ZS15KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	59.0
Compressor LRA - Half winding:	
Compressor RLA:	10.6
UL:	None
UL File #:	None
UL Guide Card:	None
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	25-Aug-2017	Return Gas Temp. (°F):	40
Compressor:	ZS15KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	13721	Air Flow Rate (CFM)	1810

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
0	8,840	105.6	15.6	5.3
5	10,000	107.1	17.1	6.0
10	11,200	108.8	18.8	6.5
15	12,400	110.5	20.5	7.0
20	13,700	112.3	22.3	7.5
25	15,000	114.2	24.2	7.9

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.