FFAP-030Z-CFV-072

HCFC, R-22, 60Hz, 1- Phase, 208/230 V

Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	19.0
Unit Length (in):	25.0
Unit Width (in):	34.1
Ship Weight (lbs):	183.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	25

Electrical

Max Fuse Size:	40
Min Circuit Ampacity:	25.3
Compressor:	ZS19KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	75.0
Compressor LRA - Half winding:	
Compressor RLA:	18.0
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	06-Dec-2017	Return Gas Temp. (°F):	40
Compressor:	ZS19KAE-PFV-118 x 1	Subcooling (°F):	5
Performance No:	13432	Air Flow Rate (CFM)	2170

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
0	12,200	103.9	13.9	5.5
5	13,900	105.3	15.3	6.3
10	15,500	106.7	16.7	6.9
15	17,200	108.3	18.3	7.4
20	19,000	109.9	19.9	7.9
25	20,900	111.5	21.5	8.4
30	22,900	113.3	23.3	8.8
35	25,000	115.1	25.1	9.3
40	27,200	117.0	27.0	9.7
45	29,600	119.0	29.0	10.3

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.