FFAP-040Z-CFV-071

HCFC, R-22, 60Hz, 1- Phase, 208/230 V

Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	26.8
Unit Length (in):	28.2
Unit Width (in):	44.1
Ship Weight (lbs):	322.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	1/2 S
Suction Connection Size (in)/Type:	1-1/8 S
Discharge Line Size(in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	42

Electrical

Max Fuse Size:	50
Min Circuit Ampacity:	33.1
Compressor:	ZS26KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	104.0
Compressor LRA - Half winding:	
Compressor RLA:	23.6
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	12-Dec-2017			Return Gas Temp. (°F):	40
Compressor:	ZS26KAE-PFV-118	x	1	Subcooling (°F):	5
Performance No:	14069			Air Flow Rate (CFM)	4240

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
0	18,600	100.7	10.7	5.2
5	21,100	101.7	11.7	5.9
10	23,600	102.9	12.9	6.5
15	26,300	104.1	14.1	7.1
20	29,000	105.4	15.4	7.7
25	32,000	106.7	16.7	8.2

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.