FFAP-042Z-CFV-071

HCFC, R-22, 60Hz, 1- Phase, 208/230 V

Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	26.6
Unit Length (in):	28.2
Unit Width (in):	44.1
Ship Weight (lbs):	325.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.5 SWEAT
Suction Connection Size (in)/Type:	1.125 SWEAT
Discharge Line Size(in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	42

Electrical

Max Fuse Size:	60
Min Circuit Ampacity:	38.9
Compressor:	ZS33KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	146.0
Compressor LRA - Half winding:	
Compressor RLA:	28.2
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	12-Dec-2017	Return Gas Temp. (°F):	40
Compressor:	ZS33KAE-PFV-118 x 1	Subcooling (°F):	5
Performance No:	14072	Air Flow Rate (CFM)	4240

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
0	22,800	103.0	13.0	5.4
5	25,800	104.3	14.3	6.1
10	28,900	105.7	15.7	6.7
15	32,100	107.2	17.2	7.2
20	35,400	108.8	18.8	7.8
25	38,900	110.4	20.4	8.3

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.