FFAP-050Z-CFV-071

HCFC, R-22, 60Hz, 1- Phase, 208/230 V

Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	26.8
Unit Length (in):	28.2
Unit Width (in):	44.1
Ship Weight (lbs):	320.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	1/2 S
Suction Connection Size (in)/Type:	1-1/8 S
Discharge Line Size(in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	64

Electrical

Max Fuse Size:	70
Min Circuit Ampacity:	43.4
Compressor:	ZS38K4E-PFV-250
Compressor LRA - Low:	
Compressor LRA - High:	169.0
Compressor LRA - Half winding:	
Compressor RLA:	31.8
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	25-Aug-2017			Return Gas Temp. (°F):	40
Compressor:	ZS38K4E-PFV-250	x	1	Subcooling (°F):	5
Performance No:	13865			Air Flow Rate (CFM)	4240

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
10	32,500	107.8	17.8	7.4
15	35,800	109.5	19.5	7.9
20	39,300	111.2	21.2	8.3
25	43,000	113.0	23.0	8.6

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.