FFAP-A18Z-CFV-072

HFC, R-134a, 60Hz, 1-Phase, 208/230V

Availability: Custom US OEM Or Wholesaler

Mechanical		Electrical	
Unit Height (in):	23.2	**Max Fuse Size:**	25
Unit Length (in):	24.3	**Min Circuit Ampacity:**	17.1
Unit Width (in):	24.1	**Compressor:**	ZS11KAE-PFV-118
Ship Weight (lbs):	.0	**Compressor LRA - Low:**	
Condenser Type:	Air	**Compressor LRA - High:**	55
CopeVap Water Storage:		**Compressor LRA - Half winding:**	
Liquid Connection Size (in)/Type:	0.375 SWEAT	**Compressor RLA**	12.6
Suction Connection Size (in)/Type:	0.875 SWEAT	**UL:**	Recognized
Discharge Line Size(in):	0.5	**UL File #:**	SA633
Water Inlet (in):		**UL Guide Card:**	LZFE2
Water Outlet (in):			
Oil Type:	POE	**Amps Per Motor:**	1.1
Oil Recharge Amount (oz):	25	**Fan Motor Quantity:**	1

Performance

Release Date:	18-Dec-2024	**Return Gas Temp. (°F):**	40
Compressor:	ZS11KAE-PFV-118 x 1	**Subcooling (°F):**	5
Performance No:	45578	**Air Flow Rate (CFM):**	1197

90 °F Ambient Air Temperature

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
Evap Temp(°F)	**Unit Capacity (BTU/hr)**	**Cond. Temp.(°F)**	**Temp. Diff.(°F)**	**EER(BTU/wh)**
-5	4,210	96.6	6.6	4.7
0	4,770	97.5	7.5	5.1
5	5,390	98.4	8.4	5.7

10	6,080	99.4	9.4	6.2
15	6,830	100.5	10.5	6.9
20	7,650	101.6	11.6	7.5
25	8,540	102.9	12.9	8.3