FPAK-012Z-CFV-072

HFC, R-134a, 60Hz, 1- Phase, 208/230 V

Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	16.6
Unit Length (in):	24.0
Unit Width (in):	17.1
Ship Weight (lbs):	103.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.375 SWEAT
Suction Connection Size (in)/Type:	0.625 SWEAT
Discharge Line Size(in):	0.375
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	25

Electrical

Max Fuse Size:	25
Min Circuit Ampacity:	16.9
Compressor:	ZS11KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	55.0
Compressor LRA - Half winding:	
Compressor RLA:	12.6
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	26-Jul-2013	Return Gas Temp. (°F):	40
Compressor:	ZS11KAE-PFV-118 x 1	Subcooling (°F):	5
Performance No:	8901	Air Flow Rate (CFM)	650

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
0	4,730	109.7	19.7	5.1
5	5,300	111.6	21.6	5.5
10	5,920	113.6	23.6	5.9
15	6,560	115.7	25.7	6.2
20	7,250	117.9	27.9	6.7
25	7,980	120.2	30.2	7.1

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.