FPAK-013Z-CFV-072

HFC, R-134a, 60Hz, 1- Phase, 208/230 V

Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	16.6
Unit Length (in):	24.1
Unit Width (in):	18.3
Ship Weight (lbs):	114.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.375 SWEAT
Suction Connection Size (in)/Type:	0.875 SWEAT
Discharge Line Size(in):	0.375
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	25

Electrical

Max Fuse Size:	35
Min Circuit Ampacity:	21.0
Compressor:	ZS15KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	68.0
Compressor LRA - Half winding:	
Compressor RLA:	15.7
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	26-Jul-2013	Return Gas Temp. (°F):	40
Compressor:	ZS15KAE-PFV-118 x 1	Subcooling (°F):	5
Performance No:	8903	Air Flow Rate (CFM)	1070

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
0	6,640	106.2	16.2	5.3
5	7,470	107.7	17.7	5.8
10	8,360	109.4	19.4	6.2
15	9,300	111.2	21.2	6.7
20	10,300	113.0	23.0	7.2
25	11,400	115.0	25.0	7.7

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.