# FPAK-015Z-TFC-072

HFC, R-134a, 60Hz, 3- Phase, 208/230 V

**Availability :** **Standard US Wholesaler**

## Mechanical

| | |
|---|---|
| Unit Height (in): | 16.6 |
| Unit Length (in): | 24.1 |
| Unit Width (in): | 18.3 |
| Ship Weight (lbs): | 117.0 |
| Condensor Type: | Air |
| CopeVap Water Storage: | NA |
| Liquid Connection Size (in)/Type: | 0.375 SWEAT |
| Suction Connection Size (in)/Type: | 0.875 SWEAT |
| Discharge Line Size(in): | 0.375 |
| Water Inlet (in): | |
| Water Outlet (in): | |
| Oil Type: | POE |
| Oil Recharge Amount (oz): | 25 |

## Electrical

| | |
|---|---|
| Max Fuse Size: | 30 |
| Min Circuit Ampacity: | 18.5 |
| Compressor: | ZS19KAE-TF5-118 |
| Compressor LRA - Low: | |
| Compressor LRA - High: | 73.0 |
| Compressor LRA - Half winding: | |
| Compressor RLA: | 13.7 |
| UL: | Listed |
| UL File #: | SA633 |
| UL Guide Card: | LZFE |
| Amps Per Motor: | |
| Fan Motor Quantity: | 1 |

## Air - Cooled Unit Performance

| | | | |
|---|---|---|---|
| Release Date: | 26-Jul-2013 | Return Gas Temp. (°F): | 40 |
| Compressor: | ZS19KAE-TF5-118 x 1 | Subcooling (°F): | 5 |
| Performance No: | 8905 | Air Flow Rate (CFM) | 1070 |

### 90°F Ambient Air Temperature

| Evap Temp (°F) | Unit Capacity (Btu/hr) | Cond. Temp. (°F) | Temp. Diff. (°F) | EER (Btu/Wh): |
|---|---|---|---|---|
| 0 | 7,410 | 108.0 | 18.0 | 5.3 |
| 5 | 8,330 | 109.7 | 19.7 | 5.7 |
| 10 | 9,310 | 111.5 | 21.5 | 6.2 |
| 15 | 10,300 | 113.4 | 23.4 | 6.6 |
| 20 | 11,500 | 115.5 | 25.5 | 7.1 |
| 25 | 12,600 | 117.6 | 27.6 | 7.5 |



Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.