FPAK-020Z-TFC-072

HFC, R-134a, 60Hz, 3- Phase, 208/230 V

Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	19.0
Unit Length (in):	25.0
Unit Width (in):	34.1
Ship Weight (lbs):	220.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	42

Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	21.8
Compressor:	ZS21KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	93.0
Compressor LRA - Half winding:	
Compressor RLA:	15.2
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	26-Jul-2013			Return Gas Temp. (°F):	40
Compressor:	ZS21KAE-TF5-118	x	1	Subcooling (°F):	5
Performance No:	8907			Air Flow Rate (CFM)	2470

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
0	10,000	107.0	17.0	5.4
5	11,300	108.5	18.5	5.9
10	12,600	110.2	20.2	6.4
15	14,000	112.0	22.0	6.9
20	15,500	113.9	23.9	7.4
25	17,200	115.9	25.9	8.0

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.