XFAP-045Z-TFC-081

HCFC, R-22, 60Hz, 3- Phase, 208/230 V

Availability : **Custom US OEM Or Wholesaler**

Mechanical

Unit Height (in):	48.9
Unit Length (in):	40.6
Unit Width (in):	17.2
Ship Weight (lbs):	333.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.5 SWEAT
Suction Connection Size (in)/Type:	0.875 SWEAT
Discharge Line Size(in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	42

Electrical

Max Fuse Size:	50
Min Circuit Ampacity:	30.0
Compressor:	ZS33KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	114.0
Compressor LRA - Half winding:	
Compressor RLA:	22.3
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	13-Oct-2015	Return Gas Temp. (°F):	40
Compressor:	ZS33KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	9438	Air Flow Rate (CFM)	4100

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
15	32,100	107.0	17.0	9.0
20	35,500	108.6	18.6	9.6
25	39,000	110.2	20.2	10.2

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.