

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	KW*	FLA	FLA	FLA	MCA	MOP
DHC0907W	575/3/60	2	5.8	41.0	2	0.33	0.67	1	3.5	5.0	-	-	-	-	-	19.3	25
											-	-	-	3.5	-	22.8	25
											-	-	-	-	1.3	20.6	25
											-	-	-	3.5	1.3	24.1	25
											EH*D-7M10	10.0	9.6	-	-	19.3	25
														3.5	-	22.8	25
														-	1.3	20.6	25
														3.5	1.3	24.3	25
											EH*D-7M15	15.0	14.4	-	-	24.3	25
														3.5	-	28.7	30
														-	1.3	25.9	30
														3.5	1.3	30.3	35
											EH*D-7M20	20.0	19.2	-	-	30.3	35
														3.5	-	34.7	35
														-	1.3	31.9	35
														3.5	1.3	36.3	40
											EH*D-7M30	30.0	28.9	-	-	42.3	45
														3.5	-	46.7	50
														-	1.3	44.0	45
														3.5	1.3	48.3	50
											EH*D-7M45	45.0	43.3	-	-	60.4	70
														3.5	-	64.8	70
														-	1.3	62.0	70
														3.5	1.3	66.4	70
DHC1023D	208/230/3/60	2	14.1	120	2	0.33	2.0	1	2.4	8.0	-	-	-	-	-	43.7/43.7	50/50
											-	-	-	9.6/8.7	-	53.3/52.4	60/60
											-	-	-	-	3.3/3.0 (2.4)	47.0/46.7	60/60
											-	-	-	9.6/8.7	3.3/3.0 (2.4)	56.6/55.4	60/60
											EH*D-3M10	7.5/10.0	20.8/24.1	-	-	43.7/43.7	50/50
														9.6/8.7	-	53.3/52.4	60/60
														-	3.3/3.0 (2.4)	47.0/46.7	60/60
														9.6/8.7	3.3/3.0 (2.4)	56.6/55.4	60/60
											EH*D-3M15	11.3/15.0	31.3/36.1	-	-	49.1/55.1	50/60
														9.6/8.7	-	61.1/66.0	70/70
														-	3.3/3.0 (2.4)	53.2/58.9	60/60
														9.6/8.7	3.3/3.0 (2.4)	65.2/69.7	70/70
											EH*D-3M20	15.0/20.0	41.7/48.1	-	-	62.1/70.1	70/80
														9.6/8.7	-	74.1/81.0	80/90
														-	3.3/3.0 (2.4)	66.3/73.9	70/80
														9.6/8.7	3.3/3.0 (2.4)	78.3/84.8	80/90
											EH*D-3M30	22.5/30.0	62.5/72.2	-	-	88.2/100	90/110
														9.6/8.7	-	100/111	110/125
														-	3.3/3.0 (2.4)	92.3/104	100/110
														9.6/8.7	3.3/3.0 (2.4)	104/115	110/125
											EH*D-3M45	33.8/45.0	93.8/108	-	-	127/145	150/150
														9.6/8.7	-	139/156	150/175
														-	3.3/3.0 (2.4)	131/149	150/150
														9.6/8.7	3.3/3.0 (2.4)	143/160	150/175

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	KW*	FLA	FLA	FLA	MCA	MOP
DHC1023L	208/230/3/60	2	14.1	120	2	0.33	2.0	1	2.4	8.0	-	-	-	-	-	43.7/43.7	50/50
											-	-	-	9.6/8.7	-	53.3/52.4	60/60
											-	-	-	-	3.3/3.0 (2.4)	47.0/46.7	60/60
											-	-	-	9.6/8.7	3.3/3.0 (2.4)	56.6/55.4	60/60
											EH*D-3M10	7.5/10.0	20.8/24.1	-	-	43.7/43.7	50/50
														9.6/8.7	-	53.3/52.4	60/60
														-	3.3/3.0 (2.4)	47.0/46.7	60/60
														9.6/8.7	3.3/3.0 (2.4)	56.6/55.4	60/60
											EH*D-3M15	11.3/15.0	31.3/36.1	-	-	49.1/55.1	50/60
														9.6/8.7	-	61.1/66.0	70/70
														-	3.3/3.0 (2.4)	53.2/58.9	60/60
														9.6/8.7	3.3/3.0 (2.4)	65.2/69.7	70/70
											EH*D-3M20	15.0/20.0	41.7/48.1	-	-	62.1/70.1	70/80
														9.6/8.7	-	74.1/81.0	80/90
														-	3.3/3.0 (2.4)	66.3/73.9	70/80
														9.6/8.7	3.3/3.0 (2.4)	78.3/84.8	80/90
											EH*D-3M30	22.5/30.0	62.5/72.2	-	-	88.2/100	90/110
														9.6/8.7	-	100/111	110/125
														-	3.3/3.0 (2.4)	92.3/104	100/110
														9.6/8.7	3.3/3.0 (2.4)	104/115	110/125
											EH*D-3M45	33.8/45.0	93.8/108	-	-	127/145	150/150
														9.6/8.7	-	139/156	150/175
														-	3.3/3.0 (2.4)	131/149	150/150
														9.6/8.7	3.3/3.0 (2.4)	143/160	150/175
DHC1023W	208/230/3/60	2	14.1	120	2	0.33	2.0	1	3.5	10.9	-	-	-	-	-	46.6/46.6	60/60
											-	-	-	9.6/8.7	-	56.2/55.3	70/60
											-	-	-	-	3.3/3.0 (2.4)	49.9/49.6	60/60
											-	-	-	9.6/8.7	3.3/3.0 (2.4)	59.5/58.3	70/70
											EH*D-3M10	7.5/10.0	20.8/24.1	-	-	46.6/46.6	60/60
														9.6/8.7	-	56.2/55.3	70/60
														-	3.3/3.0 (2.4)	49.9/49.6	60/60
														9.6/8.7	3.3/3.0 (2.4)	59.5/58.3	70/70
											EH*D-3M15	11.3/15.0	31.3/36.1	-	-	52.7/58.7	60/60
														9.6/8.7	-	64.7/69.6	70/70
														-	3.3/3.0 (2.4)	56.9/62.5	60/70
														9.6/8.7	3.3/3.0 (2.4)	68.9/73.4	70/80
											EH*D-3M20	15.0/20.0	41.7/48.1	-	-	65.7/73.8	70/80
														9.6/8.7	-	77.7/84.6	80/90
														-	3.3/3.0 (2.4)	69.9/77.5	70/80
														9.6/8.7	3.3/3.0 (2.4)	81.9/88.4	90/90
											EH*D-3M30	22.5/30.0	62.5/72.2	-	-	91.8/104	100/110
														9.6/8.7	-	104/115	110/125
														-	3.3/3.0 (2.4)	96.0/108	100/110
														9.6/8.7	3.3/3.0 (2.4)	108/118	110/125
											EH*D-3M45	33.8/45.0	93.8/108	-	-	131/149	150/150
														9.6/8.7	-	143/160	150/175
														-	3.3/3.0 (2.4)	135/153	150/175
														9.6/8.7	3.3/3.0 (2.4)	147/164	150/175

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	KW*	FLA	FLA	FLA	MCA	MOP
DHC1024D	460/3/60	2	6.4	55.1	2	0.33	0.85	1	2.4	5.4	-	-	-	-	-	21.5	25
											-	-	-	4.3	-	25.8	30
											-	-	-	-	1.2 (1.0)	22.7	25
											-	-	-	4.3	1.2 (1.0)	27.0	30
											EH*D-4M10	10.0	12.0	-	-	21.8	25
														4.3	-	27.2	30
														-	1.2 (1.0)	23.3	25
														4.3	1.2 (1.0)	28.7	30
											EH*D-4M15	15.0	18.0	-	-	29.3	30
														4.3	-	34.7	35
														-	1.2 (1.0)	30.8	35
														4.3	1.2 (1.0)	36.2	40
											EH*D-4M20	20.0	24.1	-	-	36.8	40
														4.3	-	42.2	45
														-	1.2 (1.0)	38.3	40
														4.3	1.2 (1.0)	43.7	45
											EH*D-4M30	30.0	36.1	-	-	51.9	60
														4.3	-	57.2	60
														-	1.2 (1.0)	53.4	60
														4.3	1.2 (1.0)	58.7	60
											EH*D-4M45	45.0	54.1	-	-	74.4	80
														4.3	-	79.8	80
														-	1.2 (1.0)	75.9	80
														4.3	1.2 (1.0)	81.3	90
DHC1024L	460/3/60	2	6.4	55.1	2	0.33	0.85	1	2.4	5.4	-	-	-	-	-	21.5	25
											-	-	-	4.3	-	25.8	30
											-	-	-	-	1.2 (1.0)	22.7	25
											-	-	-	4.3	1.2 (1.0)	27.0	30
											EH*D-4M10	10.0	12.0	-	-	21.8	25
														4.3	-	27.2	30
														-	1.2 (1.0)	23.3	25
														4.3	1.2 (1.0)	28.7	30
											EH*D-4M15	15.0	18.0	-	-	29.3	30
														4.3	-	34.7	35
														-	1.2 (1.0)	30.8	35
														4.3	1.2 (1.0)	36.2	40
											EH*D-4M20	20.0	24.1	-	-	36.8	40
														4.3	-	42.2	45
														-	1.2 (1.0)	38.3	40
														4.3	1.2 (1.0)	43.7	45
											EH*D-4M30	30.0	36.1	-	-	51.9	60
														4.3	-	57.2	60
														-	1.2 (1.0)	53.4	60
														4.3	1.2 (1.0)	58.7	60
											EH*D-4M45	45.0	54.1	-	-	74.4	80
														4.3	-	79.8	80
														-	1.2 (1.0)	75.9	80
														4.3	1.2 (1.0)	81.3	90

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	KW*	FLA	FLA	FLA	MCA	MOP
DHC1024W	460/3/60	2	6.4	55.1	2	0.33	0.9	1	3.5	7.2	-	-	-	-	-	23.3	30
											-	-	-	4.3	-	27.6	35
											-	-	-	-	1.2 (1.0)	24.5	30
											-	-	-	4.3	1.2 (1.0)	28.8	35
											EH*D-4M10	10.0	12.0	-	-	24.0	30
														4.3	-	29.4	35
														-	1.2 (1.0)	25.5	30
														4.3	1.2 (1.0)	30.9	35
											EH*D-4M15	15.0	18.0	-	-	31.6	35
														4.3	-	36.9	40
														-	1.2 (1.0)	33.1	35
														4.3	1.2 (1.0)	38.4	40
											EH*D-4M20	20.0	24.1	-	-	39.1	40
														4.3	-	44.4	45
														-	1.2 (1.0)	40.6	45
														4.3	1.2 (1.0)	45.9	50
											EH*D-4M30	30.0	36.1	-	-	54.1	60
														4.3	-	59.5	60
														-	1.2 (1.0)	55.6	60
														4.3	1.2 (1.0)	61.0	70
											EH*D-4M45	45.0	54.1	-	-	76.7	80
														4.3	-	82.0	90
														-	1.2 (1.0)	78.2	80
														4.3	1.2 (1.0)	83.5	90
DHC1027D	575/3/60	2	5.1	41.0	2	0.33	0.67	1	2.4	4.0	-	-	-	-	-	16.9	20
											-	-	-	3.5	-	20.4	25
											-	-	-	-	1.3	18.2	20
											-	-	-	3.5	1.3	21.7	25
											EH*D-7M10	10.0	9.6	-	-	17.0	20
														3.5	-	21.4	25
														-	1.3	18.7	20
														3.5	1.3	23.0	25
											EH*D-7M15	15.0	14.4	-	-	23.0	25
														3.5	-	27.4	30
														-	1.3	24.7	25
														3.5	1.3	29.0	30
											EH*D-7M20	20.0	19.2	-	-	29.1	30
														3.5	-	33.4	35
														-	1.3	30.7	35
														3.5	1.3	35.1	40
											EH*D-7M30	30.0	28.9	-	-	41.1	45
														3.5	-	45.5	50
														-	1.3	42.7	45
														3.5	1.3	47.1	50
											EH*D-7M45	45.0	43.3	-	-	59.1	60
														3.5	-	63.5	70
														-	1.3	60.8	70
														3.5	1.3	65.1	70

Electrical Data

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	KW*	FLA	FLA	FLA	MCA	MOP
DHC1027L	575/3/60	2	5.1	41.0	2	0.33	0.67	1	2.4	4.0	-	-	-	-	-	16.9	20
											-	-	-	3.5	-	20.4	25
											-	-	-	-	1.3	18.2	20
											-	-	-	3.5	1.3	21.7	25
											EH*D-7M10	10.0	9.6	-	-	17.0	20
														3.5	-	21.4	25
														-	1.3	18.7	20
														3.5	1.3	23.0	25
											EH*D-7M15	15.0	14.4	-	-	23.0	25
														3.5	-	27.4	30
														-	1.3	24.7	25
														3.5	1.3	29.0	30
											EH*D-7M20	20.0	19.2	-	-	29.1	30
														3.5	-	33.4	35
														-	1.3	30.7	35
														3.5	1.3	35.1	40
											EH*D-7M30	30.0	28.9	-	-	41.1	45
														3.5	-	45.5	50
														-	1.3	42.7	45
														3.5	1.3	47.1	50
											EH*D-7M45	45.0	43.3	-	-	59.1	60
														3.5	-	63.5	70
														-	1.3	60.8	70
														3.5	1.3	65.1	70
DHC1027W	575/3/60	2	5.1	41.0	2	0.33	0.67	1	3.5	5.0	-	-	-	-	-	17.9	20
											-	-	-	3.5	-	21.4	25
											-	-	-	-	1.3	19.2	20
											-	-	-	3.5	1.3	22.7	25
											EH*D-7M10	10.0	9.6	-	-	18.3	20
														3.5	-	22.7	25
														-	1.3	19.9	20
														3.5	1.3	24.3	25
											EH*D-7M15	15.0	14.4	-	-	24.3	25
														3.5	-	28.7	30
														-	1.3	25.9	30
														3.5	1.3	30.3	35
											EH*D-7M20	20.0	19.2	-	-	30.3	35
														3.5	-	34.7	35
														-	1.3	31.9	35
														3.5	1.3	36.3	40
											EH*D-7M30	30.0	28.9	-	-	42.3	45
														3.5	-	46.7	50
														-	1.3	44.0	45
														3.5	1.3	48.3	50
											EH*D-7M45	45.0	43.3	-	-	60.4	70
														3.5	-	64.8	70
														-	1.3	62.0	70
														3.5	1.3	66.4	70

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply				
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	KW*	FLA	FLA	FLA	MCA	MOP			
DHC1203D	208/230/3/60	2	15.4	156	2	0.33	2.0	1	2.4	8.0	-	-	-	-	-	46.6/46.6	60/60			
											-	-	-	9.6/8.7	-	56.2/55.3	70/70			
											-	-	-	-	3.3/3.0 (2.4)	49.9/49.6	60/60			
											-	-	-	9.6/8.7	3.3/3.0 (2.4)	59.5/58.3	70/70			
											EH*D-3M10	7.5/10.0	20.8/24.1	-	-	46.6/46.6	60/60			
														9.6/8.7	-	56.2/55.3	70/70			
														-	3.3/3.0 (2.4)	49.9/49.6	60/60			
														9.6/8.7	3.3/3.0 (2.4)	59.5/58.3	70/70			
														EH*D-3M15	11.3/15.0	31.3/36.1	-	-	49.1/55.1	60/60
																	9.6/8.7	-	61.1/66.0	70/70
											-	3.3/3.0 (2.4)	53.2/58.9				60/60			
											9.6/8.7	3.3/3.0 (2.4)	65.2/69.7				70/70			
											EH*D-3M20	15.0/20.0	41.7/48.1	-	-	62.1/70.1	70/80			
														9.6/8.7	-	74.1/81.0	80/90			
														-	3.3/3.0 (2.4)	66.3/73.9	70/80			
														9.6/8.7	3.3/3.0 (2.4)	78.3/84.8	80/90			
														EH*D-3M30	22.5/30.0	62.5/72.2	-	-	88.2/100	90/110
																	9.6/8.7	-	100/111	110/125
											-	3.3/3.0 (2.4)	92.3/104				100/110			
											9.6/8.7	3.3/3.0 (2.4)	104/115				110/125			
											EH*D-3M45	33.8/45.0	93.8/108	-	-	127/145	150/150			
														9.6/8.7	-	139/156	150/175			
														-	3.3/3.0 (2.4)	131/149	150/150			
														9.6/8.7	3.3/3.0 (2.4)	143/160	150/175			
											EH*D-3M60	45.1/60.0	125/144	-	-	166/154	175/175			
														9.6/8.7	-	178/165	200/175			
														-	3.3/3.0 (2.4)	171/158	175/175			
														9.6/8.7	3.3/3.0 (2.4)	183/169	200/175			
DHC1203L	208/230/3/60	2	15.4	156	2	0.33	2.0	1	3.5	10.9	-	-	-	-	-	49.5/49.5	60/60			
											-	-	-	9.6/8.7	-	59.1/58.2	70/70			
											-	-	-	-	3.3/3.0 (2.4)	52.8/52.5	60/60			
											-	-	-	9.6/8.7	3.3/3.0 (2.4)	62.4/61.2	70/70			
											EH*D-3M10	7.5/10.0	20.8/24.1	-	-	49.5/49.5	60/60			
														9.6/8.7	-	59.1/58.2	70/70			
														-	3.3/3.0 (2.4)	52.8/52.5	60/60			
														9.6/8.7	3.3/3.0 (2.4)	62.4/61.2	70/70			
														EH*D-3M15	11.3/15.0	31.3/36.1	-	-	52.7/58.7	60/60
																	9.6/8.7	-	64.7/69.6	70/70
											-	3.3/3.0 (2.4)	56.9/62.5				60/70			
											9.6/8.7	3.3/3.0 (2.4)	68.9/73.4				70/80			
											EH*D-3M20	15.0/20.0	41.7/48.1	-	-	65.7/73.8	70/80			
														9.6/8.7	-	77.7/84.6	80/90			
														-	3.3/3.0 (2.4)	69.9/77.5	70/80			
														9.6/8.7	3.3/3.0 (2.4)	81.9/88.4	90/90			
														EH*D-3M30	22.5/30.0	62.5/72.2	-	-	91.8/104	100/110
																	9.6/8.7	-	104/115	110/125
											-	3.3/3.0 (2.4)	96.0/108				100/110			
											9.6/8.7	3.3/3.0 (2.4)	108/118				110/125			
											EH*D-3M45	33.8/45.0	93.8/108	-	-	131/149	150/150			
														9.6/8.7	-	143/160	150/175			
														-	3.3/3.0 (2.4)	135/153	150/175			
														9.6/8.7	3.3/3.0 (2.4)	147/164	150/175			
											EH*D-3M60	45.1/60.0	125/144	-	-	170/158	175/175			
														9.6/8.7	-	182/169	200/200			
														-	3.3/3.0 (2.4)	174/162	175/175			
														9.6/8.7	3.3/3.0 (2.4)	186/173	200/200			

Electrical Data

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	KW*	FLA	FLA	FLA	MCA	MOP
DHC1203W	208/230/3/60	2	15.4	156	2	0.33	2.0	1	3.5	10.9	-	-	-	-	-	49.5/49.5	60/60
											-	-	-	9.6/8.7	-	59.1/58.2	70/70
											-	-	-	-	3.3/3.0 (2.4)	52.8/52.5	60/60
											-	-	-	9.6/8.7	3.3/3.0 (2.4)	62.4/61.2	70/70
											EH*D-3M10	7.5/10.0	20.8/24.1	-	-	49.5/49.5	60/60
														9.6/8.7	-	59.1/58.2	70/70
														-	3.3/3.0 (2.4)	52.8/52.5	60/60
														9.6/8.7	3.3/3.0 (2.4)	62.4/61.2	70/70
											EH*D-3M15	11.3/15.0	31.3/36.1	-	-	52.7/58.7	60/60
														9.6/8.7	-	64.7/69.6	70/70
														-	3.3/3.0 (2.4)	56.9/62.5	60/70
														9.6/8.7	3.3/3.0 (2.4)	68.9/73.4	70/80
											EH*D-3M20	15.0/20.0	41.7/48.1	-	-	65.7/73.8	70/80
														9.6/8.7	-	77.7/84.6	80/90
														-	3.3/3.0 (2.4)	69.9/77.5	70/80
														9.6/8.7	3.3/3.0 (2.4)	81.9/88.4	90/90
											EH*D-3M30	22.5/30.0	62.5/72.2	-	-	91.8/104	100/110
														9.6/8.7	-	104/115	110/125
														-	3.3/3.0 (2.4)	96.0/108	100/110
														9.6/8.7	3.3/3.0 (2.4)	108/118	110/125
											EH*D-3M45	33.8/45.0	93.8/108	-	-	131/149	150/150
														9.6/8.7	-	143/160	150/175
														-	3.3/3.0 (2.4)	135/153	150/175
														9.6/8.7	3.3/3.0 (2.4)	147/164	150/175
											EH*D-3M60	45.1/60.0	125/144	-	-	170/158	175/175
														9.6/8.7	-	182/169	200/200
														-	3.3/3.0 (2.4)	174/162	175/175
														9.6/8.7	3.3/3.0 (2.4)	186/173	200/200
DHC1204D	460/3/60	2	7.7	69.0	2	0.33	0.85	1	2.4	5.4	-	-	-	-	-	24.4	30
											-	-	-	4.3	-	28.7	35
											-	-	-	-	1.2 (1.0)	25.6	30
											-	-	-	4.3	1.2 (1.0)	29.9	35
											EH*D-4M10	10.0	12.0	-	-	24.4	30
														4.3	-	28.7	35
														-	1.2 (1.0)	25.6	30
														4.3	1.2 (1.0)	29.9	35
											EH*D-4M15	15.0	18.0	-	-	29.3	30
														4.3	-	34.7	35
														-	1.2 (1.0)	30.8	35
														4.3	1.2 (1.0)	36.2	40
											EH*D-4M20	20.0	24.1	-	-	36.8	40
														4.3	-	42.2	45
														-	1.2 (1.0)	38.3	40
														4.3	1.2 (1.0)	43.7	45
											EH*D-4M30	30.0	36.1	-	-	51.9	60
														4.3	-	57.2	60
														-	1.2 (1.0)	53.4	60
														4.3	1.2 (1.0)	58.7	60
											EH*D-4M45	45.0	54.1	-	-	74.4	80
														4.3	-	79.8	80
														-	1.2 (1.0)	75.9	80
														4.3	1.2 (1.0)	81.3	90
											EH*D-4M60	60.0	72.2	-	-	78.9	90
														4.3	-	84.3	90
														-	1.2 (1.0)	80.4	90
														4.3	1.2 (1.0)	85.8	90

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	KW*	FLA	FLA	FLA	MCA	MOP
DHC1204L	460/3/60	2	7.7	69.0	2	0.33	0.85	1	3.5	7.2	-	-	-	-	-	26.2	30
											-	-	-	4.3	-	30.5	35
											-	-	-	-	1.2 (1.0)	27.4	30
											-	-	-	4.3	1.2 (1.0)	31.7	35
											EH*D-4M10	10.0	12.0	-	-	26.2	30
														4.3	-	30.5	35
														-	1.2 (1.0)	27.4	30
														4.3	1.2 (1.0)	31.7	35
											EH*D-4M15	15.0	18.0	-	-	31.6	35
														4.3	-	36.9	40
														-	1.2 (1.0)	33.1	35
														4.3	1.2 (1.0)	38.4	40
											EH*D-4M20	20.0	24.1	-	-	39.1	40
														4.3	-	44.4	45
														-	1.2 (1.0)	40.6	45
														4.3	1.2 (1.0)	45.9	50
											EH*D-4M30	30.0	36.1	-	-	54.1	60
														4.3	-	59.5	60
														-	1.2 (1.0)	55.6	60
														4.3	1.2 (1.0)	61.0	70
											EH*D-4M45	45.0	54.1	-	-	76.7	80
														4.3	-	82.0	90
														-	1.2 (1.0)	78.2	80
														4.3	1.2 (1.0)	83.5	90
											EH*D-4M60	60.0	72.2	-	-	81.2	90
														4.3	-	86.5	100
														-	1.2 (1.0)	82.7	90
														4.3	1.2 (1.0)	88.0	100
DHC1204W	460/3/60	2	7.7	69.0	2	0.33	0.85	1	3.5	7.2	-	-	-	-	-	26.2	30
											-	-	-	4.3	-	30.5	35
											-	-	-	-	1.2 (1.0)	27.4	30
											-	-	-	4.3	1.2 (1.0)	31.7	35
											EH*D-4M10	10.0	12.0	-	-	26.2	30
														4.3	-	30.5	35
														-	1.2 (1.0)	27.4	30
														4.3	1.2 (1.0)	31.7	35
											EH*D-4M15	15.0	18.0	-	-	31.6	35
														4.3	-	36.9	40
														-	1.2 (1.0)	33.1	35
														4.3	1.2 (1.0)	38.4	40
											EH*D-4M20	20.0	24.1	-	-	39.1	40
														4.3	-	44.4	45
														-	1.2 (1.0)	40.6	45
														4.3	1.2 (1.0)	45.9	50
											EH*D-4M30	30.0	36.1	-	-	54.1	60
														4.3	-	59.5	60
														-	1.2 (1.0)	55.6	60
														4.3	1.2 (1.0)	61.0	70
											EH*D-4M45	45.0	54.1	-	-	76.7	80
														4.3	-	82.0	90
														-	1.2 (1.0)	78.2	80
														4.3	1.2 (1.0)	83.5	90
											EH*D-4M60	60.0	72.2	-	-	81.2	90
														4.3	-	86.5	100
														-	1.2 (1.0)	82.7	90
														4.3	1.2 (1.0)	88.0	100

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	KW*	FLA	FLA	FLA	MCA	MOP
DHC1207D	575/3/60	2	6.4	47.8	2	0.33	0.67	1	2.4	4.0	-	-	-	-	-	19.7	25
											-	-	-	3.5	-	23.2	25
											-	-	-	-	1.3	21.0	25
											-	-	-	3.5	1.3	24.5	30
											EH*D-7M10	10.0	9.6	-	-	19.7	25
														3.5	-	23.2	25
														-	1.3	21.0	25
														3.5	1.3	24.5	30
											EH*D-7M15	15.0	14.4	-	-	23.0	25
														3.5	-	27.4	30
														-	1.3	24.7	25
														3.5	1.3	29.0	30
											EH*D-7M20	20.0	19.2	-	-	29.1	30
														3.5	-	33.4	35
														-	1.3	30.7	35
														3.5	1.3	35.1	40
											EH*D-7M30	30.0	28.9	-	-	41.1	45
														3.5	-	45.5	50
														-	1.3	42.7	45
														3.5	1.3	47.1	50
											EH*D-7M45	45.0	43.3	-	-	59.1	60
														3.5	-	63.5	70
														-	1.3	60.8	70
														3.5	1.3	65.1	70
											EH*D-7M60	60.0	57.7	-	-	62.7	70
														3.5	-	67.1	80
														-	1.3	64.4	70
														3.5	1.3	68.7	80
DHC1207L	575/3/60	2	6.4	47.8	2	0.33	0.67	1	3.5	5.0	-	-	-	-	-	20.7	25
											-	-	-	3.5	-	24.2	30
											-	-	-	-	1.3	22.0	25
											-	-	-	3.5	1.3	25.5	30
											EH*D-7M10	10.0	9.6	-	-	20.7	25
														3.5	-	24.2	30
														-	1.3	22.0	25
														3.5	1.3	25.5	30
											EH*D-7M15	15.0	14.4	-	-	24.3	25
														3.5	-	28.7	30
														-	1.3	25.9	30
														3.5	1.3	30.3	35
											EH*D-7M20	20.0	19.2	-	-	30.3	35
														3.5	-	34.7	35
														-	1.3	31.9	35
														3.5	1.3	36.3	40
											EH*D-7M30	30.0	28.9	-	-	42.3	45
														3.5	-	46.7	50
														-	1.3	44.0	45
														3.5	1.3	48.3	50
											EH*D-7M45	45.0	43.3	-	-	60.4	70
														3.5	-	64.8	70
														-	1.3	62.0	70
														3.5	1.3	66.4	70
											EH*D-7M60	60.0	57.7	-	-	64.0	70
														3.5	-	68.4	80
														-	1.3	65.6	80
														3.5	1.3	70.0	80

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	KW*	FLA	FLA	FLA	MCA	MOP
DHC1207W	575/3/60	2	6.4	47.8	2	0.33	0.67	1	3.5	5.0	-	-	-	-	-	20.7	25
											-	-	-	3.5	-	24.2	30
											-	-	-	-	1.3	22.0	25
											-	-	-	3.5	1.3	25.5	30
											EH*D-7M10	10.0	9.6	-	-	20.7	25
														3.5	-	24.2	30
														-	1.3	22.0	25
														3.5	1.3	25.5	30
											EH*D-7M15	15.0	14.4	-	-	24.3	25
														3.5	-	28.7	30
														-	1.3	25.9	30
														3.5	1.3	30.3	35
											EH*D-7M20	20.0	19.2	-	-	30.3	35
														3.5	-	34.7	35
														-	1.3	31.9	35
														3.5	1.3	36.3	40
											EH*D-7M30	30.0	28.9	-	-	42.3	45
														3.5	-	46.7	50
														-	1.3	44.0	45
														3.5	1.3	48.3	50
											EH*D-7M45	45.0	43.3	-	-	60.4	70
														3.5	-	64.8	70
														-	1.3	62.0	70
														3.5	1.3	66.4	70
											EH*D-7M60	60.0	57.7	-	-	64.0	70
														3.5	-	68.4	80
														-	1.3	65.6	80
														3.5	1.3	70.0	80
DHC1503D	208/230/3/60	2	19.2	157	2	0.33	3.5	1	3.5	10.9	-	-	-	-	-	61.1/61.1	80/80
											-	-	-	9.6/8.7	-	70.7/69.8	80/80
											-	-	-	-	3.3/3.0 (2.4)	64.4/64.1	80/80
											-	-	-	9.6/8.7	3.3/3.0 (2.4)	74.0/72.8	90/90
											EH*D-3M10	7.5/10.0	20.8/24.1	-	-	61.1/61.1	80/80
														9.6/8.7	-	70.7/69.8	80/80
														-	3.3/3.0 (2.4)	64.4/64.1	80/80
														9.6/8.7	3.3/3.0 (2.4)	74.0/72.8	90/90
											EH*D-3M15	11.3/15.0	31.3/36.1	-	-	61.1/61.1	80/80
														9.6/8.7	-	70.7/69.8	80/80
														-	3.3/3.0 (2.4)	64.4/64.1	80/80
														9.6/8.7	3.3/3.0 (2.4)	74.0/73.4	90/90
											EH*D-3M20	15.0/20.0	41.7/48.1	-	-	65.7/73.8	80/80
														9.6/8.7	-	77.7/84.6	80/90
														-	3.3/3.0 (2.4)	69.9/77.5	80/80
														9.6/8.7	3.3/3.0 (2.4)	81.9/88.4	90/90
											EH*D-3M30	22.5/30.0	62.5/72.2	-	-	91.8/104	100/110
														9.6/8.7	-	104/115	110/125
														-	3.3/3.0 (2.4)	96.0/108	100/110
														9.6/8.7	3.3/3.0 (2.4)	108/118	110/125
											EH*D-3M45	33.8/45.0	93.8/108	-	-	131/149	150/150
														9.6/8.7	-	143/160	150/175
														-	3.3/3.0 (2.4)	135/153	150/175
														9.6/8.7	3.3/3.0 (2.4)	147/164	150/175
											EH*D-3M60	45.1/60.0	125/144	-	-	170/158	175/175
														9.6/8.7	-	182/169	200/200
														-	3.3/3.0 (2.4)	174/162	175/175
														9.6/8.7	3.3/3.0 (2.4)	186/173	200/200

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	KW*	FLA	FLA	FLA	MCA	MOP
DHC1503L	208/230/3/60	2	19.2	157	2	0.33	3.5	1	3.5	10.9	-	-	-	-	-	61.1/61.1	80/80
											-	-	-	9.6/8.7	-	70.7/69.8	80/80
											-	-	-	-	3.3/3.0 (2.4)	64.4/64.1	80/80
											-	-	-	9.6/8.7	3.3/3.0 (2.4)	74.0/72.8	90/90
											EH*D-3M10	7.5/10.0	20.8/24.1	-	-	61.1/61.1	80/80
														9.6/8.7	-	70.7/69.8	80/80
														-	3.3/3.0 (2.4)	64.4/64.1	80/80
														9.6/8.7	3.3/3.0 (2.4)	74.0/72.8	90/90
											EH*D-3M15	11.3/15.0	31.3/36.1	-	-	61.1/61.1	80/80
														9.6/8.7	-	70.7/69.8	80/80
														-	3.3/3.0 (2.4)	64.4/64.1	80/80
														9.6/8.7	3.3/3.0 (2.4)	74.0/73.4	90/90
											EH*D-3M20	15.0/20.0	41.7/48.1	-	-	65.7/73.8	80/80
														9.6/8.7	-	77.7/84.6	80/90
														-	3.3/3.0 (2.4)	69.9/77.5	80/80
														9.6/8.7	3.3/3.0 (2.4)	81.9/88.4	90/90
											EH*D-3M30	22.5/30.0	62.5/72.2	-	-	91.8/104	100/110
														9.6/8.7	-	104/115	110/125
														-	3.3/3.0 (2.4)	96.0/108	100/110
														9.6/8.7	3.3/3.0 (2.4)	108/118	110/125
											EH*D-3M45	33.8/45.0	93.8/108	-	-	131/149	150/150
														9.6/8.7	-	143/160	150/175
														-	3.3/3.0 (2.4)	135/153	150/175
														9.6/8.7	3.3/3.0 (2.4)	147/164	150/175
											EH*D-3M60	45.1/60.0	125/144	-	-	170/158	175/175
														9.6/8.7	-	182/169	200/200
														-	3.3/3.0 (2.4)	174/162	175/175
														9.6/8.7	3.3/3.0 (2.4)	186/173	200/200
DHC1503W	208/230/3/60	2	19.2	157	2	0.33	3.5	1	5.0	14.5	-	-	-	-	-	64.7/64.7	80/80
											-	-	-	9.6/8.7	-	74.3/73.4	90/90
											-	-	-	-	3.3/3.0 (2.4)	68.0/67.7	80/80
											-	-	-	9.6/8.7	3.3/3.0 (2.4)	77.6/76.4	90/90
											EH*D-3M10	7.5/10.0	20.8/24.1	-	-	64.7/64.7	80/80
														9.6/8.7	-	74.3/73.4	90/90
														-	3.3/3.0 (2.4)	68.0/67.7	80/80
														9.6/8.7	3.3/3.0 (2.4)	77.6/76.4	90/90
											EH*D-3M15	11.3/15.0	31.3/36.1	-	-	64.7/64.7	80/80
														9.6/8.7	-	74.3/74.1	90/90
														-	3.3/3.0 (2.4)	68.0/67.7	80/80
														9.6/8.7	3.3/3.0 (2.4)	77.6/77.9	90/90
											EH*D-3M20	15.0/20.0	41.7/48.1	-	-	70.2/78.3	80/80
														9.6/8.7	-	82.2/89.1	90/90
														-	3.3/3.0 (2.4)	74.4/82.0	80/90
														9.6/8.7	3.3/3.0 (2.4)	86.4/92.9	90/100
											EH*D-3M30	22.5/30.0	62.5/72.2	-	-	96.3/108	100/110
														9.6/8.7	-	108/119	110/125
														-	3.3/3.0 (2.4)	100/112	110/125
														9.6/8.7	3.3/3.0 (2.4)	112/123	125/125
											EH*D-3M45	33.8/45.0	93.8/108	-	-	135/153	150/175
														9.6/8.7	-	147/164	150/175
														-	3.3/3.0 (2.4)	140/157	150/175
														9.6/8.7	3.3/3.0 (2.4)	152/168	175/175
											EH*D-3M60	45.1/60.0	125/144	-	-	174/162	175/200
														9.6/8.7	-	186/173	200/200
														-	3.3/3.0 (2.4)	179/166	200/200
														9.6/8.7	3.3/3.0 (2.4)	191/177	200/200

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	KW*	FLA	FLA	FLA	MCA	MOP
DHC1504D	460/3/60	2	9.0	74.8	2	0.33	1.6	1	3.5	7.2	-	-	-	-	-	30.6	35
											-	-	-	4.3	-	34.9	40
											-	-	-	-	1.2 (1.0)	31.8	40
											-	-	-	4.3	1.2 (1.0)	36.1	40
											EH*D-4M10	10.0	12.0	-	-	30.6	35
														4.3	-	34.9	40
														-	1.2 (1.0)	31.8	40
														4.3	1.2 (1.0)	36.1	40
											EH*D-4M15	15.0	18.0	-	-	31.6	35
														4.3	-	36.9	40
														-	1.2 (1.0)	33.1	40
														4.3	1.2 (1.0)	38.4	40
											EH*D-4M20	20.0	24.1	-	-	39.1	40
														4.3	-	44.4	45
														-	1.2 (1.0)	40.6	45
														4.3	1.2 (1.0)	45.9	50
											EH*D-4M30	30.0	36.1	-	-	54.1	60
														4.3	-	59.5	60
														-	1.2 (1.0)	55.6	60
														4.3	1.2 (1.0)	61.0	70
											EH*D-4M45	45.0	54.1	-	-	76.7	80
														4.3	-	82.0	90
														-	1.2 (1.0)	78.2	80
														4.3	1.2 (1.0)	83.5	90
											EH*D-4M60	60.0	72.2	-	-	81.2	90
														4.3	-	86.5	100
														-	1.2 (1.0)	82.7	90
														4.3	1.2 (1.0)	88.0	100
DHC1504L	460/3/60	2	9.0	74.8	2	0.33	1.6	1	3.5	7.2	-	-	-	-	-	30.6	35
											-	-	-	4.3	-	34.9	40
											-	-	-	-	1.2 (1.0)	31.8	40
											-	-	-	4.3	1.2 (1.0)	36.1	40
											EH*D-4M10	10.0	12.0	-	-	30.6	35
														4.3	-	34.9	40
														-	1.2 (1.0)	31.8	40
														4.3	1.2 (1.0)	36.1	40
											EH*D-4M15	15.0	18.0	-	-	31.6	35
														4.3	-	36.9	40
														-	1.2 (1.0)	33.1	40
														4.3	1.2 (1.0)	38.4	40
											EH*D-4M20	20.0	24.1	-	-	39.1	40
														4.3	-	44.4	45
														-	1.2 (1.0)	40.6	45
														4.3	1.2 (1.0)	45.9	50
											EH*D-4M30	30.0	36.1	-	-	54.1	60
														4.3	-	59.5	60
														-	1.2 (1.0)	55.6	60
														4.3	1.2 (1.0)	61.0	70
											EH*D-4M45	45.0	54.1	-	-	76.7	80
														4.3	-	82.0	90
														-	1.2 (1.0)	78.2	80
														4.3	1.2 (1.0)	83.5	90
											EH*D-4M60	60.0	72.2	-	-	81.2	90
														4.3	-	86.5	100
														-	1.2 (1.0)	82.7	90
														4.3	1.2 (1.0)	88.0	100

Electrical Data

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	KW*	FLA	FLA	FLA	MCA	MOP
DHC1504W	460/3/60	2	9.0	74.8	2	0.33	1.6	1	5.0	10.6	-	-	-	-	-	34.0	40
											-	-	-	4.3	-	38.3	45
											-	-	-	-	1.2 (1.0)	35.2	45
											-	-	-	4.3	1.2 (1.0)	39.5	50
											EH*D-4M10	10.0	12.0	-	-	34.0	40
														4.3	-	38.3	45
														-	1.2 (1.0)	35.2	45
														4.3	1.2 (1.0)	39.5	50
											EH*D-4M15	15.0	18.0	-	-	35.8	40
														4.3	-	41.2	45
														-	1.2 (1.0)	37.3	45
														4.3	1.2 (1.0)	42.7	50
											EH*D-4M20	20.0	24.1	-	-	43.3	45
														4.3	-	48.7	50
														-	1.2 (1.0)	44.8	45
														4.3	1.2 (1.0)	50.2	60
											EH*D-4M30	30.0	36.1	-	-	58.4	60
														4.3	-	63.7	70
														-	1.2 (1.0)	59.9	60
														4.3	1.2 (1.0)	65.2	70
											EH*D-4M45	45.0	54.1	-	-	80.9	90
														4.3	-	86.3	90
														-	1.2 (1.0)	82.4	90
														4.3	1.2 (1.0)	87.8	90
											EH*D-4M60	60.0	72.2	-	-	85.4	100
														4.3	-	90.8	100
														-	1.2 (1.0)	86.9	100
														4.3	1.2 (1.0)	92.3	100
DHC1507D	575/3/60	2	7.0	53.9	2	0.33	1.54	1	3.5	5.0	-	-	-	-	-	23.9	30
											-	-	-	3.5	-	27.4	30
											-	-	-	-	1.3	25.2	30
											-	-	-	3.5	1.3	28.7	35
											EH*D-7M10	10.0	9.6	-	-	23.9	30
														3.5	-	27.4	30
														-	1.3	25.2	30
														3.5	1.3	28.7	35
											EH*D-7M15	15.0	14.4	-	-	24.3	30
														3.5	-	28.7	30
														-	1.3	25.9	30
														3.5	1.3	30.3	35
											EH*D-7M20	20.0	19.2	-	-	30.3	35
														3.5	-	34.7	35
														-	1.3	31.9	35
														3.5	1.3	36.3	40
											EH*D-7M30	30.0	28.9	-	-	42.3	45
														3.5	-	46.7	50
														-	1.3	44.0	45
														3.5	1.3	48.3	50
											EH*D-7M45	45.0	43.3	-	-	60.4	70
														3.5	-	64.8	70
														-	1.3	62.0	70
														3.5	1.3	66.4	70
											EH*D-7M60	60.0	57.7	-	-	64.0	70
														3.5	-	68.4	80
														-	1.3	65.6	80
														3.5	1.3	70.0	80

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	KW*	FLA	FLA	FLA	MCA	MOP
DHC1507L	575/3/60	2	7.0	53.9	2	0.33	1.54	1	3.5	5.0	-	-	-	-	-	23.9	30
											-	-	-	3.5	-	27.4	30
											-	-	-	-	1.3	25.2	30
											-	-	-	3.5	1.3	28.7	35
											EH*D-7M10	10.0	9.6	-	-	23.9	30
														3.5	-	27.4	30
														-	1.3	25.2	30
														3.5	1.3	28.7	35
											EH*D-7M15	15.0	14.4	-	-	24.3	30
														3.5	-	28.7	30
														-	1.3	25.9	30
														3.5	1.3	30.3	35
											EH*D-7M20	20.0	19.2	-	-	30.3	35
														3.5	-	34.7	35
														-	1.3	31.9	35
														3.5	1.3	36.3	40
											EH*D-7M30	30.0	28.9	-	-	42.3	45
														3.5	-	46.7	50
														-	1.3	44.0	45
														3.5	1.3	48.3	50
											EH*D-7M45	45.0	43.3	-	-	60.4	70
														3.5	-	64.8	70
														-	1.3	62.0	70
														3.5	1.3	66.4	70
											EH*D-7M60	60.0	57.7	-	-	64.0	70
														3.5	-	68.4	80
														-	1.3	65.6	80
														3.5	1.3	70.0	80
DHC1507W	575/3/60	2	7.0	53.9	2	0.33	1.5	1	5.0	7.2	-	-	-	-	-	26.1	30
											-	-	-	3.5	-	29.6	35
											-	-	-	-	1.3	27.4	30
											-	-	-	3.5	1.3	30.9	35
											EH*D-7M10	10.0	9.6	-	-	26.1	30
														3.5	-	29.6	35
														-	1.3	27.4	30
														3.5	1.3	30.9	35
											EH*D-7M15	15.0	14.4	-	-	27.0	30
														3.5	-	31.4	35
														-	1.3	28.7	30
														3.5	1.3	33.0	35
											EH*D-7M20	20.0	19.2	-	-	33.1	35
														3.5	-	37.4	40
														-	1.3	34.7	35
														3.5	1.3	39.1	40
											EH*D-7M30	30.0	28.9	-	-	45.1	50
														3.5	-	49.5	50
														-	1.3	46.7	50
														3.5	1.3	51.1	60
											EH*D-7M45	45.0	43.3	-	-	63.1	70
														3.5	-	67.5	70
														-	1.3	64.8	70
														3.5	1.3	69.1	70
											EH*D-7M60	60.0	57.7	-	-	66.7	80
														3.5	-	71.1	80
														-	1.3	68.4	80
														3.5	1.3	72.7	80

