

HORIZONTAL FLOW

CFM	0.2			0.4			0.6			0.8			1.0		
	RPM	DDC %	BHP	RPM	DDC %	BHP	RPM	DDC %	BHP	RPM	DDC %	BHP	RPM	DDC %	BHP
1200	578	21	0.18	702	24	0.24	816	28	0.29	922	32	0.36	1014	35	0.46
1400	648	27	0.23	762	30	0.30	867	34	0.36	965	38	0.44	1052	41	0.56
1600	717	34	0.30	822	37	0.38	917	41	0.45	1009	44	0.54	1090	47	0.68
1800	787	41	0.39	882	44	0.49	968	47	0.56	1052	50	0.66	1128	53	0.83
2000	857	48	0.51	942	51	0.62	1019	54	0.70	1095	57	0.80	1166	59	1.02
2200	927	55	0.66	1002	58	0.79	1070	60	0.87	1138	63	0.98	1204	65	1.25
2400	997	62	0.86	1062	64	1.00	1121	67	1.09	1181	69	1.19	1242	71	1.52
2600	1067	69	1.11	1122	71	1.28	1172	73	1.36	1224	75	1.46	1280	77	1.50
2800	1137	76	1.44	1182	78	1.62	1223	80	1.69	1268	81	1.78	1318	83	1.80
3000	1207	83	1.87	1242	85	2.06	1274	86	2.11	1311	88	2.18	1356	89	2.30
CFM	1.2			1.4			1.6			1.8			2.0		
	RPM	DDC %	BHP	RPM	DDC %	BHP	RPM	DDC %	BHP	RPM	DDC %	BHP	RPM	DDC %	BHP
1200	1091	38	0.50	1169	41	0.61	1224	45	0.65	1295	41	0.83	1353	45	0.94
1400	1126	44	0.60	1200	47	0.73	1256	50	0.77	1324	48	0.98	1381	51	1.10
1600	1161	50	0.72	1231	52	0.88	1287	55	0.90	1352	54	1.15	1409	57	1.30
1800	1196	56	0.86	1262	58	1.05	1319	61	1.05	1381	60	1.35	1437	63	1.52
2000	1231	62	1.03	1293	64	1.26	1351	66	1.24	1409	67	1.58	1465	69	1.78
2200	1266	67	1.23	1324	69	1.51	1382	71	1.45	1437	73	1.86	1493	75	2.09
2400	1301	73	1.47	1355	75	1.80	1414	77	1.70	1466	80	2.18	1521	81	2.46
2600	1336	79	1.76	1386	81	2.16	1445	82	2.00						
2800	1371	85	2.11	1417	86	2.20	1477	88	2.30						
3000															

Shaded area indicates air flow below 1800 SCFM (300 SCFM/ton) that is not recommended for High Stage cooling or heating.
Valid motor operating range for DDC% setting is 20 - 90.

Heating Data Tables

DHH036*D

High Stage (100 % Capacity)

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBH	44.01	40.98	38.00	35.07	33.20	31.76	28.18	24.93	22.28	20.30	18.80	18.00	16.99	15.45	15.00	9.39	6.85
T/R	34.08	32.04	30.00	27.96	26.73	25.57	22.69	20.07	17.94	16.34	15.14	14.49	13.68	11.64	9.60	7.56	5.52
KW	2.72	2.68	2.63	2.59	2.56	2.54	2.50	2.45	2.41	2.36	2.32	2.29	2.28	2.23	2.19	2.14	2.10
AMPS	10.0	9.8	9.6	9.4	9.3	9.2	9.0	8.8	8.7	8.5	8.3	8.1	8.1	7.9	7.7	7.5	7.3
COP	4.74	4.49	4.23	3.97	3.80	3.66	3.31	2.98	2.71	2.52	2.37	2.30	2.19	1.90	1.85	1.28	0.96
Hi PR	403	390	377	364	356	351	338	325	311	298	285	277	272	259	246	233	220
LO PR	143	134	125	116	111	107	99	90	81	72	63	58	54	45	36	27	18

DHH036*D

Low Stage (70% Capacity)

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBH	31.81	29.64	27.68	25.44	23.95	22.74	19.79	-	-	-	-	-	-	-	-	-	-
T/R	30.00	28.02	26.04	24.05	22.86	21.71	18.89	-	-	-	-	-	-	-	-	-	-
KW	1.66	1.61	1.56	1.51	1.48	1.46	1.41	-	-	-	-	-	-	-	-	-	-
AMPS	5.7	5.5	5.2	5.0	4.9	4.8	4.6	-	-	-	-	-	-	-	-	-	-
COP	5.60	5.39	5.20	4.94	4.75	4.57	4.12	-	-	-	-	-	-	-	-	-	-
Hi PR	391	378	365	353	345	340	327	-	-	-	-	-	-	-	-	-	-
LO PR	141	132	123	114	109	106	97	-	-	-	-	-	-	-	-	-	-

DHH048*

High Stage (100 % Capacity)

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBH	59.70	55.86	52.09	48.38	46.00	44.25	39.80	35.68	32.32	29.83	27.99	27.00	25.73	22.57	19.40	16.23	13.07
T/R	34.29	32.40	30.51	28.62	27.48	26.43	23.77	21.31	19.31	17.82	16.72	16.13	15.37	13.48	11.59	9.70	7.80
KW	3.78	3.71	3.65	3.59	3.55	3.52	3.46	3.39	3.33	3.27	3.20	3.17	3.14	3.08	3.01	2.95	2.88
AMPS	14.0	13.7	13.4	13.1	13.0	12.9	12.6	12.3	12.0	11.7	11.5	11.3	11.2	10.9	10.6	10.4	10.1
COP	4.63	4.41	4.18	3.95	3.80	3.68	3.37	3.08	2.84	2.68	2.56	2.50	2.40	2.15	1.89	1.61	1.33
Hi PR	373	361	348	336	329	324	312	300	288	276	264	256	251	239	227	215	203
LO PR	135	127	118	110	105	102	93	85	76	68	60	54	51	43	34	26	17

DHH048*D

Low Stage (70% Capacity)

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBH	44.08	41.06	38.19	35.13	33.18	31.66	27.89	-	-	-	-	-	-	-	-	-	-
T/R	39.59	37.13	34.67	32.21	30.73	29.32	25.83	-	-	-	-	-	-	-	-	-	-
KW	2.31	2.24	2.17	2.09	2.05	2.02	1.95	-	-	-	-	-	-	-	-	-	-
AMPS	8.5	8.1	7.8	7.5	7.3	7.2	6.9	-	-	-	-	-	-	-	-	-	-
COP	5.59	5.38	5.17	4.92	4.75	4.59	4.20	-	-	-	-	-	-	-	-	-	-
Hi PR	361	349	338	326	319	314	302	-	-	-	-	-	-	-	-	-	-
LO PR	133	125	116	108	103	100	92	-	-	-	-	-	-	-	-	-	-

Calculations are based on nominal CFM and 70 °F indoor dry bulb.

Amps = Outdoor unit amps (comp.+fan)

Note: Shaded area is AHRI Rating Conditions at 47°F outdoor ambient temperature

kW = Total system power

Heating Data Tables

DHH060*D

High Stage (100 % Capacity)

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBH	76.34	71.48	66.71	62.01	59.00	56.80	51.18	45.97	41.71	38.56	36.24	35.00	33.40	29.40	25.40	21.40	17.40
T/R	34.86	32.96	31.06	29.16	28.02	26.97	24.30	21.83	19.81	18.31	17.21	16.62	15.86	13.96	12.06	10.16	8.26
KW	4.82	4.74	4.67	4.60	4.55	4.52	4.45	4.37	4.30	4.22	4.15	4.10	4.07	4.00	3.92	3.85	3.78
AMPS	17.9	17.5	17.2	16.9	16.7	16.6	16.2	15.9	15.6	15.3	14.9	14.7	14.6	14.3	14.0	13.6	13.3
COP	4.64	4.42	4.19	3.96	3.80	3.68	3.37	3.08	2.84	2.68	2.56	2.50	2.40	2.15	1.90	1.63	1.35
Hi PR	383	370	358	345	338	333	321	308	296	283	271	263	258	246	233	221	208
LO PR	137	128	120	111	105	103	94	86	77	69	60	55	52	43	35	26	18

DHH060*D

Low Stage (70% Capacity)

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBH	56.53	52.67	48.91	45.03	42.56	40.64	35.86	-	-	-	-	-	-	-	-	-	-
T/R	38.08	35.73	33.39	31.04	29.63	28.29	24.97	-	-	-	-	-	-	-	-	-	-
KW	2.95	2.86	2.77	2.68	2.63	2.59	2.50	-	-	-	-	-	-	-	-	-	-
AMPS	10.7	10.3	9.9	9.6	9.3	9.2	8.8	-	-	-	-	-	-	-	-	-	-
COP	5.62	5.40	5.17	4.92	4.75	4.59	4.20	-	-	-	-	-	-	-	-	-	-
Hi PR	371	359	347	335	328	323	311	-	-	-	-	-	-	-	-	-	-
LO PR	134	126	117	109	104	101	92	-	-	-	-	-	-	-	-	-	-

DHH072*D

High Stage (100 % Capacity)

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBH	80.70	75.46	70.31	65.25	62.00	59.60	53.50	47.87	43.29	39.88	37.36	36.00	34.27	29.93	25.60	21.27	16.93
T/R	32.66	30.84	29.01	27.19	26.10	25.08	22.52	20.15	18.22	16.78	15.72	15.15	14.42	12.60	10.77	8.95	7.13
KW	5.67	5.54	5.40	5.27	5.19	5.14	5.01	4.87	4.74	4.61	4.48	4.40	4.34	4.21	4.08	3.95	3.81
AMPS	21.2	20.6	20.0	19.4	19.1	18.9	18.3	17.7	17.1	16.5	16.0	15.6	15.4	14.8	14.2	13.7	13.1
COP	4.17	3.99	3.81	3.63	3.50	3.40	3.13	2.88	2.68	2.54	2.45	2.40	2.31	2.08	1.84	1.58	1.30
Hi PR	400	387	374	361	353	348	335	322	309	296	283	275	270	257	244	231	218
LO PR	131	123	115	107	102	99	91	82	74	66	58	53	50	41	33	25	17

DHH072*D

Low Stage (70% Capacity)

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBH	59.37	55.26	51.22	47.25	44.73	42.78	37.92	33.52	29.94	27.25	25.22	24.13	22.76	19.33	15.90	12.46	9.03
T/R	36.71	34.50	32.29	30.09	28.76	27.51	24.39	21.56	19.25	17.52	16.22	15.52	14.63	12.43	10.22	8.01	5.81
KW	3.32	3.23	3.14	3.05	3.00	2.96	2.87	2.78	2.69	2.60	2.51	2.46	2.42	2.33	2.24	2.15	2.06
AMPS	12.2	11.8	11.4	11.0	10.8	10.6	10.2	9.8	9.4	9.0	8.6	8.4	8.3	7.9	7.5	7.1	6.7
COP	5.24	5.01	4.78	4.54	4.37	4.23	3.87	3.53	3.26	3.07	2.94	2.88	2.75	2.43	2.08	1.70	1.28
Hi PR	384	372	359	347	339	334	322	309	297	284	272	264	259	247	234	222	209
LO PR	129	121	113	105	100	97	89	81	73	65	57	52	49	41	33	25	17

Calculations are based on nominal CFM and 70 °F indoor dry bulb.

Note: Shaded area is AHRI Rating Conditions at 47°F outdoor ambient temperature

Amps = Outdoor unit amps (comp.+fan)

kW = Total system power

3-6 TONS		
DOWNFLOW ECONOMIZER PRESSURE DROP		
Cabinet	CFM	SP in.wg.
3 Ton	900	.03"
	1200	.05"
	1500	.08"
4 Ton	1200	.06"
	1600	.10"
	2000	.14"
5 Ton	1500	.08"
	2000	.14"
	2500	.22"
6 Ton	1800	.13"
	2400	.22"
	3000	.33"

3-6 TONS		
HORIZONTAL ECONOMIZER PRESSURE DROP		
Cabinet	CFM	SP in.wg.
3 Ton	900	.06"
	1200	.11"
	1500	.16"
4 Ton	1200	.11"
	1600	.19"
	2000	.29"
5 Ton	1500	.18"
	2000	.30"
	2500	.45"
6 Ton	1800	.24"
	2400	.41"
	3000	.61"

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	Kw*	Fla	Fla	Fla	Mca	Mop
DHH0361D	208/230/1/60	1	14.5	91.0	1	0.17	0.95	1	0.75	5.7	-	-	-	-	-	24.8/24.8	35/35
											-	-	-	9.6/8.7	-	34.4/33.5	45/45
											-	-	-	-	2.2/1.9 (1.7/1.5)	27.0/26.7	40/40
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	36.6/35.4	50/45
											EH*D-1S05A	3.8/5.0	18.1/20.8	-	-	47.4/50.9	50/60
														9.6/8.7	-	57.0/59.6	60/60
														-	2.2/1.9 (1.7/1.5)	49.6/52.8	50/60
														9.6/8.7	2.2/1.9 (1.7/1.5)	59.2/61.5	60/70
											EH*D-1S10A	7.5/10.0	36.1/41.7	-	-	69.9/76.9	70/80
														9.6/8.7	-	79.5/85.6	80/90
														-	2.2/1.9 (1.7/1.5)	72.1/78.8	80/80
														9.6/8.7	2.2/1.9 (1.7/1.5)	81.7/87.5	90/90
											EH*D-1S15A	11.3/15.0	54.2/62.5	-	-	92.5/103	100/110
														9.6/8.7	-	102/112	110/125
														-	2.2/1.9 (1.7/1.5)	94.7/105	100/110
														9.6/8.7	2.2/1.9 (1.7/1.5)	104/114	110/125
DHH0363D	208/230/3/60	1	9.2	82.0	1	0.17	0.95	1	0.75	5.7	-	-	-	-	-	18.1/18.1	25/25
											-	-	-	9.6/8.7	-	27.7/26.8	35/35
											-	-	-	-	2.2/1.9 (1.7/1.5)	20.3/20.0	25/25
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	29.9/28.7	35/35
											EH*D-3S05A	3.8/5.0	10.4/12.0	-	-	31.1/33.1	35/35
														9.6/8.7	-	40.7/41.8	45/45
														-	2.2/1.9 (1.7/1.5)	33.3/35.0	35/40
														9.6/8.7	2.2/1.9 (1.7/1.5)	42.9/43.7	45/45
											EH*D-3S10A	7.5/10.0	20.8/24.0	-	-	44.0/48.0	45/50
														9.6/8.7	-	53.6/56.7	60/60
														-	2.2/1.9 (1.7/1.5)	46.2/49.9	50/50
														9.6/8.7	2.2/1.9 (1.7/1.5)	55.8/58.6	60/60
											EH*D-3S15A	11.3/15.0	31.3/36.1	-	-	57.2/63.2	60/70
														9.6/8.7	-	66.8/71.9	70/80
														-	2.2/1.9 (1.7/1.5)	59.4/65.1	60/70
														9.6/8.7	2.2/1.9 (1.7/1.5)	69.0/73.8	70/80
DHH0363W	208/230/3/60	1	9.2	82.0	1	0.17	0.95	1	1.2	5.0	-	-	-	-	-	17.4/17.4	25/25
											-	-	-	9.6/8.7	-	27.0/26.1	35/35
											-	-	-	-	2.2/1.9 (1.7/1.5)	19.6/19.3	25/25
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	29.2/28.0	35/35
											EH*D-3S05A	3.8/5.0	10.4/12.0	-	-	30.4/32.4	35/35
														9.6/8.7	-	40.0/41.1	45/45
														-	2.2/1.9 (1.7/1.5)	32.6/34.3	35/40
														9.6/8.7	2.2/1.9 (1.7/1.5)	42.2/43.0	45/45
											EH*D-3S10A	7.5/10.0	20.8/24.0	-	-	43.3/47.3	45/50
														9.6/8.7	-	52.9/56.0	60/60
														-	2.2/1.9 (1.7/1.5)	45.5/49.2	50/50
														9.6/8.7	2.2/1.9 (1.7/1.5)	55.1/57.9	60/60
											EH*D-3S15A	11.3/15.0	31.3/36.1	-	-	56.5/62.5	60/70
														9.6/8.7	-	66.1/71.2	70/80
														-	2.2/1.9 (1.7/1.5)	58.7/64.4	60/70
														9.6/8.7	2.2/1.9 (1.7/1.5)	68.3/73.1	70/80
DHH0364D	460/3/60	1	4.2	44.3	1	0.17	0.48	1	1.2	2.5	-	-	-	-	-	8.2	15
											-	-	-	4.3	-	12.5	15
											-	-	-	-	0.9 (0.5)	9.1	15
											-	-	-	4.3	0.9 (0.5)	13.4	15
											EH*D-4S05A	5.0	6.0	-	-	15.7	20
														4.3	-	20.0	20
														-	0.9 (0.5)	16.6	20
														4.3	0.9 (0.5)	20.9	25
											EH*D-4S10A	10.0	12.0	-	-	23.2	25
														4.3	-	27.5	30
														-	0.9 (0.5)	24.1	25
														4.3	0.9 (0.5)	28.4	30
											EH*D-4S15A	15.0	18.0	-	-	30.7	35
														4.3	-	35.0	40
														-	0.9 (0.5)	31.6	35
														4.3	0.9 (0.5)	35.9	40

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	Kw*	Fla	Fla	Fla	Mca	Mop
DHH0364W	460/3/60	1	4.2	44.3	1	0.17	0.48	1	1.2	2.5	-	-	-	-	-	8.2	15
											-	-	-	4.3	-	12.5	15
											-	-	-	-	0.9 (0.5)	9.1	15
											-	-	-	4.3	0.9 (0.5)	13.4	15
											EH*D-4S05A	5.0	6.0	-	-	15.7	20
														4.3	-	20.0	20
														-	0.9 (0.5)	16.6	20
														4.3	0.9 (0.5)	20.9	25
											EH*D-4S10A	10.0	12.0	-	-	23.2	25
														4.3	-	27.5	30
														-	0.9 (0.5)	24.1	25
														4.3	0.9 (0.5)	28.4	30
											EH*D-4S15A	15.0	18.0	-	-	30.7	35
														4.3	-	35.0	40
														-	0.9 (0.5)	31.6	35
														4.3	0.9 (0.5)	35.9	40
DHH0367D	575/3/60	1	3.7	28.7	1	0.17	0.39	1	1.2	2.0	-	-	-	-	-	7.0	15
											-	-	-	3.5	-	10.5	15
											-	-	-	-	1.0	8.0	15
											-	-	-	3.5	1.0	11.5	15
											EH*D-7S05A	5.0	4.8	-	-	13.0	15
														3.5	-	16.5	20
														-	1.0	14.0	15
														3.5	1.0	17.5	20
											EH*D-7S10A	10.0	9.6	-	-	19.1	20
														3.5	-	22.6	25
														-	1.0	20.1	25
														3.5	1.0	23.6	25
											EH*D-7S15A	15.0	14.4	-	-	25.1	30
														3.5	-	28.6	30
														-	1.0	26.1	30
														3.5	1.0	29.6	30
DHH0367W	575/3/60	1	3.7	28.7	1	0.17	0.39	1	1.2	2.0	-	-	-	-	-	7.0	15
											-	-	-	3.5	-	10.5	15
											-	-	-	-	1.0	8.0	15
											-	-	-	3.5	1.0	11.5	15
											EH*D-7S05A	5.0	4.8	-	-	13.0	15
														3.5	-	16.5	20
														-	1.0	14.0	15
														3.5	1.0	17.5	20
											EH*D-7S10A	10.0	9.6	-	-	19.1	20
														3.5	-	22.6	25
														-	1.0	20.1	25
														3.5	1.0	23.6	25
											EH*D-7S15A	15.0	14.4	-	-	25.1	30
														3.5	-	28.6	30
														-	1.0	26.1	30
														3.5	1.0	29.6	30
DHH0481D	208/230/1/60	1	23.2	128	1	0.33	3.5	1	1	6.9	-	-	-	-	-	39.4/39.4	60/60
											-	-	-	9.6/8.7	-	49.0/48.1	70/70
											-	-	-	-	2.2/1.9 (1.7/1.5)	41.6/41.3	60/60
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	51.2/50.0	70/70
											EH*D-1S05A	3.8/5.0	18.1/20.8	-	-	62.0/65.5	80/80
														9.6/8.7	-	71.6/74.2	90/90
														-	2.2/1.9 (1.7/1.5)	64.2/67.4	80/80
														9.6/8.7	2.2/1.9 (1.7/1.5)	73.8/76.1	90/90
											EH*D-1S10A	7.5/10.0	36.1/41.7	-	-	84.6/91.5	90/100
														9.6/8.7	-	94.2/100	100/110
														-	2.2/1.9 (1.7/1.5)	86.8/93.4	100/100
														9.6/8.7	2.2/1.9 (1.7/1.5)	96.4/102	110/110
											EH*D-1S15A	11.3/15.0	54.2/62.5	-	-	107/118	110/125
														9.6/8.7	-	117/126	125/150
														-	2.2/1.9 (1.7/1.5)	109/119	110/125
														9.6/8.7	2.2/1.9 (1.7/1.5)	119/128	125/150
DHH0481D	208/230/1/60	1	23.2	128	1	0.33	3.5	1	1	6.9	EH*D-1S20A	15.0/20.0	72.2/83.3	-	-	130/144	150/150
														9.6/8.7	-	139/152	150/175
														-	2.2/1.9 (1.7/1.5)	132/146	150/150
														9.6/8.7	2.2/1.9 (1.7/1.5)	142/154	150/175

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	Kw*	Fla	Fla	Fla	Mca	Mop
DHH0483D	208/230/3/60	1	12.0	105	1	0.33	3.5	1	1.0	6.9	-	-	-	-	-	25.4/25.4	35/35
											-	-	-	9.6/8.7	-	35.0/34.1	45/45
											-	-	-	-	2.2/1.9 (1.7/1.5)	27.6/27.3	35/35
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	37.2/36.0	45/45
											EH*D-3S05A	3.8/5.0	10.4/12.0	-	-	38.4/40.4	45/45
														9.6/8.7	-	48.0/49.1	50/50
														-	2.2/1.9 (1.7/1.5)	40.6/42.3	45/50
														9.6/8.7	2.2/1.9 (1.7/1.5)	50.2/51.0	60/60
											EH*D-3S10A	7.5/10.0	20.8/24.0	-	-	51.3/55.3	60/60
														9.6/8.7	-	60.9/64.0	70/70
														-	2.2/1.9 (1.7/1.5)	53.5/57.2	60/60
														9.6/8.7	2.2/1.9 (1.7/1.5)	63.1/65.9	70/70
											EH*D-3S15A	11.3/15.0	31.3/36.1	-	-	64.5/70.5	70/80
														9.6/8.7	-	74.1/79.2	80/80
														-	2.2/1.9 (1.7/1.5)	66.7/72.4	70/80
														9.6/8.7	2.2/1.9 (1.7/1.5)	76.3/81.1	80/90
											EH*D-3S20A	14.9/19.9	41.5/47.9	-	-	77.2/85.2	80/90
														9.6/8.7	-	86.8/93.9	90/100
														-	2.2/1.9 (1.7/1.5)	79.4/87.1	80/90
														9.6/8.7	2.2/1.9 (1.7/1.5)	89.0/95.8	90/100
DHH0483W	208/230/3/60	1	12.0	105	1	0.33	3.5	1	1.2	5.0	-	-	-	-	-	23.5/23.5	35/35
											-	-	-	9.6/8.7	-	33.1/32.2	45/40
											-	-	-	-	2.2/1.9 (1.7/1.5)	25.7/25.4	35/35
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	35.3/34.1	45/45
											EH*D-3S05A	3.8/5.0	10.4/12.0	-	-	36.5/38.5	45/45
														9.6/8.7	-	46.1/47.2	50/50
														-	2.2/1.9 (1.7/1.5)	38.7/40.4	45/45
														9.6/8.7	2.2/1.9 (1.7/1.5)	48.3/49.1	50/50
											EH*D-3S10A	7.5/10.0	20.8/24.0	-	-	49.4/53.4	50/60
														9.6/8.7	-	59.0/62.1	60/70
														-	2.2/1.9 (1.7/1.5)	51.6/55.3	60/60
														9.6/8.7	2.2/1.9 (1.7/1.5)	61.2/64.0	70/70
											EH*D-3S15A	11.3/15.0	31.3/36.1	-	-	62.6/68.6	70/70
														9.6/8.7	-	72.2/77.3	80/80
														-	2.2/1.9 (1.7/1.5)	64.8/70.5	70/80
														9.6/8.7	2.2/1.9 (1.7/1.5)	74.4/79.2	80/80
											EH*D-3S20A	14.9/19.9	41.5/47.9	-	-	75.3/83.3	80/90
														9.6/8.7	-	84.9/92.0	90/100
														-	2.2/1.9 (1.7/1.5)	77.5/85.2	80/90
														9.6/8.7	2.2/1.9 (1.7/1.5)	87.1/93.9	90/100
DHH0484D	460/3/60	1	6.2	61.8	1	0.33	1.6	1	1.2	2.5	-	-	-	-	-	11.9	15
											-	-	-	4.3	-	16.2	20
											-	-	-	-	0.9 (0.5)	12.8	15
											-	-	-	4.3	0.9 (0.5)	17.1	20
											EH*D-4S05A	5.0	6.0	-	-	19.4	20
														4.3	-	23.7	25
														-	0.9 (0.5)	20.3	25
														4.3	0.9 (0.5)	24.6	25
											EH*D-4S10A	10.0	12.0	-	-	26.9	30
														4.3	-	31.2	35
														-	0.9 (0.5)	27.8	30
														4.3	0.9 (0.5)	32.1	35
											EH*D-4S15A	15.0	18.0	-	-	34.4	35
														4.3	-	38.7	40
														-	0.9 (0.5)	35.3	40
														4.3	0.9 (0.5)	39.6	40
											EH*D-4S20A	20.0	24.1	-	-	41.9	45
														4.3	-	46.2	50
														-	0.9 (0.5)	42.8	45
														4.3	0.9 (0.5)	47.1	50

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	Kw*	Fla	Fla	Fla	Mca	Mop
DHH0484W	460/3/60	1	6.2	61.8	1	0.33	1.6	1	1.2	2.5	-	-	-	-	-	11.9	15
											-	-	-	4.3	-	16.2	20
											-	-	-	-	0.9 (0.5)	12.8	15
											-	-	-	4.3	0.9 (0.5)	17.1	20
											EH*D-4S05A	5.0	6.0	-	-	19.4	20
														4.3	-	23.7	25
														-	0.9 (0.5)	20.3	25
														4.3	0.9 (0.5)	24.6	25
											EH*D-4S10A	10.0	12.0	-	-	26.9	30
														4.3	-	31.2	35
														-	0.9 (0.5)	27.8	30
														4.3	0.9 (0.5)	32.1	35
											EH*D-4S15A	15.0	18.0	-	-	34.4	35
														4.3	-	38.7	40
														-	0.9 (0.5)	35.3	40
														4.3	0.9 (0.5)	39.6	40
											EH*D-4S20A	20.0	24.1	-	-	41.9	45
														4.3	-	46.2	50
														-	0.9 (0.5)	42.8	45
														4.3	0.9 (0.5)	47.1	50
DHH0487D	575/3/60	1	4.5	39	1	0.33	1.54	1	1.2	2.0	-	-	-	-	-	9.1	15
											-	-	-	3.5	-	12.6	15
											-	-	-	-	1.0	10.1	15
											-	-	-	3.5	1.0	13.6	15
											EH*D-7S05A	5.0	4.8	-	-	15.2	20
														3.5	-	18.7	20
														-	1.0	16.2	20
														3.5	1.0	19.7	20
											EH*D-7S10A	10.0	9.6	-	-	21.2	25
														3.5	-	24.7	25
														-	1.0	22.2	25
														3.5	1.0	25.7	30
											EH*D-7S15A	15.0	14.4	-	-	27.2	30
														3.5	-	30.7	35
														-	1.0	28.2	30
														3.5	1.0	31.7	35
											EH*D-7S20A	20.0	19.2	-	-	33.2	35
														3.5	-	36.7	40
														-	1.0	34.2	35
														3.5	1.0	37.7	40
DHH0487W	575/3/60	1	4.5	39	1	0.33	1.54	1	1.2	2.0	-	-	-	-	-	9.1	15
											-	-	-	3.5	-	12.6	15
											-	-	-	-	1.0	10.1	15
											-	-	-	3.5	1.0	13.6	15
											EH*D-7S05A	5.0	4.8	-	-	15.2	20
														3.5	-	18.7	20
														-	1.0	16.2	20
														3.5	1.0	19.7	20
											EH*D-7S10A	10.0	9.6	-	-	21.2	25
														3.5	-	24.7	25
														-	1.0	22.2	25
														3.5	1.0	25.7	30
											EH*D-7S15A	15.0	14.4	-	-	27.2	30
														3.5	-	30.7	35
														-	1.0	28.2	30
														3.5	1.0	31.7	35
											EH*D-7S20A	20.0	19.2	-	-	33.2	35
														3.5	-	36.7	40
														-	1.0	34.2	35
														3.5	1.0	37.7	40


Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	Kw*	Fla	Fla	Fla	Mca	Mop
DHH0601D	208/230/1/60	1	27.1	178	1	0.33	3.5	1	1.0	6.9	-	-	-	-	-	44.2/44.2	70/70
											-	-	-	9.6/8.7	-	53.8/52.9	80/80
											-	-	-	-	2.2/1.9 (1.7/1.5)	46.4/46.1	70/70
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	56.0/54.8	80/80
											EH*D-1S05A	3.8/5.0	18.1/20.8	-	-	66.8/70.3	80/90
														9.6/8.7	-	76.4/79.0	90/100
														-	2.2/1.9 (1.7/1.5)	69.0/72.2	90/90
														9.6/8.7	2.2/1.9 (1.7/1.5)	78.6/80.9	100/100
											EH*D-1S10A	7.5/10.0	36.1/41.7	-	-	89.4/96.3	100/110
														9.6/8.7	-	99.0/105	110/110
														-	2.2/1.9 (1.7/1.5)	91.6/98.2	100/110
														9.6/8.7	2.2/1.9 (1.7/1.5)	101/107	110/110
											EH*D-1S15A	11.3/15.0	54.2/62.5	-	-	112/122	125/125
														9.6/8.7	-	122/131	125/150
														-	2.2/1.9 (1.7/1.5)	114/124	125/125
														9.6/8.7	2.2/1.9 (1.7/1.5)	124/133	125/150
											EH*D-1S20A	15.0/20.0	72.2/83.3	-	-	135/148	150/150
														9.6/8.7	-	144/157	150/175
														-	2.2/1.9 (1.7/1.5)	137/150	150/175
														9.6/8.7	2.2/1.9 (1.7/1.5)	146/159	150/175
DHH0603D	208/230/3/60	1	15.2	140	1	0.33	3.5	1	1.0	6.9	-	-	-	-	-	29.4/29.4	40/40
											-	-	-	9.6/8.7	-	39.0/38.1	50/50
											-	-	-	-	2.2/1.9 (1.7/1.5)	31.6/31.3	45/45
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	41.2/40.0	50/50
											EH*D-3S05A	3.8/5.0	10.4/12.0	-	-	42.4/44.4	50/50
														9.6/8.7	-	52.0/53.1	60/60
														-	2.2/1.9 (1.7/1.5)	44.6/46.3	50/50
														9.6/8.7	2.2/1.9 (1.7/1.5)	54.2/55.0	60/60
											EH*D-3S10A	7.5/10.0	20.8/24.0	-	-	55.3/59.3	60/60
														9.6/8.7	-	64.9/68.0	70/70
														-	2.2/1.9 (1.7/1.5)	57.5/61.2	60/70
														9.6/8.7	2.2/1.9 (1.7/1.5)	67.1/69.9	70/70
											EH*D-3S15A	11.3/15.0	31.3/36.1	-	-	68.5/74.5	70/80
														9.6/8.7	-	78.1/83.2	80/90
														-	2.2/1.9 (1.7/1.5)	70.7/76.4	80/80
														9.6/8.7	2.2/1.9 (1.7/1.5)	80.3/85.1	90/90
											EH*D-3S20A	14.9/19.9	41.5/47.9	-	-	81.2/89.2	90/90
														9.6/8.7	-	90.8/97.9	100/100
														-	2.2/1.9 (1.7/1.5)	83.4/91.1	90/100
														9.6/8.7	2.2/1.9 (1.7/1.5)	93.0/99.8	100/100
DHH0603W	208/230/3/60	1	15.2	140	1	0.33	3.5	1	2.3	7.7	-	-	-	-	-	30.2/30.2	45/45
											-	-	-	9.6/8.7	-	39.8/38.9	50/50
											-	-	-	-	2.2/1.9 (1.7/1.5)	32.4/32.1	45/45
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	42.0/40.8	50/50
											EH*D-3S05A	3.8/5.0	10.4/12.0	-	-	43.2/45.2	50/50
														9.6/8.7	-	52.8/53.9	60/60
														-	2.2/1.9 (1.7/1.5)	45.4/47.1	50/50
														9.6/8.7	2.2/1.9 (1.7/1.5)	55.0/55.8	60/60
											EH*D-3S10A	7.5/10.0	20.8/24.0	-	-	56.1/60.1	60/70
														9.6/8.7	-	65.7/68.8	70/70
														-	2.2/1.9 (1.7/1.5)	58.3/62.0	60/70
														9.6/8.7	2.2/1.9 (1.7/1.5)	67.9/70.7	70/80
											EH*D-3S15A	11.3/15.0	31.3/36.1	-	-	69.3/75.3	70/80
														9.6/8.7	-	78.9/84.0	80/90
														-	2.2/1.9 (1.7/1.5)	71.5/77.2	80/80
														9.6/8.7	2.2/1.9 (1.7/1.5)	81.1/85.9	90/90
											EH*D-3S20A	14.9/19.9	41.5/47.9	-	-	82.0/90.0	90/90
														9.6/8.7	-	91.6/98.7	100/100
														-	2.2/1.9 (1.7/1.5)	84.2/91.9	90/100
														9.6/8.7	2.2/1.9 (1.7/1.5)	93.8/101	100/110

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	Kw*	Fla	Fla	Fla	Mca	Mop
DHH0604D	460/3/60	1	7.4	54.7	1	0.33	1.6	1	1.2	2.5	-	-	-	-	-	13.3	20
											-	-	-	4.3	-	17.6	20
											-	-	-	-	0.9 (0.5)	14.2	20
											-	-	-	4.3	0.9 (0.5)	18.5	25
											EH*D-4S05A	5.0	6.0	-	-	20.8	25
														4.3	-	25.1	30
														-	0.9 (0.5)	21.7	25
														4.3	0.9 (0.5)	26.0	30
											EH*D-4S10A	10.0	12.0	-	-	28.3	30
														4.3	-	32.6	35
														-	0.9 (0.5)	29.2	30
														4.3	0.9 (0.5)	33.5	35
											EH*D-4S15A	15.0	18.0	-	-	35.9	40
														4.3	-	40.2	45
														-	0.9 (0.5)	36.8	40
														4.3	0.9 (0.5)	41.1	45
											EH*D-4S20A	20.0	24.1	-	-	43.4	45
														4.3	-	47.7	50
														-	0.9 (0.5)	44.3	45
														4.3	0.9 (0.5)	48.6	50
DHH0604W	460/3/60	1	7.4	54.7	1	0.33	1.6	1	2.3	4.5	-	-	-	-	-	15.3	20
											-	-	-	4.3	-	19.6	25
											-	-	-	-	0.9 (0.5)	16.2	20
											-	-	-	4.3	0.9 (0.5)	20.5	25
											EH*D-4S05A	5.0	6.0	-	-	22.8	25
														4.3	-	27.1	30
														-	0.9 (0.5)	23.7	25
														4.3	0.9 (0.5)	28.0	30
											EH*D-4S10A	10.0	12.0	-	-	30.3	35
														4.3	-	34.6	35
														-	0.9 (0.5)	31.2	35
														4.3	0.9 (0.5)	35.5	40
											EH*D-4S15A	15.0	18.0	-	-	37.9	40
														4.3	-	42.2	45
														-	0.9 (0.5)	38.8	40
														4.3	0.9 (0.5)	43.1	45
											EH*D-4S20A	20.0	24.1	-	-	45.4	50
														4.3	-	49.7	50
														-	0.9 (0.5)	46.3	50
														4.3	0.9 (0.5)	50.6	60
DHH0607D	575/3/60	1	5.6	47.8	1	0.33	1.54	1	1.2	2.0	-	-	-	-	-	10.6	15
											-	-	-	3.5	-	14.1	15
											-	-	-	-	1.0	11.6	15
											-	-	-	3.5	1.0	15.1	20
											EH*D-7S05A	5.0	4.8	-	-	16.6	20
														3.5	-	20.1	25
														-	1.0	17.6	20
														3.5	1.0	21.1	25
											EH*D-7S10A	10.0	9.6	-	-	22.6	25
														3.5	-	26.1	30
														-	1.0	23.6	25
														3.5	1.0	27.1	30
											EH*D-7S15A	15.0	14.4	-	-	28.6	30
														3.5	-	32.1	35
														-	1.0	29.6	30
														3.5	1.0	33.1	35
											EH*D-7S20A	20.0	19.2	-	-	34.6	35
														3.5	-	38.1	40
														-	1.0	35.6	40
														3.5	1.0	39.1	40

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	Kw*	Fla	Fla	Fla	Mca	Mop
DHH0607W	575/3/60	1	5.6	47.8	1	0.33	1.54	1	2.3	3.8	-	-	-	-	-	12.4	15
											-	-	-	3.5	-	15.9	20
											-	-	-	-	1.0	13.4	15
											-	-	-	3.5	1.0	16.9	20
											EH*D-7S05A	5.0	4.8	-	-	18.4	20
														3.5	-	21.9	25
														-	1.0	19.4	20
														3.5	1.0	22.9	25
											EH*D-7S10A	10.0	9.6	-	-	24.4	25
														3.5	-	27.9	30
														-	1.0	25.4	30
														3.5	1.0	28.9	30
											EH*D-7S15A	15.0	14.4	-	-	30.4	35
														3.5	-	33.9	35
														-	1.0	31.4	35
														3.5	1.0	34.9	35
											EH*D-7S20A	20.0	19.2	-	-	36.4	40
														3.5	-	39.9	40
														-	1.0	37.4	40
														3.5	1.0	40.9	45
DHH0723D	208/230/3/60	1	16.1	155	1	0.33	2.0	1	1.2	5.0	-	-	-	-	-	27.2/27.2	40/40
											-	-	-	9.6/8.7	-	36.8/35.9	50/50
											-	-	-	-	2.2/1.9 (1.7/1.5)	29.4/29.1	40/40
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	39.0/37.8	50/50
											EH*D-3S05A	3.8/5.0	10.4/12.0	-	-	40.2/42.2	50/50
														9.6/8.7	-	49.8/50.9	60/60
														-	2.2/1.9 (1.7/1.5)	42.4/44.1	50/50
														9.6/8.7	2.2/1.9 (1.7/1.5)	52.0/52.8	60/60
											EH*D-3S10A	7.5/10.0	20.8/24.0	-	-	53.1/57.1	60/60
														9.6/8.7	-	62.7/65.8	70/70
														-	2.2/1.9 (1.7/1.5)	55.3/59.0	60/60
														9.6/8.7	2.2/1.9 (1.7/1.5)	64.9/67.7	70/70
											EH*D-3S15A	11.3/15.0	31.3/36.1	-	-	66.3/72.3	70/80
														9.6/8.7	-	75.9/81.0	80/90
														-	2.2/1.9 (1.7/1.5)	68.5/74.2	70/80
														9.6/8.7	2.2/1.9 (1.7/1.5)	78.1/82.9	80/90
											EH*D-3S20A	14.9/19.9	41.5/47.9	-	-	79.0/87.0	80/90
														9.6/8.7	-	88.6/95.7	90/100
														-	2.2/1.9 (1.7/1.5)	81.2/88.9	90/90
														9.6/8.7	2.2/1.9 (1.7/1.5)	90.8/97.6	100/100
DHH0723W	208/230/3/60	1	16.1	155	1	0.33	2.0	1	2.3	7.7	-	-	-	-	-	105/117	110/125
											-	-	-	9.6/8.7	-	115/126	125/150
											-	-	-	-	2.2/1.9 (1.7/1.5)	108/119	110/125
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	117/128	125/150
											EH*D-3S05A	3.8/5.0	10.4/12.0	-	-	29.9/29.9	45/45
														9.6/8.7	-	39.5/38.6	50/50
														-	2.2/1.9 (1.7/1.5)	32.1/31.8	45/45
														9.6/8.7	2.2/1.9 (1.7/1.5)	41.7/40.5	50/50
											EH*D-3S10A	7.5/10.0	20.8/24.0	-	-	42.9/44.9	50/50
														9.6/8.7	-	52.5/53.6	60/60
														-	2.2/1.9 (1.7/1.5)	45.1/46.8	50/50
														9.6/8.7	2.2/1.9 (1.7/1.5)	54.7/55.5	60/60
											EH*D-3S15A	11.3/15.0	31.3/36.1	-	-	55.8/59.8	60/60
														9.6/8.7	-	65.4/68.5	70/70
														-	2.2/1.9 (1.7/1.5)	58.0/61.7	60/70
														9.6/8.7	2.2/1.9 (1.7/1.5)	67.6/70.4	70/80
											EH*D-3S20A	14.9/19.9	41.5/47.9	-	-	69.0/75.0	70/80
														9.6/8.7	-	78.6/83.7	80/90
														-	2.2/1.9 (1.7/1.5)	71.2/76.9	80/80
														9.6/8.7	2.2/1.9 (1.7/1.5)	80.8/85.6	90/90
DHH0723W	208/230/3/60	1	16.1	155	1	0.33	2.0	1	2.3	7.7	EH*D-3S30B	22.5/30.0	62.5/72.2	-	-	81.7/89.7	90/90
														9.6/8.7	-	91.3/98.4	100/100
														-	2.2/1.9 (1.7/1.5)	83.9/91.6	90/100
														9.6/8.7	2.2/1.9 (1.7/1.5)	93.5/100	100/110
											EH*D-3S30B	22.5/30.0	62.5/72.2	-	-	108/120	110/125
														9.6/8.7	-	118/129	125/150
														-	2.2/1.9 (1.7/1.5)	110/122	125/125
														9.6/8.7	2.2/1.9 (1.7/1.5)	120/131	125/150

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	Kw*	Fla	Fla	Fla	Mca	Mop
DHH0724D	460/3/60	1	7.0	70.8	1	0.33	0.85	1	1.2	2.5	-	-	-	-	-	12.2	15
											-	-	-	4.3	-	16.5	20
											-	-	-	-	0.9 (0.5)	13.1	15
											-	-	-	4.3	0.9 (0.5)	17.4	20
											-	-	-	-	-	19.7	25
											EH*D-4S05A	5.0	6.0	4.3	-	24.0	25
														-	0.9 (0.5)	20.6	25
														4.3	0.9 (0.5)	24.9	30
														-	-	27.2	30
											EH*D-4S10A	10.0	12.0	4.3	-	31.5	35
														-	0.9 (0.5)	28.1	30
														4.3	0.9 (0.5)	32.4	35
											EH*D-4S15A	15.0	18.0	-	-	34.7	35
														4.3	-	39.0	40
														-	0.9 (0.5)	35.6	40
														4.3	0.9 (0.5)	39.9	40
											EH*D-4S20A	20.0	24.1	-	-	42.2	45
														4.3	-	46.5	50
														-	0.9 (0.5)	43.1	45
														4.3	0.9 (0.5)	47.4	50
											EH*D-4S30A	30.0	36.1	-	-	57.3	60
														4.3	-	61.6	70
														-	0.9 (0.5)	58.2	60
														4.3	0.9 (0.5)	62.5	70
DHH0724W	460/3/60	1	7.0	70.8	1	0.33	0.85	1	2.3	4.5	-	-	-	-	-	14.2	20
											-	-	-	4.3	-	18.5	25
											-	-	-	-	0.9 (0.5)	15.1	20
											-	-	-	4.3	0.9 (0.5)	19.4	25
											EH*D-4S05A	5.0	6.0	-	-	21.7	25
														4.3	-	26.0	30
														-	0.9 (0.5)	22.6	25
														4.3	0.9 (0.5)	26.9	30
											EH*D-4S10A	10.0	12.0	-	-	29.2	30
														4.3	-	33.5	35
														-	0.9 (0.5)	30.1	35
														4.3	0.9 (0.5)	34.4	35
											EH*D-4S15A	15.0	18.0	-	-	36.7	40
														4.3	-	41.0	45
														-	0.9 (0.5)	37.6	40
														4.3	0.9 (0.5)	41.9	45
											EH*D-4S20A	20.0	24.1	-	-	44.2	45
														4.3	-	48.5	50
														-	0.9 (0.5)	45.1	50
														4.3	0.9 (0.5)	49.4	50
											EH*D-4S30B	30.0	36.1	-	-	59.3	60
														4.3	-	63.6	70
														-	0.9 (0.5)	60.2	70
														4.3	0.9 (0.5)	64.5	70
DHH0727D	575/3/60	1	6.0	58.2	1	0.33	0.67	1	1.2	2.0	-	-	-	-	-	10.2	15
											-	-	-	3.5	-	13.7	15
											-	-	-	-	1.0	11.2	15
											-	-	-	3.5	1.0	14.7	20
											EH*D-7S05A	5.0	4.8	-	-	16.2	20
														3.5	-	19.7	20
														-	1.0	17.2	20
														3.5	1.0	20.7	25
											EH*D-7S10A	10.0	9.6	-	-	22.2	25
														3.5	-	25.7	30
														-	1.0	23.2	25
														3.5	1.0	26.7	30
											EH*D-7S15A	15.0	14.4	-	-	28.2	30
														3.5	-	31.7	35
														-	1.0	29.2	30
														3.5	1.0	32.7	35
											EH*D-7S20A	20.0	19.2	-	-	34.2	35
														3.5	-	37.7	40
														-	1.0	35.2	40
														3.5	1.0	38.7	40
											EH*D-7S30A	30.0	28.9	-	-	46.3	50
														3.5	-	49.8	50
														-	1.0	47.3	50
														3.5	1.0	50.8	60

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	Type	HP	FLA	Part #	Kw*	Fla	Fla	Fla	Mca	Mop
DHH0727W	575/3/60	1	6.0	58.2	1	0.33	0.67	1	2.3	3.8	-	-	-	-	-	12.0	15
											-	-	-	3.5	-	15.5	20
											-	-	-	-	1.0	13.0	15
											-	-	-	3.5	1.0	16.5	20
											EH*D-7S05A	5.0	4.8	-	-	18.0	20
														3.5	-	21.5	25
														-	1.0	19.0	20
														3.5	1.0	22.5	25
											EH*D-7S10A	10.0	9.6	-	-	24.0	25
														3.5	-	27.5	30
														-	1.0	25.0	30
														3.5	1.0	28.5	30
											EH*D-7S15A	15.0	14.4	-	-	30.0	35
														3.5	-	33.5	35
														-	1.0	31.0	35
														3.5	1.0	34.5	35
											EH*D-7S20A	20.0	19.2	-	-	36.0	40
														3.5	-	39.5	40
														-	1.0	37.0	40
														3.5	1.0	40.5	45
											EH*D-7S30B	30.0	28.9	-	-	48.1	50
														3.5	-	51.6	60
														-	1.0	49.1	50
														3.5	1.0	52.6	60



High Voltage: Disconnect all power before servicing or installing this unit. Multiple power sources may be present. Failure to do so may cause property damage, personal injury, or death.



