

Model	DSH0361D000001S	DSH0363D000001S	DSH0364D000001S	DSH0367D000001S
COOLING CAPACITY				
Total BTU/h	35,000	35,000	35,000	35,000
SEER2 / EER2 (3-5T) or IEER / EER (6T)	14 / 12	14 / 12	14 / 12	14 / 12
AHRI Reference #	215414898	215439539	215439540	215439541
HEATING CAPACITY				
BTU/h (47° F)	33,600	33,600	33,600	33,600
HSPF2 (3-5T) or COP @47 / COP @ 17 (6T)	6.90	6.90	6.90	6.90
EVAPORATOR MOTOR / RTPF (ROUND TUBE PLATE FIN)				
Motor Type	Direct Drive	Direct Drive	Direct Drive	Direct Drive
External Static Pressure (ESP)	Standard	Standard	Standard	Standard
Wheel Dia. X Width	12 X 11	12 X 11	12 X 11	12 X 11
Indoor Nominal CFM	1220	1220	1220	1220
RPM	1200 MAX	1200 MAX	1500 MAX	1500 MAX
Indoor Horsepower	0.75	0.75	1.20	1.20
Filter Size (in)	14 X 20 X 2 (4)	14 X 20 X 2 (4)	14 X 20 X 2 (4)	14 X 20 X 2 (4)
Drain Size (NPT)	3/4	3/4	3/4	3/4
R-32 Refrigerant Charge (oz.)	140	140	140	140
Evaporator Coil Face Area (ft²)	7.33	7.33	7.33	7.33
Rows Deep/ Fins per Inch	3 / 16	3 / 16	3 / 16	3 / 16
CONDENSER FAN / RTPF (ROUND TUBE PLATE FIN)				
Quantity of Condenser Fan Motors	1	1	1	1
RPM (High/Low stage)	810	810	810	810
Outdoor Horsepower	1/6	1/6	1/6	1/6
Fan Diameter/ # Fan Blades	22 / 3	22 / 3	22 / 3	22 / 3
Face Area (ft²)	12.67	12.67	12.67	12.67
Rows Deep / Fins per Inch	2 / 16	2 / 16	2 / 16	2 / 16
COMPRESSOR				
Quantity / Type / Stages	1 / Scroll / 1	1 / Scroll / 1	1 / Scroll / 1	1 / Scroll / 1
Compressor RLA / LRA	16.4 / 88	10.6 / 97.5	4.9 / 44.3	3.8 / 27.1
ELECTRICAL DATA				
Voltage-Phase-Frequency	208/230-1-60	208/230-3-60	460-3-60	575-3-60
Indoor Blower FLA	5.7	5.7	2.5	2
Max External Static (In. W.C.)	0.8	0.8	0.8	0.8
Outdoor Fan FLA	0.95	0.95	0.48	0.39
Min. Circuit Ampacity ¹	27.2/27.2	19.9/19.9	9.1	7.2
Max. Overcurrent Protection (A) ²	40/40	30/30	15	15
Power Supply Conduit Hole Dia. (in)	1.125	1.125	1.125	1.125
Low-Voltage Conduit Hole Dia. (in)	0.5	0.5	0.5	0.5
OPERATING WEIGHT (LBS.)				
Operating Weight (lbs)	536	535	543	543
SHIPPING WEIGHT (LBS.)				
Ship Weight (lbs)	606	605	613	613

¹ Wire size should be determined in accordance with National Electrical Codes. Extensive wire runs will require larger wire sizes.

² May use fuses or HACR-type circuit breakers of the same size as noted.

Note: Always check the S&R plate for electrical data on the unit being installed.

Model	DSH0481D000001S	DSH0483D000001S	DSH0484D000001S	DSH0487D000001S
COOLING CAPACITY				
Total BTU/h	46,000	46,000	46,000	46,000
SEER2 / EER2 (3-5T) or IEER / EER (6T)	13.7 / 11.8	13.7 / 11.8	13.7 / 11.8	13.7 / 11.8
AHRI Reference #	215414899	215414900	215414901	215414902
HEATING CAPACITY				
BTU/h (47° F)	45,000	45,000	45,000	45,000
HSPF2 (3-5T) or COP @47 / COP @ 17 (6T)	6.90	6.90	6.90	6.90
EVAPORATOR MOTOR / RTPF (ROUND TUBE PLATE FIN)				
Motor Type	Direct Drive	Direct Drive	Direct Drive	Direct Drive
External Static Pressure (ESP)	Standard	Standard	Standard	Standard
Wheel Dia. X Width	12 X 11	12 X 11	12 X 11	12 X 11
Indoor Nominal CFM	1580	1580	1580	1580
RPM	1200 MAX	1200 MAX	1500 MAX	1500 MAX
Indoor Horsepower	1.00	1.00	1.20	1.20
Filter Size (in)	14 X 20 X 2 (4)	14 X 20 X 2 (4)	14 X 20 X 2 (4)	14 X 20 X 2 (4)
Drain Size (NPT)	3/4	3/4	3/4	3/4
R-32 Refrigerant Charge (oz.)	168	168	168	168
Evaporator Coil Face Area (ft²)	7.33	7.33	7.33	7.33
Rows Deep/ Fins per Inch	4 / 16	4 / 16	4 / 16	4 / 16
CONDENSER FAN / RTPF (ROUND TUBE PLATE FIN)				
Quantity of Condenser Fan Motors	1	1	1	1
RPM (High/Low stage)	1075	1075	1075	1075
Outdoor Horsepower	1/4	1/4	1/4	1/4
Fan Diameter/ # Fan Blades	22 / 4	22 / 4	22 / 4	22 / 4
Face Area (ft²)	17.28	17.28	17.28	17.28
Rows Deep / Fins per Inch	2 / 16	2 / 16	2 / 16	2 / 16
COMPRESSOR				
Quantity / Type / Stages	1 / Scroll / 1	1 / Scroll / 1	1 / Scroll / 1	1 / Scroll / 1
Compressor RLA / LRA	19.4 / 128	12.2 / 120	5.8 / 55.1	5.8 / 41.0
ELECTRICAL DATA				
Voltage-Phase-Frequency	208/230-1-60	208/230-3-60	460-3-60	575-3-60
Indoor Blower FLA	6.9	6.9	2.5	2
Max External Static (In. W.C.)	0.8	0.8	0.8	0.8
Outdoor Fan FLA	1.4	1.4	0.7	0.55
Min. Circuit Ampacity ¹	32.5 / 32.5	23.5 / 23.5	10.4	9.8
Max. Overcurrent Protection (A) ²	50/50	35/35	15	15
Power Supply Conduit Hole Dia. (in)	1.125	1.125	1.125	1.125
Low-Voltage Conduit Hole Dia. (in)	0.5	0.5	0.5	0.5
OPERATING WEIGHT (LBS.)				
Operating Weight (lbs)	587	582	586	586
SHIPPING WEIGHT (LBS.)				
Ship Weight (lbs)	657	652	656	656

¹ Wire size should be determined in accordance with National Electrical Codes. Extensive wire runs will require larger wire sizes.

² May use fuses or HACR-type circuit breakers of the same size as noted.

Note: Always check the S&R plate for electrical data on the unit being installed.

Model	DSH0601D000001S	DSH0603D000001S	DSH0604D000001S	DSH0607D000001S
COOLING CAPACITY				
Total BTU/h	57,500	57,500	57,500	57,500
SEER2 / EER2 (3-5T) or IEER / EER (6T)	13.7 / 11.8	13.7 / 11.8	13.7 / 11.8	13.7 / 11.8
AHRI Reference #	215414903	215414904	215414905	215414906
HEATING CAPACITY				
BTU/h (47° F)	55,000	55,000	55,000	55,000
HSPF2 (3-5T) or COP @47 / COP @ 17 (6T)	6.90	6.90	6.90	6.90
EVAPORATOR MOTOR / RTPF (ROUND TUBE PLATE FIN)				
Motor Type	Direct Drive	Direct Drive	Direct Drive	Direct Drive
External Static Pressure (ESP)	Standard	Standard	Standard	Standard
Wheel Dia. X Width	12 X 11	12 X 11	12 X 11	12 X 11
Indoor Nominal CFM	1870	1870	1870	1870
RPM	1200 MAX	1200 MAX	1500 MAX	1500 MAX
Indoor Horsepower	1.00	1.00	1.20	1.20
Filter Size (in)	14 X 20 X 2 (4)	14 X 20 X 2 (4)	14 X 20 X 2 (4)	14 X 20 X 2 (4)
Drain Size (NPT)	3/4	3/4	3/4	3/4
R-32 Refrigerant Charge (oz.)	163	163	163	163
Evaporator Coil Face Area (ft²)	7.33	7.33	7.33	7.33
Rows Deep/ Fins per Inch	4 / 16	4 / 16	4 / 16	4 / 16
CONDENSER FAN / RTPF (ROUND TUBE PLATE FIN)				
Quantity of Condenser Fan Motors	1	1	1	1
RPM (High/Low stage)	1122	1122	1050	1050
Outdoor Horsepower	1/3	1/3	1/3	1/3
Fan Diameter/ # Fan Blades	22 / 4	22 / 4	22 / 4	22 / 4
Face Area (ft²)	17.28	17.28	17.28	17.28
Rows Deep / Fins per Inch	2 / 20	2 / 20	2 / 20	2 / 20
COMPRESSOR				
Quantity / Type / Stages	1 / Scroll / 1	1 / Scroll / 1	1 / Scroll / 1	1 / Scroll / 1
Compressor RLA / LRA	24.0 / 156	17.3 / 155	7.7 / 58.1	7.0 / 47.8
ELECTRICAL DATA				
Voltage-Phase-Frequency	208/230-1-60	208/230-3-60	460-3-60	575-3-60
Indoor Blower FLA	6.9	6.9	2.5	2
Max External Static (In. W.C.)	0.8	0.8	0.8	0.8
Outdoor Fan FLA	2	2	0.85	0.67
Min. Circuit Ampacity ¹	38.9 / 38.9	30.5 / 30.5	13.0	11.5
Max. Overcurrent Protection (A) ²	60/60	45/45	20	15
Power Supply Conduit Hole Dia. (in)	1.125	1.125	1.125	1.125
Low-Voltage Conduit Hole Dia. (in)	0.5	0.5	0.5	0.5
OPERATING WEIGHT (LBS.)				
Operating Weight (lbs)	600	596	600	600
SHIPPING WEIGHT (LBS.)				
Ship Weight (lbs)	670	666	670	670

¹ Wire size should be determined in accordance with National Electrical Codes. Extensive wire runs will require larger wire sizes.

² May use fuses or HACR-type circuit breakers of the same size as noted.

Note: Always check the S&R plate for electrical data on the unit being installed.