

DSH0363W / DSH0364W / DSH0367W DOWNSHOT

TAP	STATIC	AIRFLOW (CFM)	RPM	WATTS	BHP
T1 *	0.8	1100	927	218	0.36
	0.9	1042	960	225	0.38
	1	983	993	233	0.39
	1.1	935	1027	240	0.40
	1.2	873	1058	248	0.42
	1.3	824	1087	253	0.43
	1.4	775	1113	258	0.44
	1.5	725	1138	262	0.45
	1.6	668	1164	276	0.46
	1.7	634	1188	283	0.47
T2	1.8	601	1212	290	0.48
	0.8	1418	986	303	0.52
	0.9	1368	1017	313	0.54
	1	1319	1047	323	0.55
	1.1	1269	1077	332	0.57
	1.2	1218	1107	341	0.59
	1.3	1167	1137	350	0.60
	1.4	1116	1164	358	0.62
	1.5	1065	1192	365	0.63
	1.6	1014	1216	371	0.64
T3	1.7	973	1241	379	0.66
	1.8	931	1265	387	0.67
	0.8	-	-	-	-
	0.9	1500	1045	363	0.63
	1	1472	1074	374	0.64
	1.1	1422	1103	383	0.66
	1.2	1376	1132	393	0.68
	1.3	1325	1161	404	0.70
	1.4	1274	1189	413	0.71
	1.5	1224	1216	422	0.73
T4	1.6	1176	1241	426	0.74
	1.7	1132	1265	434	0.76
	1.8	1088	1290	442	0.77
	0.8	1401	983	298	0.51
	0.9	1351	1014	308	0.53
	1	1301	1044	318	0.54
	1.1	1251	1074	326	0.56
	1.2	1200	1104	335	0.58
	1.3	1149	1134	345	0.59
	1.4	1098	1162	352	0.61
T5	1.5	1047	1189	359	0.62
	1.6	995	1214	366	0.63
	1.7	954	1238	373	0.65
	1.8	913	1262	381	0.66
	0.8	1495	1001	328	0.57
	0.9	1448	1031	339	0.58
	1	1400	1061	349	0.60
	1.1	1351	1091	358	0.62
	1.2	1302	1120	367	0.63
	1.3	1251	1150	378	0.65
	1.4	1200	1177	386	0.67
	1.5	1149	1205	395	0.68
	1.6	1100	1229	399	0.70
	1.7	1057	1254	407	0.71
	1.8	1014	1278	415	0.72

DSH0363W / DSH0364W / DSH0367W DOWNSHOT

TAP	STATIC	AIRFLOW (CFM)	RPM	WATTS	BHP
T1'	0.8	1317	967	273	0.47
	0.9	1265	998	282	0.48
	1	1213	1029	292	0.50
	1.1	1163	1061	300	0.51
	1.2	1109	1091	308	0.53
	1.3	1058	1121	317	0.54
	1.4	1007	1148	323	0.56
	1.5	956	1175	330	0.57
	1.6	903	1200	338	0.58
	1.7	-	-	-	-
T2'	1.8	-	-	-	-
	0.8	-	-	-	-
	0.9	-	-	-	-
	1	1546	1088	402	0.69
	1.1	1497	1116	412	0.71
	1.2	1453	1144	421	0.73
	1.3	1402	1174	433	0.75
	1.4	1352	1201	443	0.76
	1.5	1302	1228	452	0.78
	1.6	1255	1253	456	0.80
T3'	1.7	1211	1277	464	0.81
	1.8	1167	1302	473	0.83
	0.8	-	-	-	-
	0.9	-	-	-	-
	1	-	-	-	-
	1.1	1645	1143	474	0.82
	1.2	1604	1170	484	0.83
	1.3	1555	1198	497	0.85
	1.4	1507	1225	508	0.87
	1.5	1459	1253	519	0.89
T4'	1.6	1415	1277	523	0.91
	1.7	1370	1301	532	0.93
	1.8	1325	1326	541	0.95
	0.8	-	-	-	-
	0.9	-	-	-	-
	1	1495	1078	382	0.66
	1.1	1445	1107	392	0.68
	1.2	1400	1135	401	0.69
	1.3	1349	1165	413	0.71
	1.4	1298	1193	422	0.73
T5'	1.5	1248	1220	431	0.74
	1.6	1200	1244	435	0.76
	1.7	1156	1269	443	0.77
	1.8	1112	1293	452	0.79
	0.8	-	-	-	-
	0.9	-	-	-	-
	1	-	-	-	-
	1.1	-	-	-	-
	1.2	1485	1150	434	0.75
	1.3	1435	1179	446	0.77
	1.4	1385	1206	456	0.79
	1.5	1335	1233	466	0.80
	1.6	1289	1258	469	0.82
	1.7	1245	1282	478	0.84
	1.8	1200	1307	487	0.85

* In DSH0363W / DSH0364W / DSH0367W, DSH0483W / DSH0484W / DSH0487W, AND DSH06083W / DSH0604W / DSH0607W DOWNSHOT & HORIZONTAL Tables, T1 values are for fan mode only

DSH0363W / DSH0364W / DSH0367W HORIZONTAL

TAP	STATIC	AIRFLOW (CFM)	RPM	WATTS	BHP
T1 *	0.8	1181	880	208	0.35
	0.9	1118	917	215	0.36
	1	1055	954	222	0.37
	1.1	1000	987	228	0.39
	1.2	944	1020	235	0.40
	1.3	892	1055	241	0.41
	1.4	838	1085	248	0.43
	1.5	789	1117	255	0.44
	1.6	774	1163	227	0.46
	1.7	670	1183	247	0.46
T2	0.8	1500	923	290	0.49
	0.9	1467	958	300	0.51
	1	1413	992	309	0.52
	1.1	1362	1025	316	0.54
	1.2	1311	1057	324	0.56
	1.3	1260	1089	338	0.58
	1.4	1210	1117	346	0.59
	1.5	1162	1147	353	0.61
	1.6	1126	1181	351	0.63
	1.7	1058	1205	367	0.64
T3	0.8	-	-	-	-
	0.9	-	-	-	-
	1	1576	1012	357	0.61
	1.1	1527	1044	365	0.63
	1.2	1478	1076	373	0.64
	1.3	1429	1106	389	0.66
	1.4	1380	1134	398	0.68
	1.5	1333	1163	407	0.70
	1.6	1290	1192	414	0.71
	1.7	1234	1218	427	0.73
T4	0.8	1500	921	285	0.48
	0.9	1449	955	294	0.50
	1	1394	990	304	0.52
	1.1	1343	1022	311	0.53
	1.2	1291	1055	319	0.55
	1.3	1241	1087	332	0.57
	1.4	1190	1116	340	0.58
	1.5	1142	1146	348	0.60
	1.6	1107	1180	344	0.62
	1.7	1037	1204	360	0.63
T5	0.8	-	-	-	-
	0.9	-	-	-	-
	1	1500	1002	334	0.57
	1.1	1450	1034	341	0.59
	1.2	1399	1067	349	0.60
	1.3	1350	1098	364	0.62
	1.4	1300	1126	373	0.64
	1.5	1253	1156	381	0.65
	1.6	1213	1187	384	0.67
	1.7	1152	1212	398	0.69
	1.8	1095	1240	412	0.70

DSH0363W / DSH0364W / DSH0367W HORIZONTAL

TAP	STATIC	AIRFLOW (CFM)	RPM	WATTS	BHP
T1'	0.8	1414	909	262	0.44
	0.9	1357	944	270	0.46
	1	1300	979	279	0.47
	1.1	1247	1012	286	0.49
	1.2	1194	1045	293	0.51
	1.3	1143	1078	305	0.52
	1.4	1092	1107	313	0.54
	1.5	1044	1137	320	0.55
	1.6	1014	1174	310	0.57
	1.7	935	1197	327	0.58
T2'	0.8	-	-	-	-
	0.9	-	-	-	-
	1	1655	1022	383	0.65
	1.1	1607	1053	391	0.67
	1.2	1560	1085	400	0.69
	1.3	1511	1115	416	0.71
	1.4	1463	1142	426	0.73
	1.5	1417	1171	435	0.74
	1.6	1371	1199	446	0.76
	1.7	1320	1225	459	0.78
T3'	0.8	-	-	-	-
	0.9	-	-	-	-
	1				
	1.1				
	1.2				
	1.3	1673	1133	475	0.81
	1.4	1627	1160	486	0.83
	1.5	1582	1188	497	0.85
	1.6	1532	1213	513	0.87
	1.7	1489	1240	525	0.88
T4'	0.8	-	-	-	-
	0.9	-	-	-	-
	1	-	-	-	-
	1.1	-	-	-	-
	1.2	1500	1078	381	0.66
	1.3	1454	1109	397	0.68
	1.4	1405	1136	406	0.69
	1.5	1359	1166	415	0.71
	1.6	1315	1194	423	0.73
	1.7	1261	1220	437	0.74
T5'	0.8	-	-	-	-
	0.9	-	-	-	-
	1	-	-	-	-
	1.1	1641	1058	403	0.69
	1.2	1594	1089	412	0.71
	1.3	1546	1119	428	0.73
	1.4	1498	1146	438	0.75
	1.5	1452	1175	448	0.77
	1.6	1405	1201	460	0.78
	1.7	1357	1228	472	0.80
	1.8	1299	1256	485	0.82

* In DSH0363W / DSH0364W / DSH0367W, DSH0483W / DSH0484W / DSH0487W, AND DSH06083W / DSH0604W / DSH0607W DOWNSHOT & HORIZONTAL Tables, T1 values are for fan mode only

DSH0483W / DSH0484W / DSH0487W DOWNSHOT

TAP	STATIC	AIRFLOW (CFM)	RPM	WATTS	BHP
T1 *	0.8	1353	961	270	0.48
	0.9	1304	992	279	0.50
	1	1255	1023	287	0.51
	1.1	1202	1055	295	0.53
	1.2	1146	1087	303	0.54
	1.3	1099	1114	307	0.56
	1.4	1045	1139	317	0.57
	1.5	998	1164	323	0.58
	1.6	974	1182	315	0.59
	1.7	908	1217	334	0.61
T2	1.8	870	1238	335	0.62
	0.8	1804	1052	425	0.76
	0.9	1763	1079	436	0.78
	1	1722	1107	446	0.80
	1.1	1674	1133	459	0.82
	1.2	1632	1161	471	0.84
	1.3	1589	1189	478	0.86
	1.4	1541	1215	489	0.88
	1.5	1497	1241	498	0.89
	1.6	1447	1265	508	0.91
T3	1.7	1405	1287	516	0.93
	1.8	1364	1310	523	0.94
	0.8	1814	1054	430	0.77
	0.9	1773	1081	440	0.79
	1	1732	1109	451	0.81
	1.1	1685	1135	464	0.82
	1.2	1643	1163	476	0.85
	1.3	1600	1190	483	0.86
	1.4	1553	1216	494	0.88
	1.5	1508	1242	503	0.90
T4	1.6	1459	1267	513	0.92
	1.7	1417	1289	521	0.94
	1.8	1376	1312	528	0.95
	0.8	1775	1045	412	0.74
	0.9	1733	1073	423	0.76
	1	1691	1101	433	0.77
	1.1	1643	1127	446	0.79
	1.2	1600	1156	458	0.81
	1.3	1556	1183	465	0.83
	1.4	1508	1209	475	0.85
T5	1.5	1463	1235	484	0.87
	1.6	1414	1259	493	0.89
	1.7	1371	1282	501	0.90
	1.8	1329	1305	508	0.92
	0.8	1856	1064	449	0.80
	0.9	1815	1091	460	0.82
	1	1775	1117	471	0.84
	1.1	1730	1144	483	0.86
	1.2	1689	1171	496	0.88
	1.3	1646	1198	503	0.90
	1.4	1600	1224	514	0.92
	1.5	1556	1250	524	0.94
	1.6	1506	1274	535	0.96
	1.7	1466	1296	542	0.97
	1.8	1425	1319	550	0.99

DSH0483W / DSH0484W / DSH0487W DOWNSHOT

TAP	STATIC	AIRFLOW (CFM)	RPM	WATTS	BHP
T1'	0.8	1552	999	329	0.59
	0.9	1506	1028	339	0.60
	1	1460	1058	348	0.62
	1.1	1409	1087	359	0.64
	1.2	1359	1118	369	0.66
	1.3	1313	1145	374	0.67
	1.4	1260	1171	384	0.69
	1.5	1214	1197	391	0.70
	1.6	-	-	-	-
	1.7	-	-	-	-
T2'	1.8	-	-	-	-
	0.8	1998	1101	525	0.93
	0.9	1960	1125	536	0.95
	1	1922	1150	548	0.97
	1.1	1883	1175	561	0.99
	1.2	1846	1200	574	1.02
	1.3	1807	1226	582	1.04
	1.4	1766	1251	594	1.06
	1.5	1725	1276	606	1.08
	1.6	1679	1301	618	1.10
T3'	1.7	1641	1322	626	1.12
	1.8	1601	1346	637	1.14
	0.8	1877	1069	459	0.82
	0.9	1837	1096	470	0.84
	1	1797	1122	481	0.86
	1.1	1752	1148	494	0.88
	1.2	1712	1175	506	0.90
	1.3	1670	1202	514	0.92
	1.4	1624	1228	525	0.94
	1.5	1581	1254	535	0.96
T4'	1.6	1531	1278	546	0.98
	1.7	1491	1300	554	0.99
	1.8	1450	1323	562	1.01
	0.8	1935	1084	489	0.87
	0.9	1896	1109	500	0.89
	1	1857	1135	511	0.91
	1.1	1814	1160	524	0.93
	1.2	1775	1187	537	0.95
	1.3	1735	1213	545	0.97
	1.4	1691	1239	556	0.99
T5'	1.5	1649	1264	567	1.01
	1.6	1600	1289	579	1.03
	1.7	1561	1310	586	1.05
	1.8	1521	1334	596	1.07
	0.8	1997	1101	525	0.93
	0.9	1959	1125	536	0.95
	1	1922	1150	547	0.97
	1.1	1882	1174	560	0.99
	1.2	1845	1200	573	1.01
	1.3	1806	1226	581	1.04
	1.4	1765	1251	594	1.06
	1.5	1724	1276	606	1.08
	1.6	1678	1300	617	1.10
	1.7	1640	1322	626	1.12
	1.8	1600	1346	636	1.14

* In DSH0363W / DSH0364W / DSH0367W, DSH0483W / DSH0484W / DSH0487W, AND DSH06083W / DSH0604W / DSH0607W DOWNSHOT & HORIZONTAL Tables, T1 values are for fan mode only

DSH0483W / DSH0484W / DSH0487W HORIZONTAL

TAP	STATIC	AIRFLOW (CFM)	RPM	WATTS	BHP
T1 *	0.8	1438	926	257	0.46
	0.9	1384	962	266	0.48
	1	1332	999	275	0.50
	1.1	1282	1034	283	0.52
	1.2	1223	1069	292	0.53
	1.3	1170	1101	303	0.55
	1.4	1123	1130	311	0.56
	1.5	1067	1157	317	0.58
	1.6	1021	1181	322	0.59
	1.7	973	1201	329	0.60
T2	1.8	943	1222	332	0.61
	0.8	1903	1001	405	0.72
	0.9	1863	1030	415	0.74
	1	1819	1057	424	0.76
	1.1	1774	1086	436	0.78
	1.2	1726	1117	449	0.81
	1.3	1677	1148	462	0.83
	1.4	1627	1178	472	0.85
	1.5	1572	1211	483	0.87
	1.6	1528	1240	490	0.89
T3	1.7	1485	1271	502	0.92
	1.8	1431	1295	515	0.93
	0.8	1913	1003	409	0.73
	0.9	1874	1032	420	0.75
	1	1830	1058	428	0.77
	1.1	1785	1087	440	0.79
	1.2	1737	1118	453	0.81
	1.3	1689	1149	466	0.83
	1.4	1639	1179	477	0.86
	1.5	1585	1212	488	0.88
T4	1.6	1540	1241	495	0.90
	1.7	1498	1272	507	0.92
	1.8	1443	1297	520	0.94
	0.8	1872	995	393	0.70
	0.9	1832	1024	403	0.72
	1	1787	1052	412	0.74
	1.1	1741	1082	424	0.76
	1.2	1692	1114	436	0.78
	1.3	1643	1145	449	0.81
	1.4	1592	1175	460	0.83
T5	1.5	1537	1208	470	0.85
	1.6	1491	1237	477	0.87
	1.7	1450	1266	488	0.89
	1.8	1395	1289	501	0.91
	0.8	1957	1012	428	0.76
	0.9	1917	1040	438	0.78
	1	1876	1065	446	0.80
	1.1	1832	1093	459	0.82
	1.2	1785	1124	472	0.84
	1.3	1738	1154	485	0.87
	1.4	1689	1183	496	0.89
	1.5	1636	1216	507	0.91
	1.6	1592	1246	515	0.94
	1.7	1549	1278	527	0.96
	1.8	1494	1304	541	0.98

DSH0483W / DSH0484W / DSH0487W HORIZONTAL

TAP	STATIC	AIRFLOW (CFM)	RPM	WATTS	BHP
T1'	0.8	1642	955	313	0.56
	0.9	1595	989	324	0.58
	1	1546	1022	332	0.60
	1.1	1496	1056	343	0.62
	1.2	1441	1090	353	0.64
	1.3	1390	1123	364	0.66
	1.4	1339	1153	374	0.68
	1.5	1281	1183	383	0.70
	1.6	1234	1209	388	0.71
	1.7	1200	1232	397	0.72
T2'	1.8	-	-	-	-
	0.8	-	-	-	-
	0.9	-	-	-	-
	1	-	-	-	-
	1.1	1994	1120	531	0.95
	1.2	1953	1147	545	0.97
	1.3	1909	1174	561	0.99
	1.4	1867	1201	569	1.02
	1.5	1821	1233	582	1.04
	1.6	1784	1262	591	1.07
T3'	1.7	1734	1295	607	1.10
	1.8	1682	1326	621	1.12
	0.8	1979	1017	438	0.78
	0.9	1940	1044	447	0.80
	1	1899	1069	456	0.82
	1.1	1856	1097	468	0.84
	1.2	1810	1127	482	0.86
	1.3	1763	1156	496	0.88
	1.4	1715	1185	506	0.91
	1.5	1662	1219	517	0.93
T4'	1.6	1620	1249	525	0.95
	1.7	1575	1281	538	0.98
	1.8	1520	1308	552	1.00
	0.8	-	-	-	-
	0.9	2000	1057	475	0.85
	1	1962	1080	484	0.87
	1.1	1921	1107	497	0.89
	1.2	1878	1136	510	0.91
	1.3	1832	1164	525	0.93
	1.4	1786	1192	534	0.96
T5'	1.5	1736	1225	547	0.98
	1.6	1696	1255	555	1.01
	1.7	1650	1288	569	1.03
	1.8	1595	1318	583	1.06
	0.8	-	-	-	-
	0.9	-	-	-	-
	1	-	-	-	-
	1.1	1993	1120	530	0.95
	1.2	1952	1147	544	0.97
	1.3	1909	1174	560	0.99
	1.4	1866	1201	568	1.02
	1.5	1820	1233	582	1.04
	1.6	1783	1262	591	1.07
	1.7	1733	1295	607	1.10
	1.8	1681	1326	621	1.12

* In DSH0363W / DSH0364W / DSH0367W, DSH0483W / DSH0484W / DSH0487W, AND DSH06083W / DSH0604W / DSH0607W DOWNSHOT & HORIZONTAL Tables, T1 values are for fan mode only

DSH06083W / DSH0604W / DSH0607W DOWNSHOT

TAP	STATIC	AIRFLOW (CFM)	RPM	WATTS	BHP
T1 *	0.8	1584	1020	358	0.58
	0.9	1540	1053	366	0.60
	1	1496	1085	375	0.61
	1.1	1455	1112	383	0.63
	1.2	1415	1140	391	0.65
	1.3	1374	1170	402	0.66
	1.4	1338	1198	421	0.68
	1.5	1302	1221	428	0.69
	1.6	1255	1243	443	0.70
	1.7	1231	1268	452	0.72
T2	1.8	1212	1288	460	0.73
	0.8	2038	1121	556	0.92
	0.9	2000	1151	565	0.95
	1	1961	1180	573	0.97
	1.1	1924	1207	585	0.99
	1.2	1887	1233	596	1.01
	1.3	1850	1260	611	1.04
	1.4	1814	1284	623	1.06
	1.5	1777	1309	636	1.08
	1.6	1743	1334	656	1.10
T3	1.7	1703	1354	665	1.11
	1.8	1659	1374	675	1.13
	0.8	2086	1134	583	0.97
	0.9	2049	1163	592	0.99
	1	2011	1191	601	1.02
	1.1	1974	1218	613	1.04
	1.2	1936	1244	624	1.06
	1.3	1900	1270	640	1.08
	1.4	1863	1294	652	1.10
	1.5	1827	1319	665	1.13
T4	1.6	1794	1344	685	1.15
	1.7	1751	1365	693	1.16
	1.8	1704	1385	704	1.18
	0.8	2148	1150	620	1.03
	0.9	2111	1178	630	1.05
	1	2074	1206	639	1.08
	1.1	2037	1232	651	1.10
	1.2	2000	1258	663	1.13
	1.3	1963	1284	679	1.15
	1.4	1926	1307	690	1.17
T5	1.5	1889	1332	704	1.19
	1.6	1858	1357	723	1.21
	1.7	1812	1378	732	1.23
	1.8	1761	1398	743	1.25
	0.8	2220	1170	667	1.11
	0.9	2184	1197	677	1.13
	1	2148	1224	687	1.16
	1.1	2111	1249	700	1.18
	1.2	2075	1275	712	1.21
	1.3	2037	1300	729	1.23
	1.4	2000	1323	739	1.25
	1.5	1963	1348	754	1.28
	1.6	1934	1373	771	1.30
	1.7	1883	1394	781	1.32
	1.8	1829	1415	793	1.34

DSH06083W / DSH0604W / DSH0607W DOWNSHOT

TAP	STATIC	AIRFLOW (CFM)	RPM	WATTS	BHP
T1'	0.8	1730	1050	411	0.67
	0.9	1687	1082	419	0.69
	1	1645	1113	428	0.71
	1.1	1605	1141	437	0.73
	1.2	1566	1168	446	0.75
	1.3	1529	1197	459	0.77
	1.4	1500	1224	475	0.78
	1.5	-	-	-	-
	1.6	-	-	-	-
	1.7	-	-	-	-
T2'	1.8	-	-	-	-
	0.8	2259	1181	694	1.15
	0.9	2224	1207	705	1.18
	1	2188	1233	715	1.20
	1.1	2152	1259	728	1.23
	1.2	2116	1284	741	1.25
	1.3	2077	1309	757	1.28
	1.4	2040	1331	767	1.30
	1.5	2003	1356	782	1.32
	1.6	1974	1381	799	1.35
T3'	1.7	1921	1403	809	1.37
	1.8	1867	1424	821	1.39
	0.8	2136	1147	613	1.02
	0.9	2099	1175	622	1.04
	1	2062	1203	632	1.07
	1.1	2025	1229	644	1.09
	1.2	1988	1256	656	1.11
	1.3	1951	1281	672	1.14
	1.4	1914	1305	683	1.16
	1.5	1877	1330	697	1.18
T4'	1.6	1846	1355	716	1.20
	1.7	1801	1375	725	1.22
	1.8	1750	1396	735	1.24
	0.8	2284	1188	712	1.18
	0.9	2249	1214	723	1.21
	1	2214	1240	733	1.23
	1.1	2178	1265	746	1.26
	1.2	2142	1290	760	1.28
	1.3	2103	1314	776	1.31
	1.4	2066	1337	786	1.33
T5'	1.5	2028	1362	801	1.35
	1.6	2000	1387	817	1.38
	1.7	1946	1409	828	1.40
	1.8	1892	1430	840	1.42
	0.8	2390	1219	794	1.31
	0.9	2357	1243	806	1.34
	1	2323	1267	817	1.36
	1.1	2287	1291	831	1.39
	1.2	2252	1315	845	1.42
	1.3	2211	1339	862	1.44
	1.4	2173	1360	871	1.46
	1.5	2135	1385	887	1.49
	1.6	2107	1410	899	1.52
	1.7	2049	1433	912	1.54
	1.8	2000	1456	925	1.57

* In DSH0363W / DSH0364W / DSH0367W, DSH0483W / DSH0484W / DSH0487W, AND DSH06083W / DSH0604W / DSH0607W DOWNSHOT & HORIZONTAL Tables, T1 values are for fan mode only

DSH0603W / DSH0604W / DSH0607W HORIZONTAL

TAP	STATIC	AIRFLOW (CFM)	RPM	WATTS	BHP
T1 *	0.8	1674	978	350	0.55
	0.9	1630	1011	363	0.57
	1	1587	1043	373	0.59
	1.1	1535	1074	384	0.61
	1.2	1499	1105	395	0.63
	1.3	1458	1134	407	0.64
	1.4	1447	1172	435	0.66
	1.5	1408	1198	454	0.68
	1.6	1370	1221	459	0.69
	1.7	1331	1247	465	0.71
T2	1.8	1293	1271	474	0.72
	0.8	2150	1065	532	0.88
	0.9	2115	1093	548	0.90
	1	2080	1121	562	0.92
	1.1	2043	1149	573	0.94
	1.2	2003	1176	586	0.97
	1.3	1967	1203	602	0.99
	1.4	1904	1227	610	1.01
	1.5	1861	1255	620	1.03
	1.6	1822	1281	635	1.05
T3	1.7	1782	1305	646	1.07
	1.8	1742	1331	660	1.09
	0.8	2200	1076	556	0.92
	0.9	2165	1103	572	0.94
	1	2131	1130	587	0.96
	1.1	2097	1158	598	0.99
	1.2	2055	1184	611	1.01
	1.3	2020	1211	627	1.03
	1.4	1957	1234	634	1.05
	1.5	1915	1262	645	1.08
T4	1.6	1875	1288	660	1.10
	1.7	1836	1312	672	1.12
	1.8	1797	1338	685	1.14
	0.8	2262	1090	589	0.98
	0.9	2229	1116	605	1.00
	1	2195	1143	620	1.02
	1.1	2165	1169	631	1.05
	1.2	2121	1195	644	1.07
	1.3	2087	1221	660	1.09
	1.4	2026	1243	667	1.11
T5	1.5	1984	1271	679	1.14
	1.6	1945	1297	695	1.16
	1.7	1907	1320	706	1.18
	1.8	1868	1347	720	1.21
	0.8	2335	1107	631	1.05
	0.9	2303	1132	647	1.07
	1	2270	1157	663	1.10
	1.1	2244	1183	673	1.12
	1.2	2199	1207	686	1.14
	1.3	2165	1233	702	1.17
	1.4	2109	1255	709	1.19
	1.5	2068	1282	722	1.21
	1.6	2030	1307	739	1.24
	1.7	1993	1331	751	1.26
	1.8	1955	1357	764	1.28

DSH0603W / DSH0604W / DSH0607W HORIZONTAL

TAP	STATIC	AIRFLOW (CFM)	RPM	WATTS	BHP
T1'	0.8	1829	1004	401	0.64
	0.9	1788	1036	415	0.66
	1	1747	1066	427	0.68
	1.1	1698	1097	438	0.70
	1.2	1662	1127	450	0.72
	1.3	1623	1156	463	0.74
	1.4	1585	1188	483	0.76
	1.5	1544	1215	497	0.78
	1.6	1504	1240	505	0.79
	1.7	-	-	-	-
T2'	1.8	-	-	-	-
	0.8	2375	1116	655	1.09
	0.9	2343	1141	671	1.11
	1	2311	1166	687	1.14
	1.1	2288	1190	698	1.16
	1.2	2241	1214	711	1.18
	1.3	2208	1240	727	1.21
	1.4	2154	1261	734	1.23
	1.5	2114	1288	748	1.26
	1.6	2077	1313	766	1.28
T3'	1.7	2041	1337	777	1.30
	1.8	2003	1363	790	1.33
	0.8	2250	1087	583	0.96
	0.9	2217	1114	599	0.99
	1	2183	1140	614	1.01
	1.1	2152	1167	625	1.03
	1.2	2109	1193	638	1.06
	1.3	2074	1219	654	1.08
	1.4	2013	1241	661	1.10
	1.5	1971	1269	672	1.13
T4'	1.6	1932	1295	688	1.15
	1.7	1894	1319	700	1.17
	1.8	1854	1345	713	1.19
	0.8	2400	1123	671	1.12
	0.9	2368	1147	687	1.14
	1	2336	1171	704	1.16
	1.1	2315	1195	714	1.19
	1.2	2268	1219	727	1.21
	1.3	2234	1244	743	1.24
	1.4	2183	1265	750	1.26
T5'	1.5	2144	1292	765	1.28
	1.6	2107	1317	783	1.31
	1.7	2071	1340	794	1.33
	1.8	2034	1366	807	1.36
	0.8	2500	1150	745	1.24
	0.9	2476	1172	761	1.26
	1	2445	1195	778	1.29
	1.1	2430	1217	788	1.31
	1.2	2380	1239	801	1.33
	1.3	2348	1263	817	1.36
	1.4	2309	1285	826	1.38
	1.5	2271	1310	843	1.41
	1.6	2237	1334	862	1.44
	1.7	2203	1357	874	1.46
	1.8	2167	1382	885	1.49

* In DSH0363W / DSH0364W / DSH0367W, DSH0483W / DSH0484W / DSH0487W, AND DSH06083W / DSH0604W / DSH0607W DOWNSHOT & HORIZONTAL Tables, T1 values are for fan mode only

DSH0723W / DSH0724W / DSH0727W DOWNSHOT

TAP	STATIC	AIRFLOW (CFM)	RPM	WATTS	BHP
T1 **	0.6	1920	1045	450	0.85
	0.8	1845	1097	472	0.89
	0.9	1800	1126	485	0.91
	1	1762	1151	492	0.93
	1.1	1729	1177	510	0.96
	1.2	1690	1202	518	0.98
	1.3	1650	1227	527	1.00
	1.4	1612	1251	538	1.02
	1.5	1574	1274	549	1.03
	1.6	1543	1297	560	1.05
	1.8	-	-	-	-
T2 **	0.6	1840	1024	413	0.78
	0.8	1760	1076	433	0.82
	0.9	1715	1105	445	0.84
	1	1675	1131	451	0.86
	1.1	1641	1158	470	0.88
	1.2	1600	1184	478	0.90
	1.3	1558	1209	486	0.92
	1.4	1519	1233	497	0.94
	1.5	1479	1257	507	0.96
	1.6	1446	1280	518	0.98
	1.8	-	-	-	-
T3	0.6	2590	1242	895	1.60
	0.8	2527	1282	919	1.66
	0.9	2491	1304	935	1.68
	1	2462	1323	946	1.71
	1.1	2434	1341	963	1.73
	1.2	2403	1362	974	1.76
	1.3	2371	1383	985	1.79
	1.4	2339	1405	999	1.81
	1.5	2306	1426	1013	1.84
	1.6	2248	1445	1024	1.87
	1.8	-	-	-	-
T4	0.6	2402	1182	740	1.36
	0.8	2338	1228	764	1.40
	0.9	2298	1252	779	1.43
	1	2267	1272	790	1.45
	1.1	2240	1293	807	1.48
	1.2	2207	1315	817	1.50
	1.3	2175	1337	827	1.53
	1.4	2143	1359	841	1.55
	1.5	2111	1380	855	1.58
	1.6	2070	1401	866	1.60
	1.8	-	-	-	-
T5	0.6	2654	1280	950	1.70
	0.8	2588	1300	977	1.75
	0.9	2554	1321	992	1.77
	1	2524	1339	1004	1.80
	1.1	2496	1357	1020	1.82
	1.2	2464	1378	1032	1.85
	1.3	2433	1398	1043	1.88
	1.4	2400	1420	1057	1.91
	1.5	2367	1442	1070	1.94
	1.6	2300	1461	1082	1.96
	1.8	-	-	-	-

DSH0723W / DSH0724W / DSH0727W DOWNSHOT

TAP	STATIC	AIRFLOW (CFM)	RPM	WATTS	BHP
T1 **	0.6	2013	1074	495	0.95
	0.8	1940	1121	518	0.98
	0.9	1895	1149	532	1.00
	1	1859	1173	539	1.02
	1.1	1828	1199	558	1.04
	1.2	1790	1223	567	1.06
	1.3	1752	1247	575	1.09
	1.4	1716	1270	587	1.11
	1.5	1679	1293	599	1.13
	1.6	1650	1316	610	1.15
	1.8	-	-	-	-
T2 **	0.6	1950	1050	458	0.85
	0.8	1858	1100	478	0.90
	0.9	1813	1129	491	0.93
	1	1775	1154	498	0.95
	1.1	1743	1180	516	0.97
	1.2	1703	1205	525	0.99
	1.3	1664	1230	533	1.01
	1.4	1626	1253	544	1.03
	1.5	1589	1276	556	1.05
	1.6	1558	1300	566	1.07
	1.8	-	-	-	-
T3'	0.6	2740	1290	1040	1.84
	0.8	2675	1328	1067	1.89
	0.9	2643	1346	1081	1.91
	1	2614	1364	1094	1.94
	1.1	2585	1381	1109	1.96
	1.2	2552	1401	1122	1.99
	1.3	2520	1421	1134	2.02
	1.4	2487	1443	1147	2.05
	1.5	2453	1465	1160	2.08
	1.6	2371	1483	1171	2.11
	1.8	-	-	-	-
T4'	0.6	2515	1215	823	1.49
	0.8	2447	1259	850	1.54
	0.9	2409	1282	865	1.57
	1	2379	1301	876	1.60
	1.1	2352	1320	893	1.62
	1.2	2320	1342	904	1.65
	1.3	2289	1363	915	1.67
	1.4	2256	1385	928	1.70
	1.5	2224	1406	942	1.72
	1.6	2175	1426	954	1.75
	1.8	-	-	-	-
T5'	0.6	2780	1300	1083	1.89
	0.8	2713	1340	1109	1.95
	0.9	2682	1357	1123	1.98
	1	2654	1375	1137	2.01
	1.1	2623	1391	1151	2.03
	1.2	2591	1411	1164	2.06
	1.3	2558	1431	1177	2.09
	1.4	2524	1453	1190	2.12
	1.5	2489	1476	1203	2.15
	1.6	2400	1493	1214	2.18
	1.8	-	-	-	-

** In DSH0723W / DSH0724W / DSH0727W DOWNSHOT & HORIZONTAL Tables, T1, T1', T2, and T2' values are for part load only

DSH0723W / DSH0724W / DSH0727W HORIZONTAL

TAP	STATIC	AIRFLOW (CFM)	RPM	WATTS	BHP
T1 **	0.6	1880	955	417	0.80
	0.8	1967	1018	440	0.85
	0.9	1929	1043	450	0.87
	1	1886	1072	462	0.89
	1.1	1843	1100	474	0.92
	1.2	1798	1134	492	0.95
	1.3	1754	1168	510	0.95
	1.4	1707	1200	521	0.97
	1.5	1661	1232	532	1.00
	1.6	1614	1260	536	1.02
	1.8	-	-	-	-
T2 **	0.6	1970	938	380	0.72
	0.8	1879	999	404	0.76
	0.9	1838	1027	415	0.78
	1	1792	1057	427	0.80
	1.1	1746	1087	439	0.83
	1.2	1701	1121	457	0.85
	1.3	1656	1156	477	0.88
	1.4	1607	1188	487	0.90
	1.5	1557	1221	498	0.93
	1.6	1511	1249	495	0.95
	1.8	-	-	-	-
T3	0.6	2714	1168	840	1.50
	0.8	2658	1202	863	1.55
	0.9	2638	1215	870	1.57
	1	2614	1231	879	1.59
	1.1	2590	1247	888	1.61
	1.2	2557	1264	901	1.63
	1.3	2524	1280	912	1.65
	1.4	2494	1300	926	1.68
	1.5	2464	1319	940	1.70
	1.6	2426	1344	964	1.74
	1.8	-	-	-	-
T4	0.6	2536	1102	690	1.27
	0.8	2470	1145	716	1.31
	0.9	2446	1161	723	1.33
	1	2418	1180	733	1.35
	1.1	2390	1200	744	1.37
	1.2	2352	1222	758	1.40
	1.3	2314	1244	770	1.42
	1.4	2280	1267	784	1.45
	1.5	2247	1291	797	1.47
	1.6	2205	1318	822	1.51
	1.8	-	-	-	-
T5	0.6	2663	1190	896	1.60
	0.8	2718	1222	918	1.64
	0.9	2699	1233	925	1.66
	1	2675	1248	933	1.68
	1.1	2652	1264	942	1.70
	1.2	2621	1279	953	1.72
	1.3	2591	1293	964	1.74
	1.4	2561	1312	979	1.76
	1.5	2532	1330	993	1.79
	1.6	2496	1354	1015	1.82
	1.8	-	-	-	-

DSH0723W / DSH0724W / DSH0727W HORIZONTAL

TAP	STATIC	AIRFLOW (CFM)	RPM	WATTS	BHP
T1 **	0.6	1982	980	460	0.85
	0.8	2064	1039	484	0.90
	0.9	2030	1063	493	0.93
	1	1990	1090	505	0.95
	1.1	1950	1116	517	0.97
	1.2	1906	1149	534	1.00
	1.3	1862	1181	551	1.03
	1.4	1819	1212	562	1.06
	1.5	1775	1243	574	1.08
	1.6	1729	1272	583	1.11
	1.8	-	-	-	-
T2 **	0.6	1895	960	422	0.80
	0.8	1980	1021	446	0.84
	0.9	1943	1046	456	0.86
	1	1900	1074	468	0.88
	1.1	1858	1102	480	0.90
	1.2	1813	1136	497	0.93
	1.3	1768	1170	516	0.96
	1.4	1722	1201	527	0.99
	1.5	1676	1233	538	1.01
	1.6	1630	1262	542	1.03
	1.8	-	-	-	-
T3'	0.6	2854	1220	980	1.73
	0.8	2802	1250	1003	1.78
	0.9	2784	1260	1011	1.79
	1	2762	1274	1018	1.81
	1.1	2739	1288	1026	1.83
	1.2	2712	1301	1037	1.85
	1.3	2685	1315	1047	1.87
	1.4	2657	1332	1062	1.89
	1.5	2628	1349	1076	1.92
	1.6	2596	1371	1094	1.95
	1.8	-	-	-	-
T4'	0.6	2518	1138	771	1.40
	0.8	2579	1177	797	1.44
	0.9	2557	1191	804	1.46
	1	2532	1209	814	1.48
	1.1	2506	1227	823	1.50
	1.2	2471	1245	836	1.53
	1.3	2436	1264	848	1.55
	1.4	2404	1285	862	1.58
	1.5	2373	1306	876	1.60
	1.6	2333	1332	901	1.63
	1.8	-	-	-	-
T5'	0.6	2889	1232	1022	1.80
	0.8	2839	1262	1044	1.84
	0.9	2821	1272	1052	1.86
	1	2799	1285	1059	1.87
	1.1	2776	1298	1066	1.89
	1.2	2751	1312	1076	1.91
	1.3	2726	1325	1087	1.93
	1.4	2698	1342	1101	1.96
	1.5	2670	1358	1116	1.98
	1.6	2639	1379	1131	2.01
	1.8	-	-	-	-

** In DSH0723W / DSH0724W / DSH0727W DOWNSHOT & HORIZONTAL Tables, T1, T1', T2, and T2' values are for part load only

3-5 TONS		
DOWNFLOW ECONOMIZER PRESSURE DROP		
Cabinet	CFM	SP in.wg.
3 Ton	900	.03"
	1200	.05"
	1500	.08"
4 Ton	1200	.06"
	1600	.10"
	2000	.14"
5 Ton	1500	.08"
	2000	.14"
	2500	.22"
6 Ton	1800	.13"
	2400	.22"
	3000	.33"

3-5 TONS		
HORIZONTAL ECONOMIZER PRESSURE DROP		
Cabinet	CFM	SP in.wg.
3 Ton	900	.06"
	1200	.11"
	1500	.16"
4 Ton	1200	.11"
	1600	.19"
	2000	.29"
5 Ton	1500	.18"
	2000	.30"
	2500	.45"
6 Ton	1800	.24"
	2400	.41"
	3000	.61"

CONCENTRIC DIFFUSER 24 X 48 WITH 16" DIA COLLAR PRESSURE DROP		
Cabinet	CFM	DIFFUSER DP
3-6 Ton	1000	0.18
	1200	0.25
	1400	0.33
	1600	0.42
	1800	0.53
	2000	0.64

CONCENTRIC DIFFUSER 24 X 48 WITH 18" DIA COLLAR PRESSURE DROP		
Cabinet	CFM	DIFFUSER DP
3-6 Ton	1000	0.14
	1200	0.20
	1400	0.26
	1600	0.33
	1800	0.41
	2000	0.50
	2400	0.68

INDOOR COIL PRESSURE DROP		
CABINET	CFM	DP (IN W.C)
3 Ton	1170	0.06
4 Ton	1600	0.13
5 Ton	1840	0.16
6 Ton	2370	0.16

Heating Data

DSH036*D

100 % Capacity

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBh	43.43	40.68	37.97	35.31	33.60	32.35	29.17	26.22	23.80	22.02	20.70	20.00	19.09	16.83	14.56	12.29	10.03
T/R	31.70	29.98	28.26	26.53	25.50	24.56	22.14	19.90	18.06	16.71	15.71	15.18	14.49	12.77	11.05	9.33	7.61
KW	2.91	2.86	2.81	2.76	2.74	2.72	2.67	2.62	2.57	2.52	2.47	2.44	2.42	2.37	2.33	2.28	2.23
AMPS	10.9	10.6	10.4	10.2	10.1	10.0	9.8	9.6	9.4	9.2	8.9	8.8	8.7	8.5	8.3	8.1	7.9
COP	4.37	4.16	3.96	3.74	3.60	3.49	3.21	2.93	2.71	2.56	2.46	2.40	2.31	2.08	1.84	1.58	1.32
Hi PR	377	365	353	340	333	328	316	304	291	279	267	259	254	242	230	218	205
LO PR	139	131	122	113	108	105	96	87	79	70	61	56	53	44	35	27	18

DSH048*D

100 % Capacity

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBh	58.66	54.83	51.07	47.37	45.00	43.24	38.78	34.68	31.33	28.84	26.99	26.00	24.73	21.57	18.40	15.23	12.07
T/R	33.05	31.20	29.34	27.49	26.37	25.34	22.73	20.32	18.36	16.90	15.82	15.24	14.49	12.64	10.78	8.93	7.07
KW	3.96	3.88	3.79	3.71	3.66	3.63	3.55	3.47	3.39	3.31	3.22	3.18	3.14	3.06	2.98	2.90	2.82
AMPS	14.2	13.8	13.5	13.1	12.9	12.8	12.4	12.1	11.7	11.4	11.0	10.8	10.7	10.3	10.0	9.6	9.2
COP	4.34	4.15	3.95	3.74	3.60	3.49	3.20	2.93	2.71	2.56	2.45	2.40	2.31	2.06	1.81	1.54	1.26
Hi PR	381	368	356	343	336	331	319	306	294	282	269	262	257	244	232	220	207
LO PR	137	128	120	111	106	103	94	86	77	69	60	55	52	43	35	26	18

DSH060*D

100 % Capacity

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBh	69.68	65.58	61.54	57.57	55.00	53.13	48.57	44.16	40.54	37.91	36.02	35.00	33.67	30.33	27.00	23.67	20.33
T/R	33.18	31.53	29.88	28.23	27.23	26.35	24.05	21.87	20.07	18.77	17.83	17.33	16.67	15.02	13.37	11.72	10.07
KW	4.60	4.57	4.53	4.50	4.48	4.46	4.43	4.40	4.36	4.33	4.29	4.27	4.26	4.23	4.19	4.16	4.12
AMPS	16.3	16.2	16.0	15.9	15.8	15.7	15.6	15.4	15.3	15.1	15.0	14.9	14.8	14.7	14.5	14.4	14.2
COP	4.44	4.21	3.98	3.75	3.60	3.49	3.21	2.94	2.72	2.57	2.46	2.40	2.32	2.10	1.89	1.67	1.44
Hi PR	374	362	349	337	330	325	313	301	289	277	264	257	252	240	228	216	204
LO PR	137	128	120	111	106	103	94	86	77	69	60	55	52	43	35	26	18

DSH072*D

100 % Capacity

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBh	87.78	81.95	76.23	70.60	67.00	64.30	57.48	51.24	46.14	42.35	39.52	38.00	36.07	31.23	26.40	21.57	16.73
T/R	32.84	30.96	29.08	27.20	26.07	25.01	22.36	19.93	17.95	16.48	15.37	14.78	14.03	12.15	10.27	8.39	6.51
KW	6.27	6.13	6.00	5.86	5.78	5.72	5.58	5.45	5.31	5.17	5.03	4.95	4.89	4.76	4.62	4.48	4.34
AMPS	23.5	22.9	22.3	21.7	21.3	21.1	20.5	19.9	19.3	18.7	18.1	17.7	17.5	16.9	16.3	15.7	15.1
COP	4.10	3.92	3.73	3.53	3.40	3.29	3.02	2.76	2.55	2.40	2.30	2.25	2.16	1.92	1.67	1.41	1.13
Hi PR	362	351	339	327	320	315	303	292	280	268	256	249	245	233	221	209	197
LO PR	135	127	118	110	105	102	93	85	76	68	60	54	51	43	34	26	17

DSH072*D

70 % Capacity

	OUTDOOR AMBIENT TEMPERATURE																
	65	60	55	50	47	45	40	35	30	25	20	17	15	10	5	0	-5
MBh	64.20	59.81	55.85	51.25	48.33	46.02	40.32	-	-	-	-	-	-	-	-	-	-
T/R	34.81	32.58	30.36	28.14	26.80	25.51	22.36	-	-	-	-	-	-	-	-	-	-
KW	3.82	3.69	3.55	3.42	3.34	3.28	3.15	-	-	-	-	-	-	-	-	-	-
AMPS	14.0	13.4	12.8	12.2	11.9	11.6	11.0	-	-	-	-	-	-	-	-	-	-
COP	4.92	4.75	4.61	4.40	4.25	4.11	3.75	-	-	-	-	-	-	-	-	-	-
Hi PR	351	340	328	317	310	306	294	-	-	-	-	-	-	-	-	-	-
LO PR	133	125	116	108	103	100	92	-	-	-	-	-	-	-	-	-	-

Calculations are based on nominal CFM and 70 °F indoor dry bulb.

Amps = Outdoor unit amps (comp.+fan)

Note: Shaded area is AHRI Rating Conditions at 47°F outdoor ambient temperature

kW = Total system power

Model Number	Electrical Rating	Compressor			Outdoor Fan Motor			Indoor Fan Motor			Optional Electric Heat			Optional Powered Convenience Outlet	Optional Power Exhaust	Power Supply	
		QTY	RLA	LRA	QTY	HP	FLA	QTY	HP	FLA	PART #	KW*	FLA	FLA	FLA	MCA	MOP
DSH0361D	208/230/1/60	1	16.4	88.0	1	0.17	0.95	1	0.75	5.7	-	-	-	-	-	27.2/27.2	40/40
											-	-	-	9.6/8.7	-	36.8/35.9	50/50
											-	-	-	-	2.2/1.9 (1.7/1.5)	29.4/29.1	45/45
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	39.0/37.8	50/50
											EH*D-1S05A	3.8/5.0	18.1/20.8	-	-	49.8/53.3	60/60
											-	-	-	9.6/8.7	-	59.4/62.0	70/70
											-	-	-	-	2.2/1.9 (1.7/1.5)	52.0/55.2	60/60
											EH*D-1S10A	7.5/10.0	36.1/41.7	9.6/8.7	2.2/1.9 (1.7/1.5)	61.6/63.9	70/70
											-	-	-	-	-	72.3/79.3	80/80
											EH*D-1S15A	11.3/15.0	54.2/62.5	9.6/8.7	2.2/1.9 (1.7/1.5)	81.9/88.0	90/90
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	74.5/81.2	80/90
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	84.1/89.9	90/90
DSH0363D	208/230/3/60	1	10.6	97.5	1	0.17	0.95	1	0.75	5.7	-	-	-	-	-	94.9/105	100/110
											-	-	-	9.6/8.7	-	105/114	110/125
											-	-	-	-	2.2/1.9 (1.7/1.5)	97.1/107	100/110
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	107/116	110/125
											EH*D-3S05A	3.8/5.0	10.4/12.0	-	-	32.9/34.9	40/40
											-	-	-	9.6/8.7	-	42.5/43.6	50/50
											EH*D-3S10A	7.5/10.0	20.8/24.0	-	2.2/1.9 (1.7/1.5)	35.1/36.8	40/40
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	44.7/45.5	50/50
											EH*D-3S15A	11.3/15.0	31.3/36.1	-	-	45.8/49.8	50/50
											-	-	-	9.6/8.7	-	55.4/58.5	60/60
											-	-	-	-	2.2/1.9 (1.7/1.5)	48.0/51.7	50/60
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	57.6/60.4	60/70
DSH0363W	208/230/3/60	1	10.6	97.5	1	0.17	0.95	1	1.2	5.0	-	-	-	-	-	58.9/65.0	60/70
											-	-	-	9.6/8.7	-	68.5/73.7	70/80
											-	-	-	-	2.2/1.9 (1.7/1.5)	61.1/66.9	70/70
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	70.7/75.6	80/80
											EH*D-3S05A	3.8/5.0	10.4/12.0	-	-	32.2/34.2	40/40
											-	-	-	9.6/8.7	-	41.8/42.9	45/50
											EH*D-3S10A	7.5/10.0	20.8/24.0	-	2.2/1.9 (1.7/1.5)	34.4/36.1	40/40
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	44.0/44.8	50/50
											EH*D-3S15A	11.3/15.0	31.3/36.1	-	-	45.1/49.1	50/50
											-	-	-	9.6/8.7	-	54.7/57.8	60/60
											-	-	-	-	2.2/1.9 (1.7/1.5)	47.3/51.0	50/60
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	56.9/59.7	60/60
DSH0364D	460/3/60	1	4.9	44.3	1	0.17	0.48	1	1.2	2.5	-	-	-	-	-	58.2/64.3	60/70
											-	-	-	9.6/8.7	-	67.8/73.0	70/80
											-	-	-	-	2.2/1.9 (1.7/1.5)	60.4/66.2	70/70
											-	-	-	9.6/8.7	2.2/1.9 (1.7/1.5)	70.0/74.9	80/80
											EH*D-4S05A	5.0	6.0	-	-	9.1	15
											-	-	-	4.3	-	13.4	15
											-	-	-	-	0.9 (0.5)	10.0	15
											-	-	-	4.3	0.9 (0.5)	14.3	15
											EH*D-4S10A	10.0	12.0	-	-	16.6	20
											-	-	-	4.3	-	20.9	25
											-	-	-	-	0.9 (0.5)	17.5	20
											EH*D-4S15A	15.0	18.0	4.3	0.9 (0.5)	21.8	25
											-	-	-	-	-	24.1	25
DSH0364D	460/3/60	1	4.9	44.3	1	0.17	0.48	1	1.2	2.5	-	-	-	4.3	-	28.4	30
											-	-	-	-	0.9 (0.5)	25.0	25
											-	-	-	4.3	0.9 (0.5)	29.3	30
											-	-	-	-	-	31.6	35
											EH*D-4S15A	15.0	18.0	4.3	-	35.9	40
											-	-	-	-	0.9 (0.5)	32.5	35
DSH0364D	460/3/60	1	4.9	44.3	1	0.17	0.48	1	1.2	2.5	-	-	-	4.3	0.9 (0.5)	36.8	40
											-	-	-	-	-	-	-
											-	-	-	-	-	-	-
											-	-	-	-	-	-	-
											-	-	-	-	-	-	-
											-	-	-	-	-	-	-