Quick Selection Tool

Application Factor Details

System Balance is 7,020 BTU/H @ 10.84°F TD

Condensing Unit



BCH0005MBACZA0000

Preferred Options

A0000 - Standard Base - $12,038

AWEF	7.6

Meets Minimum AWEF
Does NOT Meet Minimum AWEF

Compressor	ZB06KAE
Capacity	7,020
ModelStyle	1/2-6 Horizontal Air Discharge
Platform	HTS
Application	Medium Temp (Cooler)
Power	208-230/1/60
CompressorRLA	5.4
CompressorLRA	35.7
Depth	28.25
Width	24.625
Height	19.75
NetWt.	167

- Hide Technical Data

Total: $12,038X1

Evaporator



BEL0045AS6AMAB0405

Preferred Options

B0405 - Mounted Components (TXV, Solenoid Valve, T'Stat - R-448A/R-449A) -

AWEF	9

Meets Minimum AWEF
Does NOT Meet Minimum AWEF

ModelStyle	Low Profile
Capacity	4,600
Defrost	Air Defrost
Platform	LOP
Application	Medium Temp (Cooler)
FPI	6
NoofFans	1
CoilInletOD	1/2
SuctionOD	1/2
EqualizerOD	1/4
DrainMPT	3/4
SidePortOD	-
HotGasPanConns.OD	-
Depth(in.)	13.25
Length(in.)	29.5

- Hide Technical Data

Total: $5,458X1

Total: $17,496

Source: Heatcraft Refrigeration Products Quick Selection Tool, heatcraftrpd.com/resources/tools/quick-selection/
Selection run 11/11/2026 | 6x6x8 cooler, 35F, 95F ambient, +25F SST, R-448A