


MSZ-FX18NL
17,200 BTU/H WALL-MOUNTED INDOOR UNIT



Job Name:

System Reference:

Date:



GENERAL FEATURES

- **Smart Dry Plus Mode:** The Smart Dry+ mode intelligently provides precise humidity control with minimal over-cooling of the space.
- **Wi-Fi Enabled:** Wi-Fi enabled units pair with the Comfort app for complete control over temperature, fan speeds, modes, schedules, and more.
- **Dual Barrier Coating:** Dual Barrier Coating reduces the collection of contaminants like dust, fibers, smoke, and oil on the inner surface of the indoor unit.
- **Dual Barrier Fusion:** Dual Barrier Fusion reduces the collection of contaminants like dust, fibers, smoke, and oil on the vane of the indoor unit. Dual Barrier Fusion's shielding power is fused directly into the material of the vanes during manufacturing.
- **3D i-see Sensor® (Built-in):** This advanced sensor scans the room for occupancy, then adjusts temperature and airflow based on user preferences, and saves energy when a room is empty.
- **Dual Vane:** Dual-Vane feature allows for airflow direction to be set independently using two vanes, which can then deliver airflow across wide areas of a room, levels of a zone, or to two people in different locations at the same time.

SPECIFICATIONS			SYSTEM
UNIT TYPE			MSZ-FX18NL
Cooling Capacity (Nominal) ^{1,3}	Cooling Capacity (Nominal)	Btu/h	17200
Heating Capacity (Nominal) ^{2,3}	Heating Capacity (Nominal)	Btu/h	17000
Electrical	Voltage, Phase, Frequency	V AC / V AC , Ø , Hz	208 / 230 , 1 , 60
	Voltage: Indoor - Outdoor, S1-S2	V AC	208/230
	Voltage: Indoor - Outdoor, S2-S3	V DC	12-24
	Short-circuit Current Rating [SCCR]	kA	5
	MCA	A	1
Indoor Unit	Fan Motor Type		DC Motor
	Fan Motor Output	W	40
	Airflow Rate at Cooling, Dry	CFM	272 , 339 , 392 , 456 , 593
	Airflow Rate at Cooling, Wet	CFM	231 , 288 , 333 , 387 , 504
	Airflow Rate at Heating, Dry	CFM	272 , 311 , 378 , 456 , 614
	Sound Pressure Level [Cooling]	dB (A)	27 , 31 , 35 , 39 , 45
	Sound Pressure Level [Heating]	dB (A)	26 , 29 , 34 , 39 , 47
	Dual Barrier Coating on Heat Exchanger		Yes
	External Finish Color		Munsell 1.0Y 9.2/0.2
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	39 -9/32 x 9-3/4 x 12 [998 x 247 x 305]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	43 -5/16 x 12-3/4 x 15-3/4 [1100 x 330 x 400]
	Unit Weight	lbs [kg]	31.40 [14.20]
	Package Weight	lbs [kg]	36.40 [16.50]
Refrigerant	Type		R454B
Piping	Liquid Pipe Size O.D.	inch [mm]	1/4 [6.35]
	Gas Pipe Size O.D.	inch [mm]	1/2 [12.70]

Notes

¹Cooling (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB - test

²Heating at 47°F (Indoor // Outdoor) °F 70 DB, 60 WB // 47 DB, 43 WB


³Nominal capacity only. Actual capacity output varies based on the system specific configuration

INDOOR UNIT ACCESSORIES: MSZ-FX18NL

Condensate	Refco Condensate Pump 100-240V up to 120k BTU/h	☐ COMBI
	Blue Diamond MicroBlue Condensate Pump with Fascia Kit 115-230V up to 18k BTU/h	☐ X86-011
	Blue Diamond (MaxiBlue Advanced) Mini Condensate Pump w/ Reservoir & Sensor (110V) up to 48,000 BTU/H [recommended]	☐ X87-711
	Blue Diamond MegaBlue Condensate Pump with Reservoir Sensor 115-230V up to 170k BTU/h	☐ X87-835
	Drain Pan Level Sensor/Control	☐ SS610E
	Blue Diamond MaxiBlue Condensate Pump with Reservoir Sensor 115-230V up to 48k BTU/h	☐ X88-721
	Sauermann Condensate Pump 120-230V up to 60k BTU/h	☐ SI30-230
	Blue Diamond Sensor Extension Cable 15 Ft	☐ C13-103
	Refco Condensate Removal Pump with Wall Mount Enclosure 120-240V up to 120k BTU/h	☐ GOB-II
	Blue Diamond MicroBlue Condensate Pump 115-230V up to 18k BTU/h	☐ X86-003
Control Interface	Airzone Wireless Lite Controller Black	☐ AZZBSLITERN
	Wireless Interface 2 for Comfort app	☐ PAC-USWHS002-WF-2
	M-Net I/O Control Interface for M-Series ²	☐ MAC-334IF-E
	kumo station® for Comfort app	☐ PAC-WHS01HC-E
	Thermostat Interface for 3rd Party Thermostats	☐ PAC-US445CN-1
	Airzone Wireless Think Controller Black	☐ AZZBSTHINKRN
	Airzone Wireless Think Controller White	☐ AZZBSTHINKRB
	Airzone Wired Blueface Controller White	☐ AZZBSBLUEZEROCB
	IT Extender	☐ PAC-WHS01IE-E
	Airzone Wireless Lite Controller White	☐ AZZBSLITERB
	Procon BACnet® and Modbus® Interface	☐ PAC-UKPRC001-CN-1
	Airzone Wired Blueface Controller Black	☐ AZZBSBLUEZEROCN
Disconnect Switch	(30A/600V/UL) [fits 2" X 4" utility box] - White	☐ TAZ-MS303W
	30A600VUL fits 2 X 4 utility box - Black	☐ TAZ-MS303
Drain Hose	Flexible Mini-Split Drain Hose	☐ DRX-16
Filter	Platinum Deodorizing Filter	☐ MAC-3010FT-E
Lineset	1/4 x 1/2 Lineset Twin-Tube Insulation - 30 feet	☐ MLS141212T-30
	1/4 x 1/2 Lineset Twin-Tube Insulation - 65 feet	☐ MLS141212T-65
	1/4 x 1/2 Lineset Twin-Tube Insulation - 100 feet	☐ MLS141212T-100
	1/4 x 1/2 Lineset Twin-Tube Insulation - 15 feet	☐ MLS141212T-15
	1/4 x 1/2 Lineset Twin-Tube Insulation - 50 feet	☐ MLS141212T-50
N/A		☐ Unknown
Remote Sensor	Wireless temperature and humidity sensor for Comfort app	☐ PAC-USWHS003-TH-1
	Remote Temperature Sensor for MFZ MLZ and MSZ models	☐ M21EAA307
Terminal Signal Adapter	Backup Heat Relay Kit	☐ CN24RELAY-KIT-CM3
Wired Remote Controller	Simple MA Remote Controller ¹	☐ PAC-YT53CRAU-J
	Deluxe MA Wired Remote Controller ¹	☐ PAR-42MAAUB
	Simple Direct Wired Remote Controller	☐ PAC-SDW01RC-1
	Touch MA Remote Controller ¹	☐ PAR-CT01MAU-SB
Wireless Remote Controller	Wireless RedLINK™ Remote Controller	☐ MHK2
	Lockdown Bracket for Wireless Handheld Remote Controllers	☐ RCMKP1CB
Notes		

INDOOR UNIT DIMENSIONS: MSZ-FX18NL

MSZ-FX06NL-U1
MSZ-FX09NL-U1
MSZ-FX12NL-U1
MSZ-FX15NL-U1
MSZ-FX18NL-U1
MSZ-FX24NL-U1



MSZ-FX06/09/12NL

PIPING	INSULATION	ø1-9/16 O.D
	LIQUID LINE	ø1/4 - 19-11/16 (FLARED CONNECTION ø1/4)
	GAS LINE	ø3/8 - 17-3/4 (FLARED CONNECTION ø3/8)
DRAIN HOSE		INSULATION ø1-5/32 CONNECTED PART ø5/8 O.D

MSZ-FX15/18NL

PIPING	INSULATION	ø1-9/16 O.D
	LIQUID LINE	ø1/4 - 19-11/16 (FLARED CONNECTION ø1/4)
	GAS LINE	ø3/8 - 17-3/4 (FLARED CONNECTION ø1/2)
DRAIN HOSE		INSULATION ø1-5/32 CONNECTED PART ø5/8 O.D

MSZ-FX24NL

PIPING	INSULATION	ø1-9/16 O.D
	LIQUID LINE	ø1/4 - 19-11/16 (FLARED CONNECTION ø1/4)
	GAS LINE	ø15/32 - 17-3/4 (FLARED CONNECTION ø5/8)
DRAIN HOSE		INSULATION ø1-5/32 CONNECTED PART ø5/8 O.D

*The diameter of the gas line piping is ø3/8 in one spot.