


MSZ-GX24NL
22,400 BTU/H WALL-MOUNTED INDOOR UNIT



Job Name:

System Reference:

Date:



GENERAL FEATURES

- **Dual Barrier Coating:** Dual Barrier Coating reduces the collection of contaminants like dust, fibers, smoke, and oil on the inner surface of the indoor unit.
- **Swing Mode:** An indoor unit with this capability can move air throughout the room like an oscillating fan.
- **Econo Cool:** Econo Cool is feature that temporarily adjusts the airflow to maintain comfort while using less energy.
- **Quiet:** Our indoor units offer whisper-quiet operation as low as 19 dB(A). Our outdoor units are design for ultra quiet operation.
- **Horizontal Vane Control:** Horizontal Vane Control allows the indoor unit vanes to be moved left right to provide even temperatures throughout a space.
- **Wi-Fi Enabled:** Wi-Fi enabled units pair with the Comfort app for complete control over temperature, fan speeds, modes, schedules, and more.

SPECIFICATIONS			SYSTEM
UNIT TYPE			MSZ-GX24NL
Cooling Capacity (Nominal) ^{1,3}	Cooling Capacity (Nominal)	Btu/h	22400
Heating Capacity (Nominal) ^{2,3}	Heating Capacity (Nominal)	Btu/h	27600
Electrical	Voltage, Phase, Frequency	V AC / V AC , ø , Hz	208 / 230 , 1 , 60
	Voltage: Indoor - Outdoor, S1-S2	V AC	208/230
Indoor Unit	MCA	A	1
	Fan Motor Type		DC Motor
	Fan Motor Output	W	56
	Airflow Rate at Cooling, Dry	CFM	324 , 392 , 454 , 636 , 765
	Airflow Rate at Cooling, Wet	CFM	292 , 353 , 408 , 573 , 688
	Airflow Rate at Heating, Dry	CFM	344 , 392 , 454 , 530 , 765
	Sound Pressure Level [Cooling]	dB (A)	30 , 37 , 41 , 48 , 53
	Sound Pressure Level [Heating]	dB (A)	30 , 37 , 41 , 45 , 50
	Dual Barrier Coating on Heat Exchanger		Yes
	Dual Barrier Coating on Fan		Yes
	External Finish Color		Munsell 0.7PB 9.2/0.4
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	43-5/16 x 10-1/8 x 12-13/16 [1100 x 257 x 325]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	45-1/2 x 15-1/2 x 13-1/2 [1160 x 400 x 340]
Refrigerant	Unit Weight	lbs [kg]	37 [16.50]
	Package Weight	lbs [kg]	42 [18.80]
Piping	Liquid Pipe Size O.D.	inch [mm]	1/4 [6.35]
	Gas Pipe Size O.D.	inch [mm]	5/8 [15.88]
Indoor Unit	Drain Pipe Size O.D.	inch [mm]	5/8 [16]

Notes

¹Cooling (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB - test

²Heating at 47°F (Indoor // Outdoor) °F 70 DB, 60 WB // 47 DB, 43 WB


³Nominal capacity only. Actual capacity output varies based on the system specific configuration

INDOOR UNIT ACCESSORIES: MSZ-GX24NL

Condensate	Blue Diamond Sensor Extension Cable 15 Ft	☐ C13-103
	Blue Diamond MaxiBlue Condensate Pump with Reservoir Sensor 115-230V up to 48k BTU/h	☐ X88-721
	Refco Condensate Pump 100-240V up to 120k BTU/h	☐ COMBI
	Refco Condensate Removal Pump with Wall Mount Enclosure 120-240V up to 120k BTU/h	☐ GOBI-II
	Blue Diamond MegaBlue Condensate Pump with Reservoir Sensor 115-230V up to 170k BTU/h	☐ X87-835
	Sauermann Condensate Pump 120-230V up to 60k BTU/h	☐ SI30-230
	Drain Pan Level Sensor/Control	☐ SS610E
	Blue Diamond (MaxiBlue Advanced) Mini Condensate Pump w/ Reservoir & Sensor (110V) up to 48,000 BTU/H [recommended]	☐ X87-711
Control Interface	Airzone Wireless Think Controller White	☐ AZZBSTHINKRB
	IT Extender	☐ PAC-WHS01IE-E
	kumo station® for Comfort app	☐ PAC-WHS01HC-E
	Airzone Wired Blueface Controller White	☐ AZZBSBLUEZEROCB
	Airzone Wireless Lite Controller White	☐ AZZBSLITERB
	Airzone Wireless Lite Controller Black	☐ AZZBSLITERN
	Airzone Wireless Think Controller Black	☐ AZZBSTHINKRN
	Procon BACnet® and Modbus® Interface	☐ PAC-UKPRC001-CN-1
	Thermostat Interface for 3rd Party Thermostats	☐ PAC-US445CN-1
	Airzone Wired Blueface Controller Black	☐ AZZBSBLUEZEROCN
	M-Net I/O Control Interface for M-Series ²	☐ MAC-334IF-E
	Wireless Interface 2 for Comfrot app	☐ PAC-USWHS002-WF-2
Disconnect Switch	30A600VUL fits 2 X 4 utility box - Black	☐ TAZ-MS303
	(30A/600V/UL) [fits 2" X 4" utility box] - White	☐ TAZ-MS303W
Drain Hose	Flexible Mini-Split Drain Hose	☐ DRX-16
Filter	Microparticle Filter	☐ MAC-EMF515FT-E
	Microparticle Filter	☐ MAC-EMF615FT-E
	Electro Static Anti-allergy Enzyme Filter	☐ MAC-2320FT-E
Lineset	1/4 x 5/8 Lineset Twin-Tube Insulation - 15 feet	☐ MLS145812T-15
	1/4 x 5/8 Lineset Twin-Tube Insulation - 100 feet	☐ MLS145812T-100
	1/4 x 5/8 Lineset Twin-Tube Insulation - 50 feet	☐ MLS145812T-50
	1/4 x 5/8 Lineset Twin-Tube Insulation - 65 feet	☐ MLS145812T-65
	1/4 x 5/8 Lineset Twin-Tube Insulation - 30 feet	☐ MLS145812T-30
N/A		☐ Unknown
Remote Sensor	Wireless temperature and humidity sensor for Comfort app	☐ PAC-USWHS003-TH-1
	Remote Temperature Sensor for MFZ MLZ and MSZ models	☐ M21EAA307
Terminal Signal Adapter	Backup Heat Relay Kit	☐ CN24RELAY-KIT-CM3
Wired Remote Controller	Simple MA Remote Controller ¹	☐ PAC-YT53CRAU-J
	Simple Direct Wired Remote Controller	☐ PAC-SDW01RC-1
	Touch MA Remote Controller ¹	☐ PAR-CT01MAU-SB
	Deluxe MA Wired Remote Controller ¹	☐ PAR-42MAAUB
Wireless Remote Controller	Lockdown Bracket for Wireless Handheld Remote Controllers	☐ RCMKP1CB
	Wireless RedLINK™ Remote Controller	☐ MHK2
Notes		

INDOOR UNIT DIMENSIONS: MSZ-GX24NL

MSZ-GX18NL-U1 MSY-GX18NL-U1
MSZ-GX24NL-U1 MSY-GX24NL-U1
MSZ-GX30NL-U1 MSY-GX30NL-U1
MSZ-GX36NL-U1 MSY-GX36NL-U1



MSZ-GX18NL-U1
MSY-GX18NL-U1

INSULATION	#2 O.D.
LIQUID LINE	#3/8 - 19-11/16 (FLARED CONNECTION #1/4)
GAS LINE	#1/2 - 17-11/16 (FLARED CONNECTION #1/2)
DRAIN HOSE	INSULATION #1-1/8 CONNECTED PART #5/8 O.D.

MSZ-GX24/30/36NL-U1
MSY-GX24/30/36NL-U1

INSULATION	#2 O.D.
LIQUID LINE	#3/8 - 19-11/16 (FLARED CONNECTION #1/4)
GAS LINE	#1/2 - 17-11/16 (FLARED CONNECTION #5/8)
DRAIN HOSE	INSULATION #1-1/8 CONNECTED PART #5/8 O.D.

1340 Satellite Boulevard Suwanee, GA 30024
Toll Free: 800-433-4822 · mitsubishicomfort.com