

PEAD-AA30NL
30,000 BTU/H HORIZONTAL-DUCTED INDOOR UNIT



Job Name:

System Reference:

Date:



GENERAL FEATURES

- Light Commercial: Light commercial applications include small offices, restaurants, and retail.
- Four Speed Fan: Adjust the fan between four speed settings to optimal comfort.
- Auto Changeover: The unit will automatically switch between heating and cooling modes to maintain your desired temperature.
- Condensate Lift Mechanism: A built-in condensate lift mechanism removes water that is collected during operation and reduces the need for an additional pump to remove condensate water.

SPECIFICATIONS			SYSTEM
UNIT TYPE			PEAD-AA30NL
Cooling Capacity (Nominal) ^{1,3}	Cooling Capacity (Nominal)	Btu/h	30000
Heating Capacity (Nominal) ^{2,3}	Heating Capacity (Nominal)	Btu/h	30000
Electrical	Voltage, Phase, Frequency	V AC / V AC , ø , Hz	208 / 230 , 1 , 60
	Voltage: Indoor - Outdoor, S1-S2	V AC	208/230
	Voltage: Indoor - Outdoor, S2-S3	V DC	12-24
Indoor Unit	MCA	A	2.25
	MOCP	A	15
	Fan Motor Type		DC Motor
	Fan Motor Output	W	121
	Airflow Rate at Cooling, Dry	CFM	618 , 671 , 742 , 883
	Airflow Rate at Heating, Dry	CFM	618 , 671 , 742 , 883
	Sound Pressure Level [Cooling]	dB (A)	30 , 32 , 34 , 38
	Sound Pressure Level [Heating]	dB (A)	30 , 32 , 34 , 38
	External Static Pressure	in.WG	0.14 , 0.20 , 0.28 , 0.40 , 0.60
	Dual Barrier Coating on Heat Exchanger		No
	Dual Barrier Coating on Fan		No
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	43-5/16 x 28-7/8 x 9-7/8 [1100 x 732 x 250]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	53-15/16 x 35-7/16 x 13 [1370 x 900 x 330]
	Unit Weight	lbs [kg]	67 [30]
	Package Weight	lbs [kg]	79 [36]
Refrigerant	Type		R454B
Piping	Liquid Pipe Size O.D.	inch [mm]	3/8 [9.52]
	Gas Pipe Size O.D.	inch [mm]	5/8 [15.88]
Indoor Unit	Drain Pipe Size O.D.	inch [mm]	1-1/4 [32]

Notes

¹Cooling (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB - test

²Heating at 47°F (Indoor // Outdoor) °F 70 DB, 60 WB // 47 DB, 43 WB

³Nominal capacity only. Actual capacity output varies based on the system specific configuration

INDOOR UNIT ACCESSORIES: PEAD-AA30NL

Condensate	Blue Diamond MaxiBlue Condensate Pump with Reservoir Sensor 115-230V up to 48k BTU/h	☐ X88-721
	Blue Diamond MegaBlue Condensate Pump with Reservoir Sensor 115-230V up to 170k BTU/h	☐ X87-835
	Blue Diamond Sensor Extension Cable 15 Ft	☐ C13-103
	Refco Condensate Pump 100-240V up to 120k BTU/h	☐ COMBI
	Blue Diamond (MaxiBlue Advanced) Mini Condensate Pump w/ Reservoir & Sensor (110V) up to 48,000 BTU/H [recommended]	☐ X87-711
	Sauermann Condensate Pump 120-230V up to 60k BTU/h	☐ SI30-230
Control Interface	Airzone Wireless Lite Controller White	☐ AZZBSLITERB
	Airzone Wireless Think Controller Black	☐ AZZBSTHINKRN
	kumo station® for Comfort app	☐ PAC-WHS01HC-E
	Wireless Interface 2 for Comfrot app	☐ PAC-USWHS002-WF-2
	IT Extender	☐ PAC-WHS01IE-E
	Operation and Error Status Output Adapter	☐ PAC-SF40RM-E
	Airzone Wired Blueface Controller White	☐ AZZBSBLUEZEROCB
	Airzone Wired Blueface Controller Black	☐ AZZBSBLUEZEROCN
	Procon BACnet® and Modbus® Interface	☐ PAC-UKPRC001-CN-1
	Airzone Wireless Lite Controller Black	☐ AZZBSLITERN
	Thermostat Interface for 3rd Party Thermostats	☐ PAC-US445CN-1
	Airzone Wireless Think Controller White	☐ AZZBSTHINKRB
Control Wire	202PR shielded 1PR plenum wire for Airzone 500 ft reel	☐ CW2042S2-500
	202PR 1PR shielded 1PR plenum wire for Airzone 100 ft reel	☐ CW2042S2-100
Disconnect Switch	(30A/600V/UL) [fits 2" X 4" utility box] - White	☐ TAZ-MS303W
	30A600VUL fits 2 X 4 utility box - Black	☐ TAZ-MS303
Filter Box	Filter Box with 2" thick pleated MERV 13 Filters	☐ FBM2-3-A
Lineset	3/8 x 5/8 Lineset Twin-Tube Insulation - 15 feet	☐ MPLS385812T-15
	1/4 x 5/8 Lineset Twin-Tube Insulation - 30 feet	☐ MLS145812T-30
	1/4 x 5/8 Lineset Twin-Tube Insulation - 50 feet	☐ MLS145812T-50
	1/4 x 5/8 Lineset Twin-Tube Insulation - 65 feet	☐ MLS145812T-65
	3/8 x 5/8 Lineset Twin-Tube Insulation - 50 feet	☐ MPLS385812T-50
	3/8 x 5/8 Lineset Twin-Tube Insulation - 30 feet	☐ MPLS385812T-30
	3/8 x 5/8 Lineset Twin-Tube Insulation - 65 feet	☐ MPLS385812T-65
	3/8 x 5/8 Lineset Twin-Tube Insulation - 100 feet	☐ MPLS385812T-100
	1/4 x 5/8 Lineset Twin-Tube Insulation - 15 feet	☐ MLS145812T-15
	1/4 x 5/8 Lineset Twin-Tube Insulation - 100 feet	☐ MLS145812T-100
N/A		☐ Unknown
Remote Sensor	Wall Mounted Remote Temperature Sensor	☐ PAC-SE41TS-E
	Flush Mount Remote Temperature Sensor for SEZ SLZ SVZ and all P-Series models	☐ PAC-USSEN002-FM-1
	Wireless temperature and humidity sensor for Comfort app	☐ PAC-USWHS003-TH-1
Terminal Signal Adapter	Backup Heat Relay Kit	☐ CN24RELAY-KIT-CM3
	5-Pin Wiring Harness	☐ PAC-725AD
	3-Pin Wiring Harness	☐ PAC-715AD
Wired Remote Controller	Touch MA Remote Controller	☐ PAR-CT01MAU-SB
	Deluxe MA Wired Remote Controller	☐ PAR-42MAAUB
	Simple Direct Wired Remote Controller	☐ PAC-SDW01RC-1
	Simple MA Remote Controller	☐ PAC-YT53CRAU-J
Wireless Remote Controller	Wireless RedLINK™ Remote Controller	☐ MHK2
	Lockdown Bracket for Wireless Handheld Remote Controllers	☐ RCMKP1CB
	Wireless Remote Controller	☐ PAR-SL101A-E
	Universal Wireless Receiver for PAR-FL32MA-E	☐ PAR-FA32MA-W
	Wireless MA Handheld Remote Controller (requires PAR-FA32MA-E)	☐ PAR-FL32MA-E
Notes		

METUS_2026-04_PROPIN

