PVA-AA30NL & PUY-AH30NL
30,000 BTU/H MULTI-POSITION AIR HANDLER INDOOR UNIT
27,000 BTU/H COOLING ONLY OUTDOOR UNIT

Job Name:			
System Reference:		**Date:**	





INDOOR Unit ... PVA-AA30NL

OUTDOOR Unit ... PUY-AH30NL

INDOOR UNIT FEATURES

- Multi-Position Installation: Versatile installation options, including horizontal (left or right) and vertical (up or down) orientations, with included drain pans to facilitate easy setup for any configuration.
- Wi-Fi Optional: A Wireless Interface Adapter can be ordered as an accessory for field installation.
- Three Speed Fan: Adjust the fan between three speed settings to optimal comfort.
- Blow-through design: Unique blow-through design allows simple coil cleaning when the blower is removed.
- Auto Changeover: The unit will automatically switch between heating and cooling modes to maintain your desired temperature.

OUTDOOR UNIT FEATURES

- Inverter Driven Compressor: Inverter technology uses only the precise amount of energy needed to keep a space comfortable.
- Blue Fin Coating: Anti-corrosion coating that protects the outdoor heat exchanger against salt, sulfur, and other airborne contaminants that impact the efficiency and performance of the outdoor units.
- Seacoast Protection: An anti-corrosion treatment applied to the aluminum fins of the heat exchanger of the outdoor unit to protect against corrosion caused by salt, sulfur, and other airborne contaminants, especially in coastal and industrial areas.
- Low Ambient Cooling: Low ambient cooling down to -40°F providing 100% capacity with front, side and rear wind baffle kit
- Low Ambient Cooling: Low ambient cooling down to 0°F providing 100% capacity with front wind baffle kit

Specifications are subject to change without notice.

© 2026 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

SPECIFICATIONS: PVA-AA30NL & PUY-AH30NL

Cooling at 95F[1]	Maximum Capacity	Btu/h	30600
	Rated Capacity	Btu/h	30000
	Minimum Capacity	Btu/h	10200
	Maximum Power Input	W	3100
	Rated Power Input	W	3030
	Moisture Removal	Pints/h	10.50
	Sensible Heat Factor		0.62
	Power Factor [208V / 230V]	%	93 / 93
Efficiency	SEER2		18
	EER2[1]		9.90
	ENERGY STAR® Certified		No
Electrical	Voltage, Phase, Frequency	V AC / V AC , ø , Hz	208 / 230 , 1 , 60
	Guaranteed Voltage Range	V AC	198 - 253
	Voltage: Indoor - Outdoor, S1-S2	V AC	208/230
	Voltage: Indoor - Outdoor, S2-S3	V DC	12-24
	Short-circuit Current Rating [SCCR]	kA	5
	Recommended Fuse/Breaker Size (Outdoor)	A	25
	Recommended Wire Size [Indoor - Outdoor]	AWG	14
Indoor Unit	MCA	A	4.13
	Breaker Size	A	15
	Fan Motor Output	W	244
	Fan Motor Type		Direct-driven DC Brushless Motor
	Airflow Rate at Cooling, Dry	CFM	613 , 744 , 875
	Sound Pressure Level [Cooling]	dB (A)	34 , 40 , 44
	External Static Pressure	in.WG	0.30 , 0.50 , 0.80
	Drain Pipe Size O.D.	inch [mm]	3/4 [19.05]
	External Finish Color		Galvanized steel cabinet-Powder coated Slate Gray
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	21 x 21-5/8 x 54-1/4 [534 x 548 x 1378]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	22 x 28-11/16 x 61 [558 x 728 x 1549]
	Unit Weight	lbs [kg]	141 [64]
	Package Weight	lbs [kg]	163 [74]
IDU Operating Temp. Range	Cooling Intake Air Temp [Maximum / Minimum]	°FDB , °FWB / °FDB , °FWB	90 , 72 / 66 , 61
Outdoor Unit	MCA	A	22
	MOCP	A	37
	Fan Motor Output	W	74
	Airflow Rate Cooling	CFM	1940
	Coating on Heat Exchanger (Bluefin, Sea Coast)		Yes , Yes
	Sound Pressure Level, Cooling[1]	dB (A)	49
	Compressor Type		Twin Rotary
	Compressor Model		SRB172FQHMC-L1
	Compressor Oil [Type // Charge]	// oz	RM68EH // 23
	External Finish Color		Munsell 3Y 7.8/1.1
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	37-13/32 x 14 x 37-1/8 [950 x 355 x 943]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	41-15/16 x 17-3/4 x 42-1/2 [1065 x 450 x 1079]
	Unit Weight	lbs [kg]	155 [70]
	Package Weight	lbs [kg]	179 [81]
ODU Operating Temp. Range	Cooling Intake Air Temp [Maximum / Minimum*]	°FDB	115 / 23
	Cooling Thermal Lock-out / Re-start Temperatures**	°FDB	N/A / N/A
Refrigerant	Type		R454B
	Pre-Charged Refrigerant Amount	lbs , oz	7 , 11
	Maximum Pre-Charged Piping Length	ft [m]	225 [69]
	Additional Refrigerant Charge Per Additional Piping Length	oz/ft	0
Piping	Liquid Pipe Size O.D. [Flared]	inch [mm]	3/8 [9.52]
	Gas Pipe Size O.D. [Flared]	inch [mm]	5/8 [15.88]
	Maximum Piping Length	ft [m]	225 [69]

Notes

[1]Cooling at 95°F (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB

*Indoor/Outdoor Unit Operating Temperature Range (Cooling Air Temp [Maximum / Minimum]): • Wind baffles required to operate below 23°F DB in cooling mode. • Cooling-only system with advanced wind baffle: -40°F - 115°F. • Refer to wind baffle documentation for further information.

**Outdoor Unit Operating Temperature Range (Cooling Thermal Lock-out / Re-start Temperatures):

© 2026 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

Piping	Maximum Height Difference	ft [m]	100 [30]
	Maximum Number of Bends		15

Notes

[1]Cooling at 95°F (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB
[*]Indoor/Outdoor Unit Operating Temperature Range (Cooling Air Temp [Maximum / Minimum]): • Wind baffles required to operate below 23°F DB in cooling mode. • Cooling-only system with advanced wind baffle: -40°F - 115°F. • Refer to wind baffle documentation for further information.
[**]Outdoor Unit Operating Temperature Range (Cooling Thermal Lock-out / Re-start Temperatures):

© 2026 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

INDOOR UNIT ACCESSORIES: PVA-AA30NL

Condensate	Blue Diamond Sensor Extension Cable 15 Ft	C13-103
	Blue Diamond MaxiBlue Condensate Pump with Reservoir Sensor 115-230V up to 48k BTU/h	X88-721
	Blue Diamond MaxiBlue Advanced Mini Condensate Pump w Reservoir Sensor 110V up to 48000 BTUH recommended	X87-711
	Sauermann Condensate Pump 120-230V up to 60k BTU/h	SI30-230
	Refco Condensate Pump 100-240V up to 120k BTU/h	COMBI
	Blue Diamond MegaBlue Condensate Pump with Reservoir Sensor 115-230V up to 170k BTU/h	X87-835
Control Interface	IT Extender	PAC-WHS01IE-E
	Procon BACnet® and Modbus® Interface	PAC-UKPRC001-CN-1
	Airzone Wireless Think Controller White	AZZBSTHINKRB
	Thermostat Interface for 3rd Party Thermostats	PAC-US445CN-1
	kumo station® for Comfort app	PAC-WHS01HC-E
	Airzone Wired Lite Controller White	AZZBSLITECB
	Airzone Wired Blueface Controller White	AZZBSBLUEZEROCB
	Airzone Wireless Think Controller Black	AZZBSTHINKRN
	Airzone Wireless Lite Controller White	AZZBSLITERB
	Operation and Error Status Output Adapter	PAC-SF40RM-E
	Wireless Interface 2 for Comfrot app	PAC-USWHS002-WF-2
	Airzone Wired Blueface Controller Black	AZZBSBLUEZEROCN
Control Wire	202PR 1PR shielded 1PR plenum wire for Airzone 100 ft reel	CW2042S2-100
	202PR shielded 1PR plenum wire for Airzone 500 ft reel	CW2042S2-500
Disconnect Switch	30A600VUL fits 2 X 4 utility box - Black	TAZ-MS303
	30A600VUL fits 2 X 4 utility box - White	TAZ-MS303W
Downflow Kit	Downflow Kit	CMA-1
Electric Heat Lockout	Electric Heat Lockout	ETC-211020-MIT
Electric Kit Heats	8kW Electric Heater Module - Medium Cabinet	EH08-MPA-MB
	5kW Electric Heater Module - Medium Cabinet	EH05-MPA-MB
	10kW Electric Heater Module - Medium Cabinet	EH10-MPA-MB
	3kW Electric Heater Module - Medium Cabinet	EH03-MPA-MB
Lineset	3/8 x 5/8 Lineset Twin-Tube Insulation - 50 feet	MPLS385812T-50
	3/8 x 5/8 Lineset Twin-Tube Insulation - 10 feet	MPLS385812T-10
	3/8 x 5/8 Lineset Twin-Tube Insulation - 15 feet	MPLS385812T-15
	3/8 x 5/8 Lineset Twin-Tube Insulation - 65 feet	MPLS385812T-65
	3/8 x 5/8 Lineset Twin-Tube Insulation - 30 feet	MPLS385812T-30
	3/8 x 5/8 Lineset Twin-Tube Insulation - 100 feet	MPLS385812T-100
Remote Sensor	Wireless temperature and humidity sensor for Comfort app	PAC-USWHS003-TH-1
	Wall Mount Remote Temperature Sensor	PAC-SE41TS-E
	Flush Mount Remote Temperature Sensor for SEZ SLZ SVZ and all P-Series models	PAC-USSEN002-FM-1
Terminal Block	Separate Terminal Power Block	SPTB1
Terminal Signal Adapter	Connector and wire for On/Off and Fan command using CN32	PAC-715AD
	Connector and wire for On/Off and Error status using CN51 and CN52	PAC-725AD
	Backup Heat Relay Kit	CN24RELAY-KIT-CM3
	ERV On/Off Input Adapter for CNER on SVZ PEAD and PVA models	PAC-740
Wired Remote Controller	Deluxe Wired MA Remote Controller	PAR-42MAAUB
	Simple MA Remote Controller	PAC-YT53CRAU-J
	Touch MA Remote Controller	PAR-CT01MAU-SB
	Simple Direct Wired Remote Controller	PAC-SDW01RC-1
Wireless Remote Controller	Universal Wireless Receiver for PAR-FL32MA-E	PAR-FA32MA-W
	Wireless RedLINK™ Remote Controller	MHK2
	Wireless MA Handheld Remote Controller (requires PAR-FA32MA-E)	PAR-FL32MA-E
	Lockdown Bracket for Wireless Handheld Remote Controllers	RCMKP1CB

Notes

[1]Requires MAC-334IF-E Interface to connect MA controller
[1]Unable to use with Wireless Handheld Remote Controller

© 2026 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

INDOOR UNIT ACCESSORIES: PVA-AA30NL

Wireless Remote Controller	Wireless Remote Contoller	☐ PAR-SL101A-E

Notes

[1]Requires MAC-334IF-E Interface to connect MA controller
[1]Unable to use with Wireless Handheld Remote Controller

Specifications are subject to change without notice.
© 2026 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.


OUTDOOR UNIT ACCESSORIES: PUY-AH30NL

Air Outlet Guide	Air Outlet Guide 1 Piece	PAC-SG59SG-E
Centralized Drain Pan	Centralized Drain Pan	PAC-SG64DP-E
Control/Service Tool	ControlService Tool	PAC-SK52ST
	M- & P-Series Maintenance Tool Cable Set	M21EC0397
Drain Socket	Drain Socket	PAC-SG61DS-E
Hail Guards	Hail Guard	HG-A6
M-NET Converter	M-Net Interface for P-Series	PAC-SJ95MA-E
Mini-Split Wire	14 Gauge 4 wire MiniSplit Cable50 ft roll	S144-50
	14 Gauge 4 wire MiniSplit Cable250 ft roll	S144-250
	14 Gauge 4 wire Armored MiniSplit Cable250 ft roll	SW144-250
	14 Gauge 4 wire Armored MiniSplit Cable50 ft roll	SW144-50
Mounting Pad	Condensing Unit Mounting Pad 24 x 42 x 3	ULTRILITE2
Snow/Rain Diverter	SnowRain Diverter	SRD-4
Stand	18 Single Fan Stand	QSMS1801M
	Outdoor Unit 3-14 inch Mounting Base Pair - Plastic	DSD-400P
	24 Single Fan Stand	QSMS2401M
	Condenser Wall Bracket	QSWB2000M-1
	Outdoor Unit Stand 12 High	QSMS1201M
	Condenser Wall Bracket - Stainless Steel Finish	QSWBSS
Terminal Signal Adapter	Connector and wire for On/Off and Fan command using CN32	PAC-715AD
	Connector and wire for On/Off and Error status using CN51 and CN52	PAC-725AD
Wind Baffle	Front Wind Baffle	WB-PA5
	Side Advanced Wind Baffle	WB-SD5
	Rear Wind Baffle	WB-RE5
Notes		

Specifications are subject to change without notice.

© 2026 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

INDOOR UNIT DIMENSIONS: PVA-AA30NL




Model	③Nominal Filter Size	Duct Connection
PVA-AA12NL	508×406.4×25.4 (20×16×1)	376×402 (14-13/16×15-7/8)
PVA-AA18NL		
PVA-AA24NL	508×508×25.4 (20×20×1)	477×402 (18-13/16×15-7/8)
PVA-AA30NL		
PVA-AA36NL	508×609.6×25.4 (20×24×1)	579×402 (22-13/16×15-7/8)
PVA-AA42NL		

Model	A	B	C	D	E	F	G	H	J	① Gas Pipe	② Liquid Pipe
PVA-AA12NL	402(17)	376(14-13/16)	281(11-1/8)	224(8-7/8)	1275(50-1/4)	680(26-13/16)	823(32-7/16)	735.5(29)	380(14-3/16)	12.7(1/2)	6.35(1/4)
PVA-AA18NL											
PVA-AA24NL	534(21)	477(18-13/16)	382.6(15-1/8)	286.5(10-1/2)	1378(54-1/4)	737(29-1/16)	935.5(37-9/16)	782(31-3/16)	481(18-3/16)	15.88(5/8)	9.52(3/8)
PVA-AA30NL											
PVA-AA36NL	635(25)	579(22-13/16)	484.6(19-1/8)	317.5(12-1/2)	1511(59-1/2)	798.5(31-7/16)	1063(41-1/2)	835.5(33-5/8)	563(22-3/16)		
PVA-AA42NL											

© 2026 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

OUTDOOR UNIT DIMENSIONS: PUY-AH30NL



1340 Satellite Boulevard Suwanee, GA 30024
Toll Free: 800-433-4822 · mitsubishicomfort.com

METUS_2026-09_PROPIN

Specifications are subject to change without notice.

© 2026 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.